

SUBJECT INDEX

ANALOG DEVICES' PARTS INDEX

■ ANALOG-DIGITAL CONVERSION

SUBJECT INDEX

A

- A-law, 3.26
 AA Alkaline Battery Discharge Characteristics, 9.197
 Aaron, M.R., 3.37
 Aasnaes, Hans Bent, 3.108
 Aavid 573300, 7.56
 AAVID Thermal Technologies, Inc., general catalog, 9.139
 Aavid TO-220, heat sink, 7.56
 Absorption, within shielding material, 9.149
 Absorptive switch, 7.79
 ACCEL Technologies, Inc., 9.213
 Accuracy:
 absolute, 2.97
 logarithmic DAC, 2.97
 relative, 2.97
 Acker, David E., 8.104
 ACLR, adjacent channel leakage ratio, 2.46, 2.57-58, 2.98
 ACPR, adjacent channel power ratio, 2.57-58, 2.98
 Acquisition time, 2.98, 7.102
 Active lowpass filter, audio DAC, 6.75-76
 AD2S90, integrated RDC, 3.103
 AD260, digital isolator, 9.114
 AD260/AD261:
 digital isolator,
 circuit, 9.114-115
 key specifications, 9.115
 AD261, digital isolator, 9.114
 AD376, 16-bit 20- μ s SAR ADC, 1.53
 AD390, quad 12-bit voltage output DAC, 1.50
 AD431, XFET, circuit, 7.25
 AD480, op amp, 4.12
 AD550, 4-bit binary-weighted μ DAC quad switch, 1.25, 1.38, 1.41, 3.15-17, 4.6
 AD558, 8-bit 1- μ s bipolar/IIL DAC, 1.50
 AD561, 10-bit 250-ns LWT current-output DAC, 1.38
 AD562, 12-bit 1.5- μ s DAC, 1.35, 1.38, 1.41, 1.42
 AD563, IC DAC, 1.41
 AD565:
 12-bit 200-ns LWT current-output DAC, 1.38, 1.39-40, 1.41
 circuit diagram, 1.36
 AD569, 16-bit segmented double-buffered voltage output BiCMOS DAC, 1.50
 AD570, 8-bit 25- μ s SAR ADC, 1.39
 AD571:
 10-bit 25- μ s SAR ADC, 1.38, 4.12
 diagram, 1.39-40
 AD572, 12-bit 25- μ s SAR ADC, 1.42-43, 4.6-7
 AD574:
 12-bit 35- μ s SAR ADC, 1.39-40, 1.51, 3.41, 4.12, 6.49
 block diagram, 1.40
 AD580, precision bandgap reference, with Brokaw cell, 7.5-6
 AD620:
 data sheet, 8.26
 overvoltage protection,
 circuit, 9.106
 CM clamping, 9.107
 precision in amp, 8.9
 AD629, high voltage in-amp, circuit diagram, 9.98
 AD670, 8-bit 10- μ s ADCPORT, 1.51
 AD671, 12-bit 2-MSPS ADC, 1.60
 AD673, 8-bit complete ADC, 1.51
 AD674, 12-bit 15- μ s ADC, 1.51
 AD768:
 16-bit BiCMOS DAC, 6.73
 data sheet, 6.77
 single-ended interface, diagram, 6.73
 AD770, 8-bit 300-MSPS flash ADC, 1.52
 AD797, low-noise buffer, 6.15-16
 AD815 high output current differential driver, data sheet, 9.139
 AD830, AD8129, AD8130, data sheets, 6.45
 AD850, thin-film resistor network, 1.25, 1.41, 3.16-17
 AD872:
 12-bit 10-MSPS BiCMOS sampling ADC, 1.63
 diagram, 1.61
 AD974, SAR ADC, 6.18
 AD976, SAR ADC, 6.18
 AD977, SAR ADC, 6.18
 AD76xx-family, single-supply SAR ADC, 6.18
 AD77xx-family:
 24-bit sigma-delta ADC, 3.126-127
 characteristics, 6.15
 equivalent input circuit, 6.16
 AD92xx-family, CMOS ADC, 6.29-30
 AD185x-family, audio DACs, data directed scrambling, 3.133
 AD746x-family, low voltage single-supply ADC, 6.18
 AD771x-series, 24-bit sigma-delta measurement ADC, 1.63
 AD789x-family, 12-, 14-bit 8-channel single-supply ADC, 6.18-19
 AD789x-series, LCCMOS SAR single-supply ADC, 1.62
 AD813x-family:
 differential amplifier, 6.75
 block diagram, 6.31
 configurations, 6.33-34
 feedback diagram, 6.31

■ ANALOG-DIGITAL CONVERSION

- AD813x-series, data sheets, 6.77
AD922x-family, single-ended DC-coupled level shifter and driver, circuit, 6.22-23
AD978x-series, 16-bit interpolating TxDAC family, key specifications, 8.135
AD985x, high speed DDS synthesizers, table, 8.171
AD1170, modular ADC, VFC architecture, 3.96
AD1175, 22-bit integrating ADC, 1.53-54
AD1332, 12-bit 125-kSPS sampling ADC, 1.53
AD1377, 16-bit 10- μ s SAR ADC, 1.53-54
AD1382, 16-bit 500-kSPS sampling hybrid ADC, 1.64
AD1385, 16-bit 500-kSPS sampling autocalibrated hybrid ADC, 1.64
AD1580:
 reference circuit, 7.7
 shunt mode IC reference, 7.6-7
AD1582-1585:
 bandgap references,
 circuit diagram, 7.9
 specifications, 7.8
 series connection diagram, 7.9
AD1671, 12-bit 1.25-MSPS BiCMOS sampling ADC, 1.63
AD1674:
 12-bit 100-kSPS sampling SAR ADC, 1.63
 diagram, 1.59
AD1839A:
 24-bit 96-kSPS sigma-delta codec, block diagram, 8.69
 data sheet, 8.74
AD1853:
 data sheet, 6.77
 sigma-delta audio DAC, 6.75-76
AD1856, 16-bit audio BiCMOS DAC, 1.50
AD1857, 16-bit serial sigma-delta audio DAC, 1.57-58
AD1858, 18-bit serial sigma-delta audio DAC, 1.57-58
AD1859, 20-bit serial sigma-delta audio DAC, 1.57-58
AD1860, 18-bit audio BiCMOS DAC, 1.50
AD1862, 20-bit DAC, diagram, 3.33
AD1865, dual 18-bit stereo DAC, 1.56
AD1871:
 24-bit 96-kSPS stereo multi-bit sigma-delta ADC, 3.124
 block diagram, 8.66
 digital filter, 3.126
 key specifications, 3.125
 data sheet, 8.74
AD1879, dual audio ADC, 3.123
AD1896:
 192-kHz stereo asynchronous sample rate converter, block diagram, 8.73
 data sheet, 8.74
AD1953:
 data sheet, 8.74
SigmaDSP 3-channel 26-bit signal processing DAC,
 block diagram, 8.68
 evaluation interface, 8.69
AD1955:
 16-/18-/20-/24-bit 192-kSPS sigma-delta DAC, 8.66
 functional diagram, 8.67
 schematic, 3.134
 data sheet, 8.74
AD1985, data sheet, 8.74
AD5170:
 8-bit two-time programmable digital potentiometer, block diagram, 8.54
 data sheet, 8.58
AD5172:
 data sheet, 8.58
 three-terminal potentiometer, 8.53
AD5172/AD5173, one-time-programmable digital potentiometer, block diagram, 8.53
AD5173, rheostat, 8.53
AD5231, 10-bit digital potentiometer, 5.11
AD5235:
 10-bit digital potentiometer, 5.11, 8.52-53
 block diagram, 8.52
 data sheet, 8.58
AD5245:
 data sheet, 8.58
 digital potentiometer bandwidth model, 8.55
AD5246, data sheet, 8.58
AD5247, data sheet, 8.58
AD5300, 8-bit buffered voltage output DAC, 8.42
AD5310, 10-bit buffered voltage output DAC, 8.42
AD5320:
 12-bit buffered voltage output DAC, 8.42-43
 diagram, 8.43
 data sheet, 8.48
AD5322:
 12-bit 100-kSPS dual DAC,
 block diagram, 6.63
 serial input interface, 6.62-64
 data sheet, 6.67
AD5340:
 12-bit 100-kSPS DAC,
 block diagram, 6.65
 parallel data interface, 6.64-65
 to ADSP-2189M, 6.65
 data sheet, 6.67
AD5379:
 14-bit 40-channel parallel/serial input voltage output DAC, diagram, 8.45
 data sheet, 8.48
AD5380, 40-channel multiple DAC, 1.65-66
AD5381, 40-channel multiple DAC, 1.65-66
AD5382, 32-channel multiple DAC, 1.65-66
AD5383, 32-channel multiple DAC, 1.65-66
AD5390, 16-channel multiple DAC, 1.65-66
AD5391, 16-channel multiple DAC, 1.65-66
AD5516:

- 12-bit 16-channel voltage output DAC, diagram, 8.44
 data sheet, 8.48
- AD5533B:
 32-channel precision infinite SHA, 8.45-46
 diagram, 8.46
 data sheet, 8.48
- AD5535, 32-channel 14-bit high voltage DAC, evaluation board, 9.210, 9.211
- AD5541, 16-bit DAC, 8.47
- AD5545/AD5555:
 16-/14-bit R-2R current-output DAC, 6.74
 interface circuit, 6.74
 data sheet, 6.77
- AD5570, data sheet, 8.48
- AD5660, data sheet, 8.48
- AD6521:
 voiceband/baseband mixed-signal codec, 8.141
 block diagram, 8.142
- AD6522, DSP-based baseband processor, 8.141
- AD6624/24A, 8.136
- AD6644, 14-bit 65-MSPS XFCB ADC, 3.85
- AD6645:
 14-bit 80-/105-MSPS ADC, aperture jitter, 6.83
 14-bit 80-/105-MSPS BiCMOS ADC, 6.27-28
 input common-mode voltage, 6.38-39
 RF transformers, 6.29
 transformer coupling, 6.28
 14-bit 80-/105-MSPS XFCB ADC, 4.12
 thermally enhanced package, 9.137
 14-bit 80-MSPS XFCB ADC, 3.77-78, 3.85
 characteristics, 2.51-53
 NF calculation, 2.64-66
 SFDR, 2.52, 2.56-57
 SNR versus jitter, 2.73
 wideband CDMA channel, 2.58
 14-bit 105-MSPS XFCB ADC, 1.65-66, 3.85,
 8.146
 aperture jitter, 6.97
 circuit, 7.107-108
 diagram, 3.78
 data sheet, 6.45
 signal sampling frequency, 8.125
 subranging pipelined ADC, 8.128
 dithered and undithered DNL, 8.128-129
 dithered and undithered SFDR FFT, 8.130
 DNL errors, 8.128
 two-tone intermodulation performance, 8.123
- AD7001, CMOS GSM baseband converter, 1.62, 1.63
- AD7008:
 10-bit 50-MSPS DDS DAC, 1.57
 diagram, 1.58
- AD7111:
 LOGDAC monolithic multiplying DAC, 2.112, 3.27
 diagram, 3.27
- AD7226, quad 8-bit double-buffered voltage output BiCMOS DAC, 1.50
- AD7240, 12-bit voltage mode CMOS DAC, 1.50
- AD7245, 12-bit double-buffered voltage output LCCMOS DAC, 1.50
- AD7450, 12-bit 1-MSPS ADC, evaluation board, 9.210
- AD7450A, 12-bit 1-MSPS 3-V ADC, 6.35
- AD7450A/AD7440, data sheet, 6.45
- AD7466:
 12-bit 200-kSPS SAR ADC, 6.17
 input circuit, 6.17
 timing diagram, 6.51
- AD7466/AD7467/AD7468, data sheet, 6.45, 6.67
- AD7467, successive approximation ADC, 6.17
- AD7468, successive approximation ADC, 6.17
- AD7520:
 10-bit 500-ns monolithic multiplying CMOS DAC, 1.36-37, 1.38, 4.13
 current-mode R-2R architecture, 1.36
- AD7524:
 8-bit 150-ns LWT multiplying DAC,
 buffer latch, 1.38
 diagram, 1.37-38
- AD7528, dual 8-bit buffered CMOS MDAC, 1.50
- AD7535, 14-bit double-buffered LCCMOS MDAC, 1.50
- AD7541, 12-bit 1- μ s LWT multiplying DAC, 1.36-37, 1.38
- AD7545, 12-bit buffered CMOS MDAC, 1.50
- AD7546, 16-bit segmented CMOS voltage mode DAC, 1.50
- AD7550, 13-bit quad slope ADC, 1.38, 1.140
- AD7568, 12-bit octal CMOS DAC, 1.56-58
- AD7570, 10-bit 20- μ s CMOS SAR ADC, 1.38, 1.40
- AD7572, 12-bit 5- μ s SAR LCCMOS ADC, 1.51
- AD7575, 8-bit 5- μ s SAR LCCMOS sampling ADC, 1.51
- AD7579, 10-bit 50-kSPS LCCMOS SAR sampling ADC, 1.51
- AD7582, 4-channel muxed input 12-bit CMOS ADC, 1.51
- AD7621, 16-bit 3-MSPS PulSAR ADC, 1.65-66, 3.61
- AD7664, 16-bit 570-kSPS ADC, 1.65
- AD7674, 18-bit 800-kSPS PulSAR ADC, 1.65-66, 3.61, 6.42-43
- AD7675, 16-bit 100-kSPS PulSAR ADC, 3.61
- AD7676, 16-bit 500-kSPS PulSAR ADC, 3.61
- AD7677:
 16-bit 1-MSPS PulSAR ADC, 3.61, 6.41-42
 diagram, 3.61
 data sheet, 6.45
- AD7678, 18-bit 100-kSPS PulSAR ADC, 3.61
- AD7679, 18-bit 570-kSPS PulSAR ADC, 3.61
- AD7730:
 24-bit bridge transducer sigma-delta ADC, 1.63
 evaluation board, 9.210
- 24-bit sigma-delta single-supply ADC, block diagram, 8.3

■ ANALOG-DIGITAL CONVERSION

- 24-bit single-supply sigma-delta ADC, 6.79
 - bridge application, 3.131
 - calibration modes, 3.130-131
 - design component, 8.10
 - design evaluation, 8.12
 - diagram, 1.62, 3.128
 - digital filter, 3.129, 8.4
 - external voltage reference, 3.131
 - high impedance input buffer, 6.15
 - internal digital filter, 3.128-129
 - key specifications, 8.5
 - oversampling, 3.128
 - ratioimetric operation and Kelvin sensing, 8.5
 - resolution, 8.10-11
 - settling time, 3.130
 - weigh scale analysis, 8.6, 8.6-12
- AD7730/AD7730L, data sheet, 8.26
- AD7739:
 - 24-bit sigma-delta ADC, 8.36-38
 - block diagram, 8.36
 - timing, 8.38
 - data sheet, 8.48
- AD7793:
 - data sheet, 8.26
 - dual channel 24-bit sigma-delta ADC, 8.12-14
 - block diagram, 8.13
- AD7820, 8-bit 1.36- μ s half-flash sampling ADC, 1.51
- AD7821, 8-bit 1-MSPS half-flash sampling ADC, 1.51
- AD7840, 14-bit double-buffered voltage output LCCMOS DAC, 1.50
- AD7846, 16-bit segmented voltage output LCCMOS DAC, 1.50
- AD7853/AD7853L:
 - 12-bit 200-/100-kSPS SAR ADC, 6.55
 - diagram, 6.55
 - interfacing, 6.56
 - data sheet, 6.67
- AD7853L, serial ADC output timing, 6.56
- AD7854/AD7854L:
 - 12-bit 3-V 200-/100-kSPS parallel output ADC, 6.59-61
 - block diagram, 6.59-60
 - data sheet, 6.67
- AD7865:
 - 14-bit 4-channel SAR ADC, 8.39-40
 - block diagram, 8.39
 - data sheet, 8.48
- AD7870, 12-bit 100-kSPS LCCMOS SAR sampling ADC, 1.51
- AD7871, 14-bit 83-kSPS LCCMOS SAR sampling ADC, 1.51
- AD7873:
 - 12-bit SAR ADC,
 - touchscreen digitizer, 8.102-103
 - application circuit, 8.103
- data sheet, 8.105
- AD7880:
 - 12-bit 66-kSPS LCCMOS sampling SAR ADC, 1.59, 1.63
 - diagram, 1.60
- AD7890, data sheet, 6.45
- AD7890-10, 12-bit 8-channel ADC, input circuit, 6.18-19
- AD7908/AD7918/AD7928:
 - 8-, 10-, 12-bit 1-MSPS successive approximation ADC, 8.34-35
 - block diagram, 8.34
 - data sheet, 8.48
- AD7938/AD7939:
 - 12-, 10-bit 1.5-MSPS successive approximation ADC, 8.35-36
 - block diagram, 8.35
 - data sheet, 8.48
- AD7943, multiplying DAC, 3.2
- AD8001, high speed current-feedback amplifier, evaluation board, 9.207-209
- AD8016:
 - 20-lead PSOP3 package, heat sink, 9.131
 - BATWING package, 9.131
 - PSOP3 package, 9.130
- AD8016 low power high output current xDSL line driver, data sheet, 9.139
- AD8017 dual high output current high speed amplifier, data sheet, 9.139
- AD8017AR:
 - 8-pin SOIC op amp,
 - maximum power dissipation data, 9.127-128
 - Thermal Coastline IC package, 9.130
 - thermal rating curves, 9.129
- AD8021:
 - data sheet, 6.45
 - op amp, 6.41-43
- AD8027, data sheet, 6.45
- AD8027/8028, op amp family, pin-selectable crossover threshold, 6.8
- AD8031, 6.43
- AD8038, differential amplifier, 6.37
- AD8055, dual supply op amp, 6.72, 6.74
- AD8055/AD8056, data sheet, 6.77
- AD8057:
 - high speed op amp, 6.12
 - distortion versus frequency, 6.14
 - distortion versus output voltage, 6.15
 - key specifications, 6.13
 - thermal ratings, 9.133-134
- AD8057/AD8058, data sheet, 6.45
- AD8058:
 - dual high speed op amp,
 - ADC driver, 6.29-30
 - distortion versus frequency, 6.14
 - distortion versus output voltage, 6.15
 - key specifications, 6.13
 - thermal ratings, 9.133-134
- AD8061:
 - data sheet, 6.77

- op amp, 6.72-73
 - rail-to-rail output, 6.23
- AD8108/AD9109, crosspoint switch, 7.82
- AD8110/AD8111, buffered crosspoint switch, 7.82
- AD8113, audio/video crosspoint switch, 7.82
- AD8114/AD8115, crosspoint switch, 7.82
- AD8116:
 - buffered video crosspoint switch, 7.82-83
 - diagram, 7.83
- AD8130, differential receiver, 6.34
- AD8131, AD8132, AD8137, AD8138, AD8139, data sheets, 6.45
- AD8132, differential ADC driver, 6.35
- AD8137, differential amplifier, 6.35
- AD8138:
 - differential ADC driver, 6.36-37
 - noise calculations, 6.37
- AD8139:
 - differential amplifier, 6.38-39, 6.42-44
 - DC coupled driver for ADC, circuit, 6.39
- AD8152:
 - 3.2-Gbps asynchronous digital crosspoint switch, 7.83-84
 - circuit, 7.84
- AD8170, bipolar video multiplexer, 7.80
- AD8174, bipolar video multiplexer, 7.80
- AD8180, bipolar video multiplexer, 7.80
- AD8182, bipolar video multiplexer, 7.80
- AD8183, video multiplexer, 7.80-81
- AD8183/AD8185, triple 2:1 video multiplexers, 7.81
- AD8185, video multiplexer, 7.80-81
- AD8186, single-supply video multiplexer, 7.80-81
- AD8187, single-supply video multiplexer, 7.80-81
- AD8346, quadrature modulator, 4.25
- AD8349, 800-MHz to 2.7-GHz quadrature modulator, 8.134-136
- AD8351:
 - data sheet, 6.45
 - single-ended to differential converter, 6.40
 - key features, 6.39-40
 - performance, 6.40
- AD8370:
 - data sheet, 6.45
 - variable-gain-amplifier, 6.41
- AD8402, 2-channel 8-bit DAC, 1.58
- AD8403, 4-channel 8-bit DAC, 1.58
- AD8515, single-supply rail-to-rail op amp, 6.18
- AD8517, single-supply rail-to-rail op amp, 6.18
- AD8531/8532/8534, CMOS op amp family, 6.7
- AD8551, chopper-stabilized amplifier, 9.50
- AD8628:
 - chopper-stabilized op amp, 6.74
 - data sheet, 6.77
- AD8631, single-supply rail-to-rail op amp, 6.18
- AD8800, TrimDAC, 1.58
- AD9000, 6-bit 75-MSPS flash ADC, 1.52
- AD9002, 8-bit 150-MSPS flash ADC, 1.52
- AD9003, 12-bit 1-MSPS sampling ADC, 1.53
- AD9005, 112-bit 10-MSPS sampling ADC, 1.53-54
- AD9006/AD9016, 6-bit 500-MSPS flash ADC, 1.52
- AD9008, DDS DAC, 1.58
- AD9012, 8-bit 100-MSPS TTL flash ADC, 1.52
- AD9014, 14-bit 10-MSPS modular ADC, 1.64
- AD9020, 10-bit 60-MSPS flash ADC, 1.52
- AD9028/AD9038, 8-bit 300-MSPS flash ADC, 1.52
- AD9032, 12-bit 210-MSPS sampling ADC, 1.65-66
- AD9042:
 - 12-bit 41-MSPS ADC, 1.63, 1.64, 3.85, 4.12
 - circuit, 7.106-107
 - functional diagram, 1.61, 3.75
- AD9048, 8-bit 35-MSPS flash ADC, 1.52
- AD9054, 8-bit 200-MSPS ADC, 1.62
- AD9054A, 8-bit 200-MSPS MagAMP ADC, 3.86
- AD9058, dual 8-bit 50-MSPS flash ADC, 1.52
- AD9060, 10-bit 75-MSPS flash ADC, 1.52
- AD9220, 12-bit 10-MSPS CMOS ADC, 1.61, 1.63
- AD9221, 12-bit 1-MSPS CMOS ADC, 1.61, 1.63
- AD9223, 12-bit 3-MSPS CMOS ADC, 1.61, 1.63
- AD9225:
 - 12-bit 25-MSPS CMOS ADC, 6.20-21, 6.24
 - diagram, 3.76
 - single-ended input, 6.21
- AD9226, 12-bit 65-MSPS ADC, SINAD and ENOB, 2.49
- AD9229:
 - quad 12-bit 65-MSPS ADC, 6.52-53
 - serial outputs, 6.53
- AD9235:
 - 12-bit 20-/40-/65-MSPS ADC, 6.36-37
 - 12-bit 65-MSPS CMOS ADC, 3.69
 - diagram, 3.77
 - timing diagram, 3.70
 - data sheet, 6.45
- AD9236, 12-bit 80-MSPS ADC, sinewave histogram
- DNL and INL, 5.43-44
- AD9245:
 - 14-bit 80-MSPS 3-V CMOS ADC, packaging and heat sink, 9.135
 - power dissipation versus frequency, 9.134-135
- AD9289:
 - data sheet, 6.67
 - quad 12-bit 65-MSPS ADC, 6.52
 - timing diagram, 6.53-54
- AD9410, 10-bit 210-MSPS ADC, 3.51-53
- AD9430:
 - 12-bit 170-/210-MSPS BiCMOS ADC, 6.26-27, 6.57-59, 9.136-137
 - block diagram, 6.57-58
 - demuxed CMOS output timing, 6.59
 - diagram, 3.77
 - FIFO evaluation, FFT output, 5.61-62
 - LVDS driver, diagram, 9.176
 - NPR, 2.60, 5.70

■ ANALOG-DIGITAL CONVERSION

- packaging and heat sink, 9.136-137
- pipelined, 3.69
- supply current versus sample rate, 9.136
- timing, 6.58
- transformer coupling, 6.27
- 12-bit 210-MSPS ADC, 8.146
 - evaluation board, 9.211
 - data sheet, 6.45, 6.67
- AD9433, 12-bit 105-/125-MSPS BiCMOS ADC, 6.41
- AD9480, 8-bit 250-MSPS ADC, 3.49
- AD9700, 8-bit 125-MSPS video ECL DAC, 1.50
- AD9712, 12-bit 100-MSPS DAC, 1.57
- AD9720, 10-bit 400-MSPS DAC, 1.57
- AD9726:
 - 16-bit 600+-MSPS DAC,
 - block diagram, 6.66
 - LVDS input, 6.66
 - data sheet, 6.67
- AD9744, 14-bit 165-MSPS TxDAC, spectral output, 5.22-23
- AD9772A, data sheet, 6.77
- AD9773, 12-bit TxDAC, oversampling interpolating, 2.89
- AD9775:
 - 14-bit 160-/400-MSPS TxDAC, 3.22
 - CMOS DAC core, structure, 3.22
 - oversampling interpolating, 2.89
- AD9777:
 - 16-bit 160-MSPS TxDAC,
 - oversampling interpolating, 2.89
 - power dissipation, 9.138
 - SFDR, 2.84-86
 - smart partitioning, diagram, 4.25
- AD9786, 16-bit 160-MSPS TxDAC, block diagram, 8.134
- AD9814, 14-bit 3-channel CCD front-end, 8.99
- AD9816, 12-bit 3-channel CCD front-end, 8.99
- AD9822, 14-bit 3-channel CCD front-end, 8.99
- AD9826, 16-bit 3-channel CCD front-end, 8.99
- AD9833, low power 50-MSPS DDS synthesizer, key features, 8.167
- AD9834:
 - low power 50-MSPS DDS synthesizer,
 - block diagram, 8.167
 - key features, 8.167
- AD9850, 10-bit 125-MSPS DDS DAC, 1.57
- AD9851, 10-bit DDS DAC, spectral outputs, 5.22
- AD9857:
 - 14-bit 200-MSPS quadrature digital upconverter, 8.173
 - block diagram, 8.173
- AD9858:
 - 10-bit 1-GSPS DAC DDS, 1.65-66, 8.168-171
 - block diagram, 8.169
 - key specifications, 8.170
 - single loop upconversion, 8.170
- AD9860/AD9862:
 - mixed-signal front end,
- broadband communications, 4.29
- for broadband wireless OFDM modem, 4.29
- AD9877/AD9879, set-top box mixed signal front end, 4.25
- AD9887A:
 - 8-bit 170-MSPS dual flat panel interface,
 - functional diagram, 8.93
 - data sheet, 8.105
- AD9888:
 - 8-bit 100-/140-/170-/205-MSPS analog flat panel interface, diagram, 8.92
 - data sheet, 8.105
- AD9898:
 - CCD signal processor, block diagram, 8.99
 - data sheet, 8.105
- AD9954:
 - 14-bit 400-MSPS 1.8-V DDS, 8.171-172
 - block diagram, 8.172
 - key specifications, 8.172
- AD10242, dual 12-bit 41-MSPS AD9042 ADCs, 1.64
- AD10678, 16-bit 65-/80-/105-MSPS multichip ADC, 1.65-66
- AD12400:
 - 12-bit 400-MSPS ADC, 1.65-66, 8.152-155
 - Advanced Filter Bank, 8.152-154
 - block diagram, 8.153
- AD74122:
 - 16-/20/24-bit 48-kSPS stereo voiceband codec, 8.65
 - block diagram, 8.65
 - data sheet, 8.74
- AD20msp430:
 - chipset, composition, 8.141
 - SoftFone chipset, 8.140-141
- AD1671, 12-bit 1.25-MSPS sampling BiCMOS ADC,
 - diagram, 1.60
- Adage, 1.21, 1.23-24
- Adams, R., 3.137
- Adams, Robert, 3.137
- Adams, Robert W., 3.36, 3.137
- Adams, R.W., 3.137
- ADC:
 - 1-bit comparator, 3.42-45
 - 3-bit binary ripple, input and residue waveforms, 3.80
 - 3-bit folding,
 - based on Chasek design, 3.83
 - single-ended waveforms, 3.83
 - block diagram, 3.82
 - input and residue waveforms, 3.82
- 3-bit serial-binary, diagram, 3.80
- 5-bit counting, 3.88
 - developed by Reeves, 1.9
 - Reeves, 3.88
- 6-bit subranging error corrected,
 - diagram, 3.68
 - diagrams, 3.66

- 7-bit 9-MSPS recirculating pipelined, diagram, 3.74
 7-bit pipelined, proposed, 3.75
 8- to 16-bit, theoretical maximum NPR, 2.60
 10-, 11-, 12-bit, theoretical NPR, 2.59
 12-bit,
 noise floor, 2.43
 testing methods, 5.33
 16-bit, requires 16-bit driver, 6.42
 16-bit sigma-delta, 1.51
 50-kSPS vacuum-tube based, 1.21
 absolute accuracy, 2.97
 analog bandwidth, 2.50
 using FFT, 5.75
 analog input, high frequency BER test, 2.80
 analog signal, BER test, 2.79
 analyzer configuration file, inputs, 5.62
 aperture delay time, 5.73
 aperture jitter, 6.83
 locked-histogram test method, 5.70-72
 using FFT, 5.73-75
 architecture, 3.39-108
 counting and integrating, 3.87-103
 timeline, 3.87
 design issues, 3.78
 audio, high performance, 8.66-69
 back-to-back static testing, 5.31-33
 BER, 2.76-80, 3.45, 5.83-86
 testing, 2.77-78, 5.83
 BiCMOS, 6.5
 binary, single-stage transfer function, diagram, 3.79
 bipolar process, 6.1
 bit error rate, 2.76-80
 buffered differential input, 6.26
 buffering, against logic noise, 9.60-62
 charge run-down, 3.89
 code center, 5.28, 5.29-30
 code density test,
 code density test, 5.40
 DNL integration, 5.40
 linear ramp input, 5.38-44
 code transition noise, 5.38
 code transition points, test setup, 5.29-30
 combined pipelined and multibit, diagram, 3.71
 conversion using one stage per bit, 3.78
 counting and integrating, 3.87-113
 architecture timeline, 1.29
 crossplot measurements, linearity, 5.33-35
 crossplot test, 5.34
 static errors, major code transitions, 5.35
 differential amplifier,
 driving, 6.29-44
 fully integrated driver, 6.31-34
 differential gain, 5.78-83
 differential input,
 driver, 6.23-29
 drivers, 6.35-44
 integrated differential driver, 6.35-44
 single-ended circuits, driving, 6.21-23
 switched capacitor, driving, 6.19-23
 differential nonlinearity, details, 2.18
 differential phase, 5.78-83
 digital interface, 6.47-67
 digital output, grounding, 9.37-38
 digitally corrected subranging, 3.65
 drive circuit, 6.2
 driver,
 differential amplifier, 6.29-44
 selection criteria, 6.3
 driving, 6.15-44
 dual slope,
 diagram, 3.96
 integrator output waveforms, 3.97
 dual slope/multi-slope, 3.96-98
 dynamic performance analysis, 2.42
 dynamic range, 6.1
 dither, 8.126-131
 increasing using dither, 8.126-131
 dynamic testing, 5.45-86
 back-to-back, 5.45-49
 setup, 5.45
 FFT, basics, 5.51-59
 manual, 5.45-49
 manual "back-to-back", 5.45-49
 ENOB using sinewave curve fitting, 5.49-50
 error corrected, 3.61-78
 external reference, diagram, 3.39
 feedback subtraction, 1.28, 3.54
 FFT analysis, 2.41
 flash, 1.40, 3.46-53
 4-, 6-, 8-bit monolithic, 1.41
 8-bit 20-MSPS, SHA, 2.26
 monolithic, 1980s, 1.52-53
 PCM patent, 1.6
 folding, 3.78-87
 function, 2.1
 gain and ENOB versus frequency, 2.50
 generalized bit-per-stage architecture, diagram, 3.79
 grounding, 9.30
 high-impedance differential input, transmission accuracy, 9.52
 high-resolution, using VFC and frequency counter, 3.92
 high-speed,
 architectures, 3.46-87
 timeline, 1.29, 3.87
 back-to-back testing, 5.46
 CMOS latched buffer, 9.61-62
 pipelined, CMOS process, 4.15
 histogram test, linear ramp input, 5.38-44
 hybrid,
 1970s, list, 1.43
 1980s, 1.53-54
 1990s, 1.64
 hybrid and modular,

■ ANALOG-DIGITAL CONVERSION

- 1980s, 53-54
- 1990s, 1.64
 - high performance, 1980s, list, 1.53
 - ideal bipolar, transfer function, 2.10
 - input and output, definition, 2.1
 - input impedance, equal to source resistance, 2.62
 - input protection, circuit, 9.109
 - integrating, frequency response, 3.98
 - integrating and counting, 3.87-113
 - linearity,
 - crossplot measurements, 5.33-35
 - testing methods, 5.46
 - metastable states, 2.76-80
 - modular,
 - 1980s, 1.53-54
 - 1990s, 1.64
 - early 1970s, 1.44
 - monolithic,
 - 1970s, 1.38-40
 - summary, 1.40
 - 1980s, 1.51
 - list, 1.51
 - 1990s, 1.59-64
 - list, 1.63
 - multistage subranging, design, 3.78
 - N-bit two-stage subranging,
 - diagram, 3.62
 - residue waveforms, 3.63
 - noise, 2.43-45
 - noise and distortion sources, 2.44
 - noise figure,
 - model, 2.61
 - oversampling and process gain effects, 2.65
 - from SNR, sampling rate, and input power, 2.64
 - summary, 2.68
 - non-monotonic, missing code, 2.19
 - non-monotonicity, 2.18-19
 - trimming, 2.19
 - nonlinearity, using beat frequency and envelope tests, 5.49
 - Nyquist-type, 8.1
 - offset and gain error, measurement, 5.31
 - optical converter, 3.98-99
 - output, error codes, 2.76
 - overvoltage recovery time, 5.77-78
 - parallel output interface, 6.51, 6.57-61
 - timing, 6.57
 - pipelined, 2.113, 3.61-78, 6.49-50
 - 1-bit per stage, diagram, 3.72
 - 1.5-bit per stage:
 - error corrected range, 3.73
 - residue waveform, 3.73-74
 - error correction, 3.72
 - stages, diagram, 3.71
 - timing diagram, 3.69
 - power meter, application, 8.22-25
 - power-saving modes, 3.41
 - practical, noise, 2.43-44
 - processing gain, FFT output, 5.55
 - quantization noise, 2.37-45
 - quantization uncertainty, 5.28
 - ramp run-up, 3.89-90
 - recirculating subranging, 3.74
 - reference input terminal, buffered, 3.40
 - reference value, 3.39
 - reference with buffer, diagram, 3.40
 - relationship to DAC, 2.1
 - resolver-to-digital converter and synchro, 3.99-103
 - sampling, 2.112, 7.92
 - internal SHA, 9.30
 - sample-and-hold function, 5.45
 - simultaneous sampling system, 8.39
 - sampling clock input, 3.41
 - SAR, 3.91, 6.50
 - algorithm, 3.57
 - algorithm analogy, 1.27
 - development summary, 1.28
 - diagram, 1.28
 - fundamental timing, diagram, 3.53-54
 - switched capacitor DAC, 3.55
 - timing, 3.54-55
 - serial bit-per-stage binary and Gray-coded, 3.78-87
 - serial interface to DSPs, 6.55-56
 - serial output interface, 6.51-54
 - servo-loop tester, computer-based, 5.36-38
 - servo-loop transition test, 5.35-36
 - settling time, 2.112, 5.76-77
 - SFDR, 2.41
 - sigma-delta, 2.112
 - architecture timeline, 1.30
 - digital filter, 2.74
 - high resolution, 3.127-131
 - driving, 6.15-16
 - high speed clock, 9.30
 - performance:
 - chop mode disabled, 8.183
 - normal, 8.182
 - switched capacitor input, circuit, 7.22
 - synchronization, 8.40
 - sign-magnitude, 2.15
 - single-supply,
 - CMOS, 6.5
 - driver, fundamental application circuit, 6.4
 - input protection, circuit, 9.109
 - scaled input, driving, 6.18-19
 - SNR, 2.63
 - sampling clock jitter, 5.60
 - sparkle codes, 2.76-80
 - specifications, 5.27-28
 - static, 5.28-44
 - back-to-back, testing, 5.32
 - testing, 5.28-44
 - static transfer, DC errors, 2.12-21

- subranging, 1.53-54, 2.19, 2.113, 3.11, 3.61-78
 - improper trimming, errors, 2.20
 - missing codes, 3.63
 - pipeline stage design, 3.67-68
- successive approximation, 3.11, 3.53-61, 3.91
 - 5-bit 8-kSPS, 3.58
 - dynamic transient loads, 7.23-24
 - single-ended input, driving, 6.17-18
- superposition, 5.34
- testing, 5.27-91, 5.28
 - back-to-back static, 5.31-33
 - dynamic, 5.45-86
 - FFT, 5.51-59
- time-interleaved, block and timing diagrams, 8.147
- total effective input noise, from SNR, 2.63
- total SNR, equation, 2.72-73
- tracking, 3.90-91
- transfer function,
 - endpoint measurement, 5.35
 - referred noise, 5.37
- transient response, 2.73-74, 2.73-75
- trimmed, 3.39
- unipolar, transfer function, 2.5
- video testing, 5.78-83
- voltage-to-frequency converter, 3.91-96
- ADC-12QZ:**
 - 12-bit 40- μ s SAR ADC, 1.44, 1.46
 - quad-switch ICs, 4.6
- ADC-12U**, 12-bit 10- μ s SAR ADC, Pastoriza, 1.24-25
- ADC analyzer software:**
 - Coherent Sampling Calculator, 5.63
 - single-tone input, 5.65
 - two-tone input, 5.65
- ADC/DAC**, DNL errors, 2.47
- ADC FIFO evaluation kit**, ADC evaluation boards, 9.211-212
- ADC80**, 12-bit 25- μ s SAR ADC, 1.43
- ADC1130**, 14-bit 12- μ s SAR ADC, 1.46
- ADC1140**, 16-bit 35- μ s SAR ADC, 1.53
- ADE775x-series**, energy-metering IC, 1.63
- ADE7755:**
 - data sheet, 8.26
 - energy metering IC, 8.23-25
 - block diagram, 8.23
 - current and voltage sense connections, 8.25
 - pulse output, 8.24
- ADF4360:**
 - PLL with internal VCO, 6.93
 - phase noise and jitter, 6.93
- ADG200-series**, switches and multiplexers, 7.62
- ADG201-series**, switches and multiplexers, 7.62
- ADG439F**, trench-isolated multiplexer, 7.89
- ADG465:**
 - channel protector IC, circuit diagram, 9.98
 - single channel protector, 9.110
- ADG466**, triple channel protector, 9.110-111
- ADG467**, octal channel protector, 9.110
- ADG508F**, trench-isolated multiplexer, 7.89
- ADG509F**, trench-isolated multiplexer, 7.89
- ADG528F**, trench-isolated multiplexer, 7.89
- ADG708:**
 - 8-channel multiplexer,
 - crosstalk versus frequency, 7.72
 - off-isolation versus frequency, 7.68
- ADG801/ADG802**, CMOS switch, resistance versus input, 7.64
- ADG918**, absorptive CMOS switch, 7.79
- ADG919**, reflective CMOS switch, 7.79
- ADG32xx-series**, bus switches, 7.84
- ADG324x-series**, unidirectional interfaces, 9.191
- ADG3231:**
 - low-voltage bus switch, 9.188-189
 - low voltage logic level translator, diagram, 9.191
- ADG3233:**
 - low voltage logic level translator and bypass switch, 9.191-192
 - functional block diagram, 9.192
 - modes, 9.193
- ADG3246:**
 - bus switch,
 - hot-plug application, 9.194
 - hot swapping, 9.194
- ADG3257:**
 - quad 2:1 Mux/Demux bus switch, 9.186-188
 - eye diagrams, 9.188
 - maximum pass voltage versus input voltage, 9.188
 - resistance versus input voltage, 9.187
- Adjacent channel leakage ratio, 2.57-58, 2.98
- Adjacent channel power ratio, 2.57-58, 2.98
- Adler, Joseph V., 6.98
- ADM1023:**
 - data sheet, 8.26
 - microprocessor temperature monitor, 8.19-22
 - block diagram, 8.21
 - input conditioning circuits, 8.20
 - key specifications, 8.22
 - on-chip temperature sensor, 8.21
- ADM3311E RS-232 Port Transceiver**, data sheet, 9.126
- ADP33xx-series**, LDO architecture, diagram, 9.70
- ADP330x family:**
 - anyCAP topology, 7.40-41, 7.43
 - merged amplifier-reference design, 7.40-41
- ADP333x family:**
 - anyCAP topology, 7.40
 - merged amplifier-reference design, 7.40-41
- ADP3300:**
 - basic 50-mA LDO regulator circuit, 7.46
 - evaluation board, capacitor size, 7.48
- ADP3310:**
 - anyCAP LDO regulator controller, current limiting, 7.57

■ ANALOG-DIGITAL CONVERSION

- features, 7.52
- functional diagram, 7.52-53
- LDO linear regulator controller, 9.79-80
- ADP3310-3.3, fixed-voltage LDO controller, 9.77-78
- ADP3310-5, PMOS FET LDO regulator controller, circuit, 7.53
- ADP3331, LDO, adjustable, 9.73
- ADP3605, voltage inverter, 9.76
- ADP3607:
 - voltage doubler, 9.76
 - functional diagram, 9.76
- ADP3607-5, charge-pump, application circuit, 9.77
- ADR01/ADR02/ADR03, data sheet, 6.77
- ADR39x:
 - bandgap reference specification, 7.10
 - connection diagram, 7.10
- ADR290-ADR293 series:
 - circuit, 7.12
 - specifications, 7.13
- ADR430-ADR439 series, specifications, 7.13
- ADR510, shunt reference, 7.5
- ADR512, shunt reference, 7.5
- ADSP-2106L, SHARC DSP, 9.170
- ADSP-2189, 75-MHz DSP, 6.60-61
- ADSP-2189M:
 - data sheet, 6.67
 - DSP, 6.55-56
- ADSP-21160, SHARC with internal PLL, 9.43
- ADT1-1WT, Mini-Circuits RF transformer, 6.26-27
- ADT4-1WT, Mini-Circuits RF transformer, 6.24-25
- ADT7301:
 - 13-bit digital temperature sensor, 8.17-19
 - circuit, 8.18
 - key specifications, 8.18
 - data sheet, 8.26
- ADu7xxx-series, microconverter, based on ARM7 processor, 8.187-190
- ADuC-series, MicroConverters, 1.65-66
- ADuC70xx-series, development system, 8.189
- ADuC702x-series, ARM7-based MicroConverters, 8.188
- ADuC812 MicroConverter, precision analog microcontroller, 1.63
- ADuC814, reduced pin-count low cost SAR MicroConverter, diagram, 8.179
- ADuC834, MicroConverter, in bridge transducer, 8.184-185
- ADuM1100A:
 - digital isolator, 9.112-114
 - characteristics, 9.113
- ADuM1100B:
 - digital isolator, 9.112-114
 - characteristics, 9.113
- ADV453, video RAM-DAC, 1.50
- ADV471, video RAM-DAC, 1.50
- ADV476, video RAM-DAC, 1.50
- ADV478, video RAM-DAC, 1.50
- ADV7125:
 - data sheet, 8.105
 - triple 8-bit 330-MSPS DAC, 8.88-89
 - functional diagram, 8.89
- ADV7160/ADV7162:
 - 220-MSPS video RAM-DAC, diagram, 8.90
 - data sheet, 8.105
- ADV7183A:
 - 10-bit video decoder, 8.82-83
 - block diagram, 8.83
 - data sheet, 8.104
- ADV7310:
 - 12-bit video encoder, 8.83-84
 - block diagram, 8.84
 - data sheet, 8.104
- Advanced digital post processing, 8.151
- Advanced filter bank, 8.146, 8.151-155, 8.152
 - block diagram, 8.152
 - design, 8.152-155
 - digital post-processing, 8.151-155
- Advanced Filter Bank technical description, 8.157
- Advanced Micro Devices, 1.25, 1.28, 1.33, 1.40, 1.45, 1.52
- Advanced Mobile Phone Service, 8.108
- AFE, 1.66
- Agilent Labs, 8.146
- Agilent press release, 8.157
- Aging, resistor, 9.14
- Air-gap discharge, ESD testing, 9.121
- Akazawa, Yukio, 2.90, 3.105
- Alfke, P., 9.197
- Aliasing, 2.26, 2.98
 - in direct digital synthesis, 8.163-165
 - implications;, 2.27
 - in time domain, 2.28
- All-0s, all bits off, 2.105
- All-1s, all bits on, 2.104
- All bits off, 2.105
- All bits on, 2.104-105
- All-parallel ADC, 3-bit converter, 3.46
- Aluminum electrolytic capacitor, 9.8
- AM685, 1.40
 - ECL latched comparator, 3.43-44
 - IC comparator, 1.41
- AM685/687, 3.49-50
- AM687, 1.40
 - dual ECL comparator, 1.45
 - high-speed comparator, 3.63
 - IC comparator, 1.41
- AM6688:
 - 4-bit 100-MSPS flash ADC, 1.40, 1.45, 1.52
 - 4-bit 100-MSPS flash converter, Advanced Micro Devices Inc., 3.49
- Ammann, Stephan K., 3.108
- Amplifier:
 - differential,
 - fully integrated driver, 6.31-34
 - voltage levels, 6.32
 - feedback, patent, 1.14
 - intercept points, definition, 2.54

- output stages, 6.8-10
- performance, 6.3-15
- rail-rail input stages, 6.5-8
- Amplifier output:**
 - EMI/RFI, 9.162-163
 - voltage phase-reversal, 9.101-102
- AMPS wideband digital receiver, 8.117
- noise, 8.120
- sensitivity, 8.119
- spurious requirements, 8.118
- Analog bandwidth, 2.46, 2.98**
 - ADC, 2.50
 - data converter, 6.3
 - using FFTs, 5.75
- Analog computing circuitry, 2.2**
- Analog connector, high-end receiver, 8.81**
- Analog Devices, 1.33**
- Analog Devices, Inc., founding, 1.24
- Analog Dialogue, 1.47**
- Analog Dialogue magazine, 1.33-34**
- Analog-Digital Conversion Handbook, 1.34**
- Analog-Digital Conversion Notes, 1.34**
- Analog Front End, 1.66**
- Analog-front-end integrated devices, 8.99**
- Analog front ends, 1.55**
- Analog full scale, 2.14**
- Analog ground, in mixed-signal IC, 9.35**
- Analog ground plane, PCB, 9.37**
- Analog multiplexer, diagram, 8.28-31**
- Analog power supply, systems, 9.65-91**
- Analog switch:**
 - application, 7.73-78
 - dummy switch in feedback, 7.76
 - dynamic performance, 7.74
 - minimizing on resistance, 7.75-77
 - and multiplexer, 7.61-89
 - unity gain inverter, 7.74
- Analog-to-time conversion, using PTM, 1.8**
- Analog variable, 2.2**
- Analogic, 1.23**
- Analogic Corporation, 1.33**
- Analogic, Inc., 4.2**
- Anderson, Robin N., 3.108
- Andreas, D., 3.137
- Andrews, James R., 5.25
- Anti-ballistic missile system, 1.22-23**
- Anti-imaging filter, 8.163**
 - digital audio, 8.64
- Antialiasing filter, 2.29, 3.115**
 - design and requirements, 2.30
 - dynamic range, 2.30
 - elliptic, TTE Inc., 2.31
 - position, op amp noise, 6.38
 - transition band, 2.30
 - undersampling, 2.33-34
- anyCAP:**
 - design features, 7.40-42
 - functional diagram, basic LDO regulator, 7.45-46
- LDO regulator,**
 - functional diagram, 7.45
 - thermal considerations, 7.46-51
- LDO series devices, 7.43-44**
 - low current, 7.44
 - "paddle-under-lead" packaging, 7.50
 - thermal coastline packaging, 7.49
 - thermal performance, 7.48
- LDO topology, benefits, 7.43**
- low dropout regulator family, 7.39-51**
- pole-splitting topology, 7.42-43**
- pole splitting topology, 7.42-43**
- anyCAP LDO regulators, 9.70, 9.72**
- Aperture delay, 2.69**
 - sample-to-sample variation, 2.70
 - SHA, 7.96-97
- Aperture delay time, 2.68-72, 2.98**
 - ADC, 5.73
 - measurement, using locked-histogram test, 5.73
 - SHA, 7.96-97
- Aperture jitter, 2.68-72, 2.99, 6.83, 9.39**
 - ADC, locked-histogram test method, 5.70-72
 - calculation, using locked-histogram test, 5.72
 - degradation in SNR, 5.74
 - effects, 2.70
 - RMS noise, 5.72
 - sample-to-sample variation, 2.70
 - SHA, 7.97
 - test setup, 5.74
 - using FFTs, 5.73-75
- Aperture time, 2.68-72, 2.98**
 - SHA, 7.95
- Aperture time jitter, 1.49**
- Aperture uncertainty, 2.99**
 - SHA, 7.97
- ARM7, TDMI microcontroller, 8.141**
- ARM7TDMI, MCU core, 8.187**
- Armstrong, Major Edwin H., 8.108
- Aspinall, D., 3.106, 7.111
- Asynchronous digital subscriber line, 9.194**
- Asynchronous VFC, 3.91**
- Audio, digitall, 8.59-74**
- Audio codec, multichannel, 8.69-70**
- Audio DAC, multichannel, 8.69-70**
- Audio DAC family, chart, 8.67**
- Audio Engineering Society, standards, 8.60**
- Audio Precision, 5.25**
- Audio Precision, System Two, analyzer, 5.19**
- Automatic zero, 2.99**
- Avalanche diode, 7.3**
- AWG2020, Tektronix, 5.17**
- AWG2021, Tektronix, 5.17**

B

- B4001 and B4003 common-mode chokes, 9.178**
- Back-to-back testing, ADC, for large-signal input, 5.48**
- Baird, Jon, 8.175
- Baker, Bonnie, 9.63

■ ANALOG-DIGITAL CONVERSION

- Baker, R. Jacob, 2.117, 3.140, 5.89, 5.91
Baldwin, Eugene E., 5.25
Ball-grid array, 1.55
Ball-grid-array, packaging, 4.17
Ball grid array package, 9.200
Ballistic trajectory computation, 1.21
Ball, W.W. Rouse, 1.32, 3.105
Bandgap reference, 6.80, 7.4-10
 basic, 7.4
 characteristics, 7.14
Bandpass filter, 5.70-72, 6.92
Bandpass sampling, 2.31-32
Bandpass sigma-delta ADC, 3.132-133
Bandwidth:
 aliasing, 2.98
 analog input small-signal, 2.99
 effective resolution, 2.99
 full-linear, 2.99
 full-power, 2.98, 2.99
 full width, 2.98
 sampling, rule, 2.32
Bardeen, J., 1.18, 4.9
Bardeen, John, 1.15, 4.3-4
Barnes, Erik, 8.105
Barney, K. Howard, 3.107
Barrow, Jeff, 9.63
Barr, P., 1.31, 5.87
Bartow, Doug, 8.105
Baseband antialiasing filter, 2.29-31
Baudon, J.M.E., 1.4
Baudot code, 1.3
BCD, coding scheme, 2.14
Beat frequency test:
 ADC linearity, 5.46-47
 test setup, 5.47
Beckman Instruments, 1.24
Bedingfield, Robert C., 1.23
Bell Laboratories, 1.14-16, 1.22-23, 4.3-4
Bell Labs, 7.91
 Gray code, 2.6
 nonlinear DAC, 3.26
Bell μ -255 standard, 3.26
Bell System, 1.3
Bell Telephone Laboratories, 1.10-11, 1.17, 8.59
Bell Telephone Labs, 3.109
Bell Telephone system, 4.1
Bell, Alexander Graham, 1.3, 1.17
Bell, Barry A., 5.25
Benjamin, O.J., 3.137
Bennett, W.R., 1.18, 2.37, 2.90
BER, 2.76-80, 3.45
 ADC, 2.76-80
 bit error rate, 2.76-80, 3.45, 5.83
 tests, 5.83-86
 high-frequency test, analog input, 5.84-85
 low-frequency test, analog signal, 5.84
PC-based test, test setup, 5.86
 tests, 5.83-86
and time between errors, 2.80
Best straight line method, integral linearity error measurement, 2.16
Best, R.E., 6.98, 8.175
Beyschlag Resistor Products, 9.24
Bias current, 2.99
BiCMOS, 1.49
Bin width, in FFT, 5.54
Binary code:
 shadow mask, 1.12
 unipolar, 2.4
Binary-coded decimal code, 2.11-12
 table, 2.12
Binary-coded shadow mask, 3.47
Binary number, 2.3
Binary ripple ADC, 3.81
Binary-to-Gray code, conversion, 2.8
Binary transfer function, 3.78
Binary-weighted DAC, 3.9-12
Binary-weighted voltage-mode DAC, 3.9
Bipolar code:
 4-bit converter, table, 2.9
 relationships, table, 2.11
Bipolar converter, 2.14-15
Bipolar mode, 2.100
Bipolar offset, 2.100, 2.110
Bipolar processes, 4.11
Bipolar zero error, DAC, 5.2-4
Bird's nest breadboard, 9.201
Bit error rate, see BER
Bit-per-stage ADC, 3.88
BJT RFI rectification, 9.157-158
 sensitivity, 9.159
Black, Harold S., 1.14, 1.18, 4.1, 4.9
Black, H.S., 1.11, 1.18, 2.90, 4.9
Blackman, window function, 5.57-58
Black, W.C., Jr., 8.157
Blair, Jerome, 5.89
Blanking, 1.53
Blattner, Rob, 7.60
Bleaney, B., 9.24, 9.63
Bleaney, B.I., 9.24, 9.63
Block conversion, 8.115
Blood, William R., Jr., 9.179
Bloomingdale, Cindy, 9.179
Bode plot, 7.67
Bogatin, Eric, 9.178, 9.179
Bondzeit, Frederick, 3.108
Bootstrapping, 7.103
Bordeax, Ethan, 9.181
Boser, B., 3.137
Bowers, G.G., 1.31
Boyce, David E., 5.89
BPF, bandpass filter, 3.132
Brahm, C.B., 3.111, 3.136
Brannon, Brad, 2.90, 6.98, 8.156, 8.157
Brattain, Walter, 1.15, 4.3-4
Brattain, W.H., 1.18, 4.9
Breadboarding, 9.199-213
 and prototyping, 9.199-213

- Bridge, ratiometric, 8.9
 Bridge output, 2.2
 Broadband aperture jitter, 6.83
 Brokaw cell, 7.5-6
 bandgap reference, 7.33-34
 Brokaw, A. Paul, 1.47, 4.19
 Brokaw, Adrian Paul, 1.47, 3.36
 Brokaw, Paul, 1.35, 1.40, 1.47, 3.18, 4.12, 7.26,
 7.60, 9.63, 9.91, 9.179
 Bruck, Donald B., 2.116, 3.139, 5.87, 5.90
 Bryant, James, 2.1, 2.37, 2.93, 3.1, 3.39, 3.108,
 3.109, 4.11, 4.19, 7.1, 9.1, 9.25, 9.30, 9.63, 9.93,
 9.125, 9.141, 9.178, 9.199
 Bryne, Mike, 9.126
 BTL, standards, 9.184
 Buchanan, James E., 9.23
 Bucklen, Willard K., 3.105, 8.104
 Buckley, Kevin, 8.105
 Buffer, ADC digital output, 9.37
 Buffer amplifier, 3.18-19
 Buffer latch, 1.35
 Buffering:
 AC analog outputs, 6.69-77
 ADC reference, 3.40
 BiCMOS ADC, 6.25-26
 complementary bipolar ADC, 6.25-26
 DAC analog output, 6.69-77
 internal, 6.1
 Bulk metal resistor, 9.16
 Buried Zener, 6.80, 7.11, 7.14, 7.16, 7.19
 Burkhardt, Andrew, 9.178
 Burr Brown, 1.23, 1.33
 Burst mode, 6.49-50
 Bus, 2.100
 Bus switch:
 advantages, 9.187
 hot swap and hot plug applications, 9.193-194
 low voltage, 9.190
 NMOS FET, for interfacing, 9.186-190
 Buss wire, 9.31
 Busy, ADC status, 3.41
 Butterworth filter, 2.30
 noise bandwidth, 2.62
 two-pole, SNR, 2.87
 Buxton, Joe, 9.93, 9.125, 9.178
 Bypass/decoupling, local high frequency, 9.89-90
 Byrne, Mike, 9.30
 Byte, 2.100, 2.112
 low, 2.100
- C**
- Cable:
 electrically long, 9.151
 electrically short, 9.151
 ground loops, in shielded twisted pair, 9.152
 improper use of shielding, 9.151
 mutual inductance, 9.19
 shielded,
 hybrid grounding with passive sensor, 9.153
 impedance-balanced drive, 9.154
 Cable driving, 9.1
 Cables and shields, 9.151-155
 Cage jack, 9.31, 9.205
 Calibration process, 4.8
 Candy, J.C., 2.116, 3.37, 3.112, 3.136, 3.137,
 3.139, 5.90
 Capacitance, 4.15
 parallel plates, diagram, 9.58
 Capacitance-coupled noise, reduction, 9.144-145
 Capacitive coupling:
 EMI path, 9.142
 equivalent circuit, 9.59
 Capacitive noise, 9.59, 9.59-60
 Capacitor, 9.2-8
 ceramic, 9.82, 9.84
 comparisons, 9.8
 decoupling, 9.36, 9.41, 9.43
 dielectric absorption, 7.101, 9.3-4
 circuit diagram, 9.3
 dissipation factor, 9.5-6
 electrolytic, 9.7, 9.82, 9.83
 equivalent circuit, 9.84
 failure mechanisms, 9.7
 film, 9.82, 9.83
 general purpose aluminum, 9.83
 leakage, 9.5
 materials, 9.2
 noise reduction, 9.82-85
 organic semiconductor, 9.83
 parasitic waveforms, 9.84
 parasitics, 9.2-3, 9.5-6
 passive component, 9.1
 polarized, 9.7
 power supply noise reduction and filtering,
 9.82-85
 series impedance, 9.5
 stacked-film, 9.83
 switching, 9.83
 tantalum, 9.83
 temperature, 9.6
 tolerance, 9.6
 types, 9.2, 9.4, 9.82
 Carbon composition resistor, 9.9, 9.16
 Carbrey, R.L., 3.37
 Card entry filter, 9.87-88
 circuit diagram, 9.87
 power supply noise reduction and filtering,
 9.87-88
 ringing, 9.87
 Carrier, and harmonic distortion, 2.48
 Cascaded network, two-stage, diagram, 2.67
 Cattermole, K.W., 1.2, 1.17, 2.22, 2.90, 2.116,
 3.139, 5.90
 CAV-1040, 10-bit 40-MSPS sampling ADC,
 1.53-54
 CAV-1220, 12-bit 20-MSPS sampling ADC,
 1.53-54
 Caveney, R.D., 3.106

■ ANALOG-DIGITAL CONVERSION

- CB, 3.85
- CB processes, 4.12
 - JFET used, 4.12
- CCD:
 - kT/C noise, 8.97
 - output stage and waveforms, 8.96
 - thermal noise, calculation, 8.97
- CCD array, linear and area, chart, 8.95
- CCD image processor, 1.55
- CCD imaging electronics, 8.94-99
- CDMA, spread-spectrum system, 8.112
- CDMA system, signals, chart, 8.123
- Çeçen, Kâzim, 1.17
- Cecil, Jim, 4.13
- Cell phone, handsets, 8.136-139
- Cellular radio system, 2.40
- Cellular telephone:
 - ADC and DAC, handsets, 8.139-145
 - handsets, 8.136-139
 - ADCs and DACs, 8.139-140
 - receiver, direct conversion architecture, 8.143
- Cellular telephone system, 8.108
- Ceramic capacitor, 9.82
- Chain code, 1.3
- Changeover switch, 3.3
- Channel protector, for dual-supply in-amp, circuit, 9.107
- Channel-to-channel isolation, 2.100, 2.102
- Channelizer, 8.115
- Charge-balance VFC, 3.91
 - diagram, 3.93
- Charge-coupled device, 8.94-99
- Charge coupling, 7.71
- Charge injection, 2.100
 - reducing, 7.104
- Charge injection model, 7.69
- Charge-pump circuit, 9.74
- Charge-pump voltage converter, 9.74-75
 - advantages, 9.74-75
 - characteristics, 9.75
 - regulated output, 9.75-77
- Charge run-down ADC, 3.89
- Charge transfer, 2.100, 2.111
- Charged Device Model, ESD model, 9.121
- Charpentier, A., 3.137
- Chasek, N.E., 3.82, 3.106
- Chesnut, Bill, 9.91
- Chip area, voltage tolerance/compliance, 9.196
- Chip enable, 6.57
- Chip-on-Lead packaging, 7.49-50
- Chip-scale package, 1.55
- Chip-scale-packaging, 4.17
- Chip Select, ADC edges, 3.42
- Chopper-stabilized amplifier, 8.20
- Chroma signal, 8.79, 8.82
- Chrominance, 5.78
- Circuit, effective input impedance, 6.32-33
- Circuit inductance, ground plane, 9.49
- Clamping diode:
 - leakage, 9.95-96
 - reverse bias current, 9.95
- Clamping diode leakage, 9.95-96
- Clelland, Ian, 9.91
- Clock distribution:
 - end-of-line termination, 9.174
 - source terminated transmission lines, 9.174
- Clock generator, "hybrid", 6.94-95
- Cloninger, Chris, 8.156
- Closed-loop SHA, circuit, 7.103-104
- CM choke, 9.146
- CM overvoltage protection:
 - amplifier output voltage phase reversal, 9.101-102
 - CMOS channel protectors, 9.98-99
 - high CM voltage in-amp, 9.99-100
 - inverting op amp, 9.100-101
- CMOS, 9.181
 - process, 4.13-15
 - standards, 9.184
- CMOS ADC:
 - differential input, transformer coupling, 6.25
 - equivalent input circuit, 6.19-23
 - SHA, 6.19-20
 - single-ended drive circuit, 6.21-23
- CMOS channel protector, 9.98
- CMOS IC output driver, configuration, 9.183
- CMOS logic, 1.41, 2.2
- CMOS process, 3.11
- CMOS processes, 4.13-15
- CMOS switch, 3.4, 5.35
 - 1-GHz, attributions, 7.78-79
 - absorptive, 7.79
 - adjacent, equivalent circuit, 7.65
 - basics, 7.62-64
 - charge injection, 7.69
 - charge injection effects, 7.70
 - complementary pair technology, 7.63
 - DC performance, factors, 7.66
 - diode protection, 7.87
 - dynamic performance,
 - charge injection, 7.69
 - off isolation, 7.68
 - transfer accuracy versus frequency, 7.67
 - error sources, 7.65-73
 - input protection, external Schottky diodes, 7.88
 - junction-isolation, cross-section, 7.86
 - latchup prevention, 7.87
 - MOSFET technology, 7.62-63
 - off isolation versus frequency, 7.68
 - on-resistance versus signal voltage, 7.64
 - overcurrent protection, 7.88
 - parasitic latch, equivalent circuit, 7.86
 - parasitic latchup, 7.85-89
 - reflective, 7.79
 - settling time, 7.72
 - single-pole, settling time, table, 7.73

- transfer function, Bode plot, 7.67
 trench-isolation technique, 7.89
 CMR, 2.101, 6.74
 input transient currents, 6.24
 Coaxial cable, 9.154
 shielding, 9.155
 Code:
 binary, unipolar, 2.4
 binary-coded decimal, 2.11-12
 binary-to-Gray, conversion, 2.8
 bipolar, 2.8-12
 offset binary, 2.8-9
 center, 2.4
 complementary, 2.12
 fractional binary, 2.3
 Gray, 2.4, 2.6-8
 Gray-to-binary, conversion, 2.8
 integer binary, 2.3
 meaning, 2.3
 missing, 2.107
 MSB, error, 2.7
 ones complement, 2.8, 2.11
 reflective-binary, 2.6
 resolution,
 flicker-free, 2.45
 noise-free, 2.45
 sign-magnitude, 2.8, 2.11
 sparkle, ADC, 2.76-80
 twos complement, 2.8, 2.9, 2.11
 unipolar, 2.3-5
 Code center, 5.28
 data converter, 2.14
 Code-center testing, misleading results, 5.29-30
 Code density test:
 ADC, 5.38-44
 data display, 5.39-40
 setup, 5.39
 Code-division-multiple-access, see CDMA
 Code resolution:
 flicker-free, 2.109
 noise-free, 2.106, 2.109
 Code transition noise, 2.100
 DNL, 2.20
 Code width, 2.100
 Codec, 1.55, 5.27, 5.78, 8.59, 8.61, 8.82
 voiceband, 8.65
 Coder-decoder, 1.55, 5.27
 Coding, quantizing, 2.1-22
 Coherent sampling, FFT output signal and
 harmonics, 5.63
 Cold junction compensation, thermocouple, 8.14
 Collins, Niamh, 8.175
 Color difference, 8.79
 Colton, Evan T., 1.32, 3.106
 Comfort noise insertion, 8.138
 Common-impedance, EMI path, 9.142
 Common-impedance noise:
 reducing, 9.143-144
 reduction, 9.143-144
 solutions, 9.144
 Common-mode choke, 9.162
 Common-mode error, 2.101
 Common-mode overvoltage protection:
 CMOS channel protectors, 9.98-99
 high CM voltage in-amp, 9.99-100
 Common-mode range, 2.101
 Common-mode rejection, see CMR
 Common-mode voltage, 2.101
 Compact PCI Hot Swap Specification R1.0, 9.197
 Companding, 3.26
 Comparator:
 1-bit ADC, 3.42-45
 in flash ADC, 3.46
 latched, 2.76
 metastability, 3.50
 metastable output states, error codes, 3.51
 metastable state errors, diagram, 3.45
 μA711/712, 3.49
 in parallel ADC, 3.46
 structure, 3.42
 diagram, 3.43
 Comparator ADC, 1-bit, 3.42-45
 Complementary bipolar, see CB
 Complementary bipolar processes, 4.12
 Complementary code, 2.12
 Compliance voltage, 6.71
 Compliance-voltage range, 2.101
 Complimentary metal oxide semiconductor,
 see CMOS
 Component analog video standard, 8.79-80
 Composite video signal, 8.79
 Composite video testing, test setup, 5.78
 Compound monolithic, 4.7-8
 Computer Labs, 1.23, 1.33
 Computer Labs, Inc., 1.24, 1.41, 1.43, 1.44,
 4.4-5
 Conduction, EMI path, 9.142
 Conductive wrist strap, for ESD protection, 9.120
 Conductor:
 ground plane, skin effect, 9.47
 Ohm's law, 9.27
 resistance, 9.26-27
 skin depth, 9.47
 Conductor resistance, in PCB, 9.26-27
 Connolly, J.A., 9.63, 9.125
 Contact discharge, ESD testing, 9.121
 Contact-image sensor, 8.94-99
 waveforms, 8.98
 Continuous-aperiodic signal, in FFT, 5.52
 Continuous-periodic signal, in FFT, 5.52
 Continuously available output, ADC, 3.91
 Continuously converting, temperature sensor
 output mode, 8.15-16
 Conversion complete, 2.101, 2.102
 Conversion rate, 2.101
 Conversion relationship, meaning, 2.3
 Conversion time, 2.101, 2.112
 Convert command, for ADC, 8.29

■ ANALOG-DIGITAL CONVERSION

- Convert-start command, ADC, 3.41
Converter:
 optical, 3.98-99
 sub-ranging, 2.104
Convolutional coding, 8.137
Conway, Paul, 8.191
Cooley, J.W., 5.89
Copper, resistance, 9.47
Copper conductor, resistance calculation, 9.26
Correlated double sampling, 8.97-98
Cost, 4.23
Counting ADC, 3.88
Counting and integrating ADC architectures, 3.87-113
Counting DAC, monotonic, 3.29
Counting pulse-width modulated DAC, 3.28-29
Counts, Lew, 9.23, 9.125, 9.178
Coupling, within signal cabling, 9.19
Coxeter, H.S.M., 1.32, 3.105
Craven, Bob, 1.35
Craven, Robert B., 1.47
Critical components, assembly, 9.7
Crook, David, 6.98, 8.175
Crosspoint switch:
 digital, 7.83-84
 video, 7.82-83
Crosstalk, 2.101-102, 7.71-72, 8.28
 adjacent switches, equivalent circuit, 7.72
 digital, 2.102
 noise interference, 9.144
Crystal oscillator, low phase jitter, 9.39
Crystal Oscillators: MF Electronics, 9.63
Crystal Oscillators: Wenzel Associates, Inc., 9.64
Crystal Semiconductor, 1.51
CSZ5316, monolithic sigma-delta ADC, 1.51
Current limiting, 7.30
Current-mode binary-weighted DAC, 3.10-11
Current output thermometer DAC, 3.7
Current-steering multivibrator VFC, 3.91
Current-steering VFC, diagram, 3.92
Curtin, Mike, 6.98, 8.175
Cushing, Richard, 8.175
Cutler, C.C., 3.109, 3.111, 3.136
Cyclic serial DAC, 3.29-31
- D**
- DAC:
 1-bit changeover switch, 3.4
 3-bit binary-decoded, linearity error, superposition, 5.9
 3-bit capacitor, 3.55-56
 3-bit nonideal,
 DNL and INL, superposition, 5.7
 transfer function, superposition, 5.6
 4-bit, DNL and INL, superposition, 5.7
 4-bit binary-decoded, superposition, bit tests, 5.8
 4-bit binary-weighted, R-2R ladder network, diagram, 3.16
 4-bit cyclic serial, diagram, 3.30
 5-bit binary-weighted, diagram, 3.9
 5-bit counting,
 developed by Reeves, 1.10
 diagram, 3.29
 6-bit binary-weighted, diagram, 3.10
 6-bit nonlinear segmented, characteristics, 3.27
 7-bit segmented, test codes, 5.12
 8-bit, 8-kSPS data converter, 3.26
 12-bit, sampling clock to output ratio, SFDR, 8.166
 12-bit current-output, with cascaded binary quad switches, diagram, 3.17
 12-bit monolithic, with quad switch, problems, 3.18
 architecture, 3.1-38
 low-distortion, 3.31-33
 monotonic, 3.4
 audio, high performance, 8.66-69
 basic structures, 3.3-4
 Kelvin divider, 3.4-6
 binary-weighted, 3.9-12
 currents switched to load, 3.14-15
 electro-mechanical, 3.9
 voltage-mode, 3.9
 bipolar process IC, 1970s, 1.34-36
 bipolar zero error, 5.2-4
 buffer, selection criteria, 6.3
 buffered reference input terminal, 3.2
 buffered reference output terminal, 3.2
 buffering analog output, 6.69-77
 capacitive binary-weighted, in successive approximation ADC, 3.12
 capacitive coupling, 3.34
 CMOS IC, 1970s, 1.36-38
 communications, 5.13
 compound monolithic, 1.35
 counting,
 monotonic, 3.29
 pulse-width modulated, 3.28-29
 current-mode, 3.12
 current-mode binary-weighted, 3.10-11
 current-mode R-2R ladder network, 3.14
 current output, general model, 6.70
 cyclic serial, 3.29-31
 DDS, distortion, 2.85
 deglitching, 7.93
 demultiplexed, data distribution, 8.41
 differential nonlinearity, 5.2, 5.5
 details, 2.18
 digital input interface, 6.61-66
 digital interface, 6.47-67
 digital output interface, 6.61-66
 distortion,
 measurement, 5.17-18, 5.17-24
 test setup, 5.18
 DNL, measurement, 2.17

DNL and INL,
 no superposition, 5.10-13
 via superposition, 5.6-10
 double-buffered, advantages, 3.33-34, 6.61-62
 dynamic performance, 81-89, 2.81-91, 5.13-25
 end-point errors, 5.2-5
 even harmonics, 5.23
 four-quadrant, 3.24
 full-scale settling time, measurement, 5.14
 fully decoded, 3.6-9
 no superposition, 5.10
 gain error, 5.1, 5.2-4
 glitch, 2.102
 glitch impulse area, 2.82-83, 5.15
 oscilloscope, 5.15-17
 grounding, 9.30
 high-speed,
 alternative loading, 3.35
 buffering using differential amplifier, 6.75
 clock rate, 3.34
 high speed,
 SFDR performance trends, 4.16
 update rate trends, 4.16
 high speed communication, CMOS process, 4.15
 history, hydraulic, 1.1
 hybrid,
 1970s, list, 1.43
 1980s, 1.53-54
 1990s, 1.64
 hybrid and modular,
 1980s, 53-54
 1990s, 1.64
 high performance, 1980s, list, 1.53
 hydraulic, 1.1
 ideal bipolar, transfer function, 2.10
 input and output, definition, 2.1
 integral nonlinearity, 5.1, 5.2, 5.5
 intentionally nonlinear, 3.25-26
 interpolating, oversampling, 2.87-89
 inverted mode, 3.12
 linearity error, 5.5
 superposition, 5.9
 logic, 3.33-35
 low distortion, 5.2
 mid-scale glitch, 2.83
 mid-scale settling time, measurement, 5.14
 modular,
 1980s, 1.53-54
 1990s, 1.64
 monolithic,
 1970s, summary, 1.38
 1980s, 1.49-51
 list, 1.50
 1990s, 1.56-58
 list, 1.58
 bipolar process IC, 1.34-36
 monotonicity, 5.1
 INL and DNL, 5.10
 multiple, data distribution, 8.41
 multiplying, 3.2, 3.24-25
 current-mode R-2R ladder network, 3.25
 diagram, 3.25
 non-monotonicity, 2.17
 nonlinear, 3.25-26, 3.28
 normal mode, 3.12
 odd harmonics, 5.24
 offset coding, bipolar zero error, 5.4-5
 offset error, 5.1, 5.2-4
 output, 3.3, 3.5
 deglitching, 3.32
 voltage or current, 3.3
 output settling time, 2.81-82
 output spectrum, $\sin(x)/x$ frequency rolloff, 2.87
 oversampling interpolating, 3.23-24
 diagram, 3.24
 patents, 3.23
 parallel input interface to DSP, 6.64-66
 R-2R, 3.12-18
 R-2R 3-bit binary, 3.26
 R-2R ladder,
 current mode, 3.14
 equal current sources, 3.14-15
 voltage mode, 3.13
 R-2R thin-film resistor, 3.11
 reference input terminal, buffered, 3.2
 reference output terminal, buffered, 3.2
 reference voltage, 3.2
 references, 3.1-2
 references and buffer, diagram, 3.3
 relationship to ADC, 2.1
 resolution, definition, 5.1
 segmented, 3.18-23
 all-codes testing, 5.11
 current-output, structure, 3.21
 voltage-output, 3.19
 serial input interface, 6.62-64
 to DSP, 6.62-64
 settling time, 2.81-82, 2.112, 5.13-14, 5.16
 oscilloscope, 5.15-17
 SFDR, measurement, 2.85, 5.19
 SFDR and SNR, 2.83-86
 sigma-delta, 3.33, 3.133-134, 5.12
 sign-magnitude, rare, 2.14-15
 skew glitch, 3.20
 SNR, measurement, analog spectrum analyzer, 2.86-87
 static error,
 basic test method, 5.1-2
 measurement methods, 5.1
 static linearity, testing, 5.12
 static transfer functions, DC errors, 2.12-21
 string, 3.4, 3.18
 INL trimming, 3.6
 no superposition, 5.10
 resistors, 3.6
 unbuffered, segmented, 3.19-20

■ ANALOG-DIGITAL CONVERSION

- superposition, 5.5-6
 - errors, 5.5
- testing, 5.1-25
 - dynamic performance, 5.13-25
 - static, 5.1-13
- thermometer, 3.4, 3.6-9
- two-quadrant, 3.24
- unipolar, transfer function, 2.5
- vacuum tube, binary, 3.9
- very high speed, 3.20
- voiceband and audio, 5.12
- voltage-mode, 3.12
- voltage-mode binary-weighted resistor, 3.10
- voltage-output thermometer, 3.4
- DAC-12QZ:
 - 12-bit DAC, 1.46
 - 12-bit modular DAC, 4.8
- DAC80, 12-bit DAC, 1.41-43
- DAC1138, 18-bit DAC, 1.46
- DAC08:
 - 8-bit 80-ns DAC, 1.38
 - 8-bit 85-ns IC DAC, diagram, 1.34
 - IC DAC, 1.41
- Daigle, Paul, 8.26
- Daisy chain, temperature sensor output mode, 8.15
- Daisy-chaining, 6.62
- Dammann, C.L., 3.37
- Damping resistors, high-speed DSP
- interconnections, 9.172
- Dark current, 8.95
- Dark signal, 8.95
- Darlington connection, 9.68, 9.70
- Darlington NPN, pass device, 7.31-33
- Data acquisition system:
 - on a chip, 8.34
 - on chip, 8.33-36
 - configurations, 8.27-28
 - filtering, 8.31-33
 - diagram, 8.31
 - multichannel, 8.27-48
 - design, 8.27
 - multiplexing, 8.28-31
 - PGA and SAR ADC, diagram, 8.29
 - timing diagram, 8.31
- Data converter:
 - 8-bit 10-MSPS, 1.23
 - 2000s, list, 1.66
 - absolute maximum ratings, 2.93
 - AC errors, 2.37-90
 - ADC transient response, 2.73-75
 - analog bandwidth, 2.50
 - analog full scale, 2.14
 - aperture time, delay, and jitter, 2.68-72
 - applications, 8.1-192
 - architectures, 1.27-30, 3.1-140
 - feedback subtraction, 1.27
 - bipolar processes, 4.11
 - code centers, 2.14
 - coding schemes, 2.14
- commercial,
 - 1950s, 1.21-22
 - history, 1960s, 1.22-26
- data sheet importance, 2.93, 2.95
- distortion, 2.47-48
- DNL error, 2.17
 - dynamic performance, 2.46-80
 - quantifying, table, 2.46
- dynamic performance specifications, 6.3
- early processes, 4.1-10
- ENOB, 2.48-50
- evaluation board, 9.209-212
- gain error, 2.15
- general specifications, 2.93-96
- high resolution, low noise references, 7.24-25
- high speed, CMOS process, 4.14
- history, 1.1-66, 5.27-28
 - 1950s, 1.21-22
 - 1950s and 1960s, 1.21-32
 - 1950s to 1960s, 1.21-32
 - 1970s, 1.33-47, 1.33-49
 - 1980s, 1.49-54
 - 1990s, 1.55-64
 - 2000s, 1.65-66
 - early, 1.1-19
 - telegraph to telephone, 1.3-5
- hybrid, 1.33, 4.3-8
 - 1970s, 1.41-44
- hybrid and modular components, 1970s, list, 1.41
- ideal N-bit, theoretical quantization
- noise, 2.37-43
- ideal transfer characteristics, 2.13-14
- integral and differential nonlinearity
- distortion, 2.46-47
- intercept points, 2.54-56
- interfacing, 6.1-98
- intermodular distortion, 2.53
- internal control registers, initialization, 6.48
- linearity errors, 2.15
- logic, 2.95-96
- logic interface issues, 2.94-95
- low power, sleep, and standby modes, 6.48-49
- measurement and control, 2.13
- modern, trends, 6.1-2
- modern processes, 4.11-19
- modular, 1.33, 4.3-8, 4.6
 - 1970s, 1.44-46
 - milestones, 1.46
 - monolithic, 1.33
 - 1970s, 1.34-40
 - monolithic DAC, 1980s, 1.49-51
 - multi-tone SFDR, 2.56-57
 - noise filter and noise figure, 2.61-68
 - NPR, 2.58-60
 - offset error, 2.15
 - overall considerations, 2.93-94
 - packages, examples, 4.18

- PCM, 1.5-6
 phase noise, 2.71
 popular reference options, 6.80
 power-on initialization, 6.47-48
 process technology, 4.1-30
 processes, summary, 4.15
 processes and architectures, 4.15-18
 summary, 4.18
 reconstruction systems, 2.13
 sampling frequency,
 burst mode, 6.49-50
 minimum, 6.49-50
 single-shot mode, 6.49-50
 sampling systems, 2.13
 SFDR, 2.51-53
 SINAD, 2.48-50
 SNR, 2.48-50
 solid state, 4.3-8
 specifications, 2.93-96
 definitions, 2.97-117
 specifications and testing, history, 5.27-28
 structure, 2.93
 supply current, 2.94
 support circuit, 7.1-112
 testing, 5.1-91
 THD, 2.47-48
 THD+N, 2.47-48
 theoretical quantization noise, 2.37-45
 thermal considerations, 9.134-138
 transfer functions, 2.17
 vacuum tube, 4.1-3
 voltage, 2.93
 voltage reference, 7.1-26
 voltage reference considerations, 6.81
 voltage references, 6.79-81
 wideband CDMA, 2.57-58
 worst harmonic, 2.47-48
 Data distribution system, 8.41-45
 with infinite SHA, 8.45-47
 multiple programmable voltage sources, 8.41
 Data ready, 2.101, 2.102, 6.57
 ADC status, 3.41
 Data valid, 6.57, 6.59
 Datel, 1.33
 DATRAC, 3.59-60
 11-bit 50-kSPS SAR ADC, picture, 3.60
 11-bit 50-kSPS vacuum tube converter, 5.27
 11-bit 50-kSPS vacuum tube SAR ADC, 4.2-3
 Datrac converter:
 11-bit 50-kSPS vacuum tube ADC, 1.22
 from Epsco, 1.21
 Dattorro, J., 3.137
 DCS, digitally corrected subranging, 2.113
 DDS, 1.57, 8.159-176
 aliasing, 8.163-165
 graph, 8.164
 anti-imaging filter, 8.163
 architecture, signal flow, 8.163
 digital dither, 8.166
 direct digital synthesis, 2.84
 flexible, diagram, 8.161
 frequency planning, 8.165-166
 for integrated DAC, 4.22
 low power 400-MSPS product family, table, 8.173
 modern integrated systems, 8.166-174
 schematic, 8.160
 tuning equation, 8.161
 DDS I/Q quadrature modulators, table, 8.174
 DDS synthesizers, low-power, chart, 8.168
 De Forest, Lee, 1.13, 1.18, 4.1, 4.9
 De Jager, F., 3.136
 Dead time, DAC, 2.81
 Deadbug prototyping, 9.200-202
 breadboard, 9.201
 power busses, 9.202
 short decoupling paths, 9.200
 DEC PDP minicomputer, 5.27
 Decimation, 3.111, 3.116
 GSM channel, 8.112
 Decimation filter, on ADC, 4.22
 Decoder, digital video, 8.81-84
 Decoupling, and grounding, diagram, 9.38
 Decoupling capacitor, 9.36, 9.41, 9.43
 Deglitcher, 2.102, 2.105
 Deglitching, 3.31-32
 Del Signore, B.P., 3.137
 Delay constant, microstrip, 9.167
 Deloraine, E.M., 3.109, 3.136
 Delta modulation, 3.109
 changes, 3.109
 for quantization, 3.110
 in sigma-delta ADC, 3.113
 versus differential PCM, scheme, 3.110
 Delta phase register, 8.160
 Delta-sigma architecture, 3.112-113
 Demler, Michael J., 2.116, 3.139, 5.88, 5.90
 Demodulation, 8.137
 analog, 2.32
 Dempsey, Dennis, 3.20, 3.37
 Demultiplexed data bus, 9.177
 Demuxed CMOS output data, 6.58
 Derating curves, 9.130
 Derjavitch, B., 3.109, 3.136
 Designing for EMC, 9.178
 Dickinson, Arthur H., 3.107
 Dielectric, PCB design, 9.165
 Dielectric absorption, 7.100-101, 9.3-4
 capacitor, 9.2
 PCBs, 9.57
 SHA applications, 9.4
 surface guarding, 9.57
 Dielectric hysteresis, 9.3
 Differential analog input capacitance, 2.102
 Differential analog input impedance, 2.102
 Differential analog input resistance, 2.102
 Differential analog input voltage range, 2.102
 Differential circuit, 9.28

■ ANALOG-DIGITAL CONVERSION

- Differential current-to-differential voltage conversion, 6.75
- Differential gain, 2.102, 5.78-83
 ADC, 5.78-83
 digital measurement, 5.81
 test signal, 5.80, 5.82
- Differential input ADC driver, 6.23-29
- Differential linearity, 2.107-108
 error, 2.15
 definition, 2.17
- Differential nonlinearity, see DNL
- Differential overvoltage, 9.104
- Differential PCM, 3.109
 versus delta modulation, scheme, 3.110
- Differential phase, 2.102, 5.78-83
 ADC, 5.78-83
 digital measurement, 5.81
 test signal, 5.80, 5.82
- Differential single-ended conversion, 6.70-73
- Differential to single-ended conversion, 6.70-73
- Differential transformer coupling, 6.71
- DigiPOT, 1.58, 8.56
- Digit grounder, 3.57, 3.59
- Digital audio, 8.59-74
 48-kSPS sampling, 8.62
 ADC and DAC, 8.63-65
 trends, 8.63-65
 anti-imaging filter, 8.64
 CD, circuit diagrams, 8.64
 key specifications, 8.61
 PCM, 8.63
 sampling rate and THD+N, 8.60-63
 studio quality recording, 8.66
 THD+N and sample rate, 8.62
- Digital baseband, software radio, 8.109-110
- Digital circuit:
 cost efficiency, 4.23
 standard voltage level, 9.181
- Digital converter, Advanced Filter Bank compensation, 8.154
- Digital corrected subranging, 3.64
- Digital crosspoint switch, 7.83-84
- Digital crosstalk, 2.102
- Digital Display Working Group, 8.105
- Digital down converter, 8.115
- Digital error correction, 3.64
- Digital filter, 3.111, 3.116, 3.125-126
 GSM channel, 8.113
 for sigma-delta ADC, 3.125-126
- Digital ground, in mixed-signal IC, 9.35
- Digital ground plane, PCB, 9.37
- Digital IC, fabrication process geometry, 4.23
- Digital interface, ADC and DAC, 6.47-67
- Digital isolation, 9.111-116
 LED/photodiode optocoupler, circuit, 9.113
 LED/phototransistor optocoupler, circuit, 9.112
- Digital isolator, overvoltage protection, 9.111-116
- Digital phase wheel, 8.162
- Digital post-processing:
 advanced, 8.151
 architecture, 8.151
- Digital potentiometer, 1.58, 8.49-58
 AC considerations, 8.55
 advantages and applications, 8.57
 applications, 8.55-57
 circuit applications, 8.56
 CMOS, characteristics, 8.51
 modern, small packaging, 8.50-51
 nonvolatile memory, 8.51-53
 one-time-programmable, 8.53-54
 from string DAC, 3.5
 tiny packaging, 8.50-51
- Digital receiver:
 AMPS wideband, 8.117
 multicarrier, chart, 8.131
 narrowband, 8.110-114
 narrowband IF-sampling, 8.110-114
 GSM/EDGE, 8.110-114
 single carrier, chart, 8.131
 software radio, 8.110
 wideband, 8.114-126
 wideband IF-sampling, 8.114-126
- Digital synthesis, direct, 8.159-176
- Digital temperature measurement, direct, 8.14-19
- Digital video:
 ADC and DAC, decoders and encoders, 8.81-84
 basics, 8.75-77
 black box, 8.78
 decoders and encoders, 8.81-84
 display electronics, 8.75-105
 formats, 8.77-81
 serial data interfaces, 8.81
 signal generation, model, 8.79
 standard broadcast television interlace format, 8.75
- Digital videodisc, 8.63
- Digital videotape recorders, development, 8.78
- Digital voltmeter, 2.15
- Digitally corrected subranging ADC, 2.113
- Digitizing, SHA function, 2.26
- Diniz, George, 8.105
- Diode:
 protection network, circuit diagram, 9.97
 unbuffered, 7.20
- Diode reference circuit, 7.3
- DIP package, prototyping, 9.206
- DiPilato, Joe, 3.138, 8.157
- Direct digital synthesis, 1.58, 2.84, 6.48, 8.159-176
 aliasing, 8.163-165
 frequency planning, 8.165-166
 modern integrated systems, 8.166-174
 see also DDS
- Direct IF-to-digital conversion, 2.31-32
- Discontinuous transmission, 8.137-138
- Discrete Fourier transform, 5.51-53

- applications, 5.51
- characteristics, 5.53
- outputs, conversion, 5.53
- sampled-periodic time domain signal, 5.52
- Discrete time Fourier series, 5.51-52
- Discrete time sampling, 2.24
- Discriminator, 3.43
- Displacement current, 9.143
- Display electronics, 8.85-90
 - graphics resolution and pixel rates, table, 8.86
- Dissipation factor, 9.5-6
- Distortion measurement, 5.17
 - DAC, 5.17-24
- Distortion products, location, 2.48
- Dither, 2.42, 8.126-131
 - out-of-band, to improve SFDR, 8.127
 - used to randomize ADC transfer function, 8.127
- Dither noise, 8.126
 - generation, 8.129
- Dither sinewave, 5.81
- Divider buffer, 3.18-19
- DNL, 2.72, 3.32, 5.2
 - DAC, 5.2, 5.5
 - due to encoding process, 2.46-47
 - error, 2.17
 - randomized, 8.129
 - temperature coefficient, 2.114
- DNR, digital audio, 8.60-61
- Dobkin, Robert C., 7.60
- Doeling, W., 9.23, 9.63
- Doernberg, Joey, 5.88
- Dominant pole, 7.37
- Dooley, Daniel J., 2.116, 3.139
- Dorey, Howard A., 3.108
- Double-buffered DAC, advantages, 3.33-34
- Double throw switch, 3.4
- Doublet glitch, DAC, 2.82
- Downconversion, 8.142
- DPO, digital phosphor scope, 5.15
- Drakhlis, Boris, 6.98
- DRDY, data ready, 3.41
- Drift, 2.102-103, 7.16, 7.18
- Droop, 6.50
 - rate, 2.102-103
 - SHA, 7.99
- Dropout voltage, 7.27-28, 7.31, 9.66
 - inverting mode pass device, 9.68
- DSO, digital storage scope, 5.15
- DSP:
 - grounding, internal PLL, 9.43-44
 - output rise and fall times, graph, 9.170
 - serial interface, 6.51
- Dual-slope conversion, 2.111
- Dual-slope converter, 2.103
- Dual-slope integration, in ADC, 3.97
- Dual slope/multi-slope ADC, 3.96-98
- Dual supply op amp, differential DC coupled
- output, 6.72
- Duff, David, 2.90
- Dummer, G.W.A., 9.24, 9.63
- Duracell Inc., 9.197
- Duracell MN1500 AA alkaline battery, discharge characteristics, 9.182
- DVD, sampling, 8.63
- Dynamic range, digital audio, 8.60-61
- Dynamic response, 2.104
- Dynamic settling time transient:
 - from charge coupling, 7.71
 - during multiplexing, 7.71
- Dynamic stability, 2.113
- Dynamic testing:
 - ADC, 5.45-86
 - low-distortion sinewave inputs, 5.66-68
- E**
- EIA RS-170, monochrome television standard, 8.76
- Earnshaw, J.B., 3.104
- Eccles-Jordan bistable multivibrator, 3.88
- Eckbauer, F., 3.137
- ECL, 1.41, 2.2, 9.175
 - emitter-coupled logic, 3.43
 - high-speed, invention, 1.24
 - standards, 9.184
- Edge rates, 9.163
- Edson, J.O., 1.11, 1.18, 1.31, 2.22, 3.84, 3.104, 3.106, 7.111
- Edwards, D.B.G., 3.106, 7.111
- EEMEM family, digital potentiometer, 8.52
- Effective aperture delay time, 2.69, 2.98
 - measurement, and ADC input, 2.70
 - SHA, 7.96-97
- Effective input noise, 2.103, 2.106
- Effective number of bits, see ENOB
- Effective resolution, 2.45, 2.103, 2.109, 8.8
- Effective resolution bandwidth, see ERB
- Effective series inductance, 9.5
- Effective series resistance, 9.5
- Efstathiou, Dimitrios, 8.156
- EIA RS-343A standard, electronic display, 8.85
- EIAJ ED-4701 Test Method C-111, 9.125
- 8051, 1.63
- Electrolytic capacitor, 9.82
 - ceramic, 9.84
 - film, 9.83
 - general purpose aluminum, 9.83
 - impedance, graph, 9.85
 - organic semiconductor, 9.83
 - stacked-film, 9.83
 - switching, 9.83
 - tantalum, 9.83
- Electromagnetic compatibility, see EMC
- Electromagnetic interference, see EMI
- Electromagnetic radiation, EMI path, 9.142
- Electromechanical Compatibility level, European Community, 9.121
- Electromechanical rotating commutator,

■ ANALOG-DIGITAL CONVERSION

- multiplexing, 1.4
- Electron beam coder:
 - Bell Labs, 3.48
 - modes, 2.6
 - shadow masks, 2.7
- Electron beam coding tube, 1.11-12
- Electronic Concepts, Inc., 9.91
- Electrostatic discharge, 2.94
 - see also ESD
- Elliott, Michael, 3.107, 7.111
- Elliott, Michael R., 3.107
- Elliptic filter, TTE, 2.30
- EMC:
 - described, 9.141
 - emissions, 9.141
- EMI:
 - coupling paths, 9.142
 - noise sources, 9.142
- EMI path:
 - high impedance ground connection, 9.143
 - summary, 9.143
- EMI/RFI, 9.141-179
 - amplifier outputs, 9.162-163
 - common-mode choke, for in-amps, 9.162
 - considerations, 9.141-179
 - coupling paths, 9.142
 - damping resistors, fast logic edges, 9.171
 - flexible common-mode and differential-mode filter, 9.161
 - general purpose common-mode/differential mode filter, 9.161
 - mechanisms, 9.142, 9.142-179
 - noise coupling mechanisms, 9.143
 - noise filter, op amp circuit, diagram, 9.160
 - noise sources, 9.142
 - op amp and in-amp outputs, long cable driving, 9.163
 - and passive components, 9.146-147
 - rectification sensitivity, op amp and in-amp, 9.155-157
 - reducing system susceptibility, 9.147-148
 - shielding, review, 9.148-151
 - susceptibility, 9.141
 - system susceptibility reduction, 9.147-148
- Emitter-coupled-logic, 2.2, 2.94
 - design, 6.96
- Emitter-coupled logic, see ECL
- Encode, sampling clock, 2.103
- Encode command, 2.103, 2.112
 - ADC, 3.41
- Encode pulselwidth/duty cycle, 2.103
- Encoder, 2.24, 3.41
 - digital video, 8.81-84
 - nonsampling, input frequency limitations, 2.24
- End-of-conversion, see EOC
- End point method, integral linearity error measurement, 2.16-17
- Engelhardt, E., 3.137
- ENIAC computer, invention, 1.21
- ENOB, 1.49, 1.55, 2.103, 5.28
 - of ADC, using sinewave curve fitting, 5.49-50
 - calculation using SINAD, 5.50
- data converter, 6.3
- degradation, in comparators, 3.50
- effective number of bits, 2.46, 2.48-50, 2.103, 3.115
- FPBW, 2.99
- jitter, 6.84
 - and SINAD, 6.84
- Envelope test:
 - ADC linearity, 5.46
 - lower input frequency, 5.47
 - test setup, 5.47
- EOC, 2.101, 3.41
 - ADC status, 3.41
- Epsco, 1.33
- Epsco Engineering, 1.21, 4.2
- Equivalent input referred noise, 2.43-44
- Equivalent series inductance, capacitor, 9.2
- Equivalent series resistance, capacitor, 9.2
- ERB, 2.99, 5.75
- Erisman, Brian, 9.91
- Error:
 - gain, 2.97
 - linearity, 2.97
 - sources, 2.97
 - zero, 2.97
- Error code, 1.52
- Error corrected ADC, 3.61-78
- Error correction, quantization levels, 3.64
- Error voltage, 8.148
 - digital current in analog path, 9.32
- Esaki diode, 3.48
- ESD, 9.116
 - damage, 9.118
 - data sheet statement, 9.119
 - models and testing, 9.121-124
 - packaging and labeling, 9.118
 - prime sources, 9.116
 - protection and prevention, buyer and seller, 9.120
 - summary, 9.124
 - testing methods,
 - differences, 9.122-123
 - waveforms, 9.123
 - voltage sources, 9.117
- ESD Association Draft Standard DS5.3, 9.125
- ESD Association Standard S5.2, 9.125
- ESD Prevention Manual, 9.125
- ESD protection, 9.195
- ESI, 9.5
 - capacitor, 9.2
- ESL:
 - capacitor loss, 9.83
 - filter loss, 9.84
- ESR, 9.5
 - capacitor, 9.2
- Eubanks, John M., 1.23

- Euler's equation, 5.53
 European Broadcast Union, standards, 8.60
 Evaluation board, 9.206-212
 data converter, 9.209-212
 characteristics, 9.209
 dedicated op amp, 9.207-209
 general purpose op amp, older, 9.207
 Expander, 3.26
 External components, 4.22
- F**
- Fabrication process:
 geometry,
 and cost, 4.24
 for digital IC, 4.23
- Fagen, M.D., 1.17, 1.32
- Failure, resistor, 9.14
- Fair-Rite Linear Ferrites Catalog, Fair-Rite Products, 9.91
- Fair-Rite Products, 9.91
- Fairchild, 1.24, 1.33
- Fairchild Semiconductor, 1.15, 4.3-4, 4.11
- Far-field interference, EMI path, 9.142
- Faraday shield, 9.20, 9.58-61, 9.59-60, 9.144
 floating, 9.60
 impractical location, 9.60
 operational model, 9.60
- Farmer, M.B., 1.4
- Fast Fourier transform, see FFT
- FASTRON GmbH, 9.91
- FASTStep mode, for AD7730, 3.130
- Fault-protected multiplexer, 9.99
- FDM, telephone, 1.8
- FDMA, frequency division multiple access, 2.58
- Feedback amplifier, patent, 1.14
- Feedback coder, 1.25, 3.57
- Feedback subtraction, 1.27-28, 3.56
- Feedback subtraction ADC, 1.28
- Feedback subtractor coder, 1.25, 3.57
- Feedthrough, 2.103, 7.101
 SHA, 2.103
- Feedthrough error, 2.103
- Felix, Micheal O., 5.89
- Ferguson, P.F., Jr., 3.137, 3.138
- Ferrite:
 characteristics, 9.86
 filter inductor, 9.86-87
 power supply noise reduction and filtering, 9.86-87
- Ferrite bead, 9.38, 9.42-44, 9.86, 9.89, 9.160, 9.164
- FET RFI rectification, 9.158-159
- Fetterman, Scott, 3.106
- FFT, 5.54
 accuracy, 5.65-66
 ADC analog bandwidth, 5.75
 ADC aperture jitter, 5.73-75
 analysis, 2.23
 basics, 5.51-59
- to compute discrete Fourier transform, 5.54
 dynamic ADC testing, 5.59-65
 FPBW, 2.99
 processing gain, 2.42
 sinewaves, 5.56
 single-tone sinewave testing, 2.42
 spectral analysis, ADC, 5.50
 test setup, 5.59-65
 configuration and measurements, 5.59-65
 diagram, 5.60
 verifying accuracy, 5.65-66
- Fiedler, Udo, 3.107
- Film capacitor, 9.82
- Filter:
 advanced, 8.152
 analog, oversampling, 2.88
 anti-imaging, 3.23, 8.163
 for digital audio, 8.64
 antialiasing, 3.115, 8.32
 baseband, 2.29-31
 position, op amp noise, 6.38
 in undersampling, 2.33-34
 undersampling, 2.33-34
 attenuation, 7.19
 bandpass, 5.70-72, 6.92
 Butterworth, 2.30
 noise bandwidth, 2.62
 two-pole, SNR, 2.87
 bypass/decoupling, 9.89-90
 card entry, 9.87-88
 power supply noise reduction and filtering, 9.87-88
 custom analog, firms, 2.31
 damping, 9.85
 data acquisition system, 8.31-33
 differential, 6.72
 digital, 3.125-126
 implications, 3.125-126
 sigma-delta ADC, 2.74
 elliptic,
 11-pole, characteristics, 2.31
 TTE, 2.30
 Gaussian active, buffering for audio DAC, 6.76
 interpolation, 3.23
 loss via ESR, 9.82-83
 lowpass, audio DAC, 6.75-76
 lowpass/bandpass, 2.23
 noise, power supply, 9.81-90
 notch, 2.59, 2.109
 minimizing analyzer overdrive, 5.68
 passive components, EMI reduction, 9.147
 rail bypass/distribution, 9.88
 power supply noise reduction and filtering, 9.88
 single-pole, settling time, table, 8.32
 type, EMI reduction, 9.147
- Finite amplitude resolution, due to quantization, 2.24
- Fisher, J., 3.137

■ ANALOG-DIGITAL CONVERSION

- Flach, Donald R., 5.88
Flash ADC, 1.40, 2.112, 3.46, 3.88
 4-, 6-, 8-bit monolithic, 1.41
 5-bit, diagram, 3.47
 monolithic, 1980s, 1.52-53
Flash converter, 2.103-104, 3.48
 3-bit all-parallel, diagram, 3.46
 ADC, 3.46-53
 comparator, 2.76
 electronic, 1.11
 interpolating, 3.52
 output latches, 3.70
 power dissipation, 3.51
Flash SADC, 3.64
Flat panel display, 8.90-94
 analog and digital interfaces, 8.91
 electronics, 8.90-94
Flat-pulse generator, 5.76-77
Fleming, Tarlton, 9.23
Flexibility, 4.23
Flicker-free code resolution, 2.45, 2.109
Floating shield, 9.60
Flutter, 5.29
Flyers, 3.45
 ADC, 2.76
Flynn, George, 1.31
Folding ADC, 3.42, 3.78-87
Folding converter, 3.81
Folding stage, functional equivalent circuit, 3.81
Folding transfer function, 3.78, 3.84
 using rectifier amplifiers, diagram, 3.84
Four-element-varying bridge configuration, 8.6
Four-quadrant, 2.104, 2.108
4000-series, CMOS logic, RCA, 1.24
Fourier analysis, 5.51-59
Fourier series, 5.51-52
Fourier transform, 5.51-52
FPBW, 2.50, 5.75
Fraschilla, J.L., 3.106
Freeman, J., 1.31, 5.87
Freeman, Wes, 9.93, 9.125
Frenzel, Louis E., 8.156
Frequency division multiple access, 2.58
Frequency division multiplexing, see FDM
Frequency synthesis, 8.159
Frequency-to-voltage conversion, see FVC
Friis equation, for noise figure, 2.67
FS-125, modular op amp, Computer Labs, 1.23
FSEA30, Rhode and Schwartz, 5.18
FSR, full-scale range, 2.104
Fu, Dennis, 3.108
Full-power bandwidth, see FPBW
Full-scale, 2.104
 positive or negative, 2.104
Full-scale input power, ADC, 2.104
Full-scale range, 2.97, 2.104, 2.107
Fully decoded DAC, 3.6-9
diagram, 3.7
Fundamental frequency, 2.50
FVC, 2.104
- G**
- Gailus, Paul H., 3.138
Gain, 2.105
Gain error, 2.15, 2.97
 DAC, 5.1, 5.2-4
 measurement, 5.31
Gain nonlinearity, 2.110
Gain tempco, 2.114
Gaines, W.M., 1.31, 5.87
Gallium arsenide, data converter role, 4.17
Gallium arsenide process, 3.50
Gamma unit, 8.79
Ganesan, A., 3.137
Garcia, Adolfo, 9.125, 9.178, 9.213
Gardner, F.M., 6.98, 8.175
Gate-drain capacitance, 7.70
Gaussian active filter, buffering for audio DAC, 6.76
Gaussian-filtered minimum-shift keying, 8.145
Gaussian frequency distribution, 6.83
Gaussian noise, 2.38, 2.58, 2.109, 5.44, 8.8, 8.124
General Electric, 1.23
General Instrument Corp., 1.23
Gentile, Ken, 8.175
George A. Philbrick Researches, Inc., 1.34, 4.2, 4.9
Gerber file, 9.46, 9.204, 9.209
Gerke, Daryl, 9.178
Germanium transistor, invention, 1.14
Gilbert, Roswell W., 3.108
Giles, James N., 3.44, 3.104
Giles, Jim, 1.40
Glitch, 2.102, 2.105, 2.109
 DAC, 2.102
 net impulse area, calculation, 2.83
Glitch charge, 2.106
Glitch energy, 2.102, 2.106, 5.15
 DAC, 2.82
Glitch impulse, 2.106
Glitch impulse area, 1.49, 2.102, 2.105-106
 DAC, 2.82-83, 5.15
 measurement, 5.15-17
 net impulse area, calculation, 2.83
Gold, B., 5.89
Goldberg, A., 8.104
Goldberg, A.A., 8.77
Goldberg, Bar-Giora, 6.98
Goodall, W.M., 1.11, 1.18, 3.105
Goodenough, Frank, 7.60, 9.91
Goodman, D.J., 3.112, 3.136
Gorbatenko, G.G., 3.106
Gordon Engineering, 1.33
Gordon, Bernard M., 1.21, 1.22, 1.25, 1.28, 1.31, 1.32, 2.116, 3.36, 3.59, 3.105, 3.106, 3.107, 3.139, 4.2, 5.27, 5.87, 5.88, 5.90

- Gorman, Christopher, 3.20, 3.37
 Gosser, Roy, 3.106, 4.12, 7.111
 Goto, 3.104
 Graham, M., 9.197
 Grame, Jerald, 9.63
 Grant, Doug, 8.139, 9.23
 Graphics control system, signal generation, 8.87
 Graphics display, RGB video levels, 8.89
 Gratzek, Tom, 8.156
 Gray bit, 3.81
 Gray bit output, 3.81
 Gray code, 1.3, 1.12-13, 2.4-8, 3.47-48, 3.51, 3.81, 3.99
 ADC architecture, 3.42
 in ADC architecture, 3.84
 coding scheme, 2.14
 decoding, errors, 3.52
 latched, 3.51
 LSB error, 1.13
 Gray code MagAMP design, 3.85
 Gray code shadow mask, 3.47
 Gray-coded ADC, 3.78-87
 Gray-to-binary code, conversion, 2.8, 3.51
 Gray transfer function, 3.78
 Gray, Elisha, 1.13, 2.6, 3.47
 Gray, Frank, 1.13, 1.18, 2.6, 2.22, 3.47, 3.104
 Gray, G.A., 2.90
 Gray, J.R., 3.106, 7.111
 Gregg, Christopher, 9.178
 Grift, Rob E.J. van de, 3.107
 Groshong, Richard, 8.156
 Gross, George F., Jr., 3.106
 Ground, 2.2
 analog and digital,
 separation, 9.34-35
 diagram, 9.35
 isolation techniques, 9.50-52
 PCB, layers, 9.32-33
 return current, 9.28
 Ground current, amplifier degradation, 9.50
 Ground isolation amplifier, 9.51
 differential input, 9.51
 Ground isolation techniques, 9.50-52
 Ground loop, digital isolator, 9.111
 Ground noise, 9.39
 Ground plane, 9.30-32
 breaks, 9.49-50
 circuit inductance, 9.49
 current flow, 9.49
 in mixed-signal multicard system, 9.33-34
 summary, 9.33
 Grounded-input histogram, 2.44
 for input-referred noise, 5.44
 Grounding, 9.30-45
 ADC digital output, 9.37-38
 decoupling, 9.35-36
 and decoupling, diagram, 9.38
 double-sided versus multilayer PCBs, 9.32-33
 ground plane multiple connections, 9.81
 linear and switching regulators, 9.78-81
 mixed-signal, 9.40-41
 mixed signal system, 9.30-46
 multicard mixed-signal systems, 9.33-34
 multicard systems,
 high digital currents, summary, 9.42-43
 low digital currents, summary, 9.41-42
 PCB, 9.25
 sampling clock, 9.38-41
 separating analog and digital, 9.34-35
 signal routing, for LDO, diagrams, 9.80
 single-card, for multicard system, 9.40-41
 summary, 9.44-45
 Grown-junction silicon transistor, 4.3
 GSM-900MHz system:
 sensitivity requirements, 8.121
 spurious requirements, 8.120-121
 GSM/DCS cellular telephone handset, functional diagram, 8.140
 GSM digital cellular telephone system, block diagram, 8.137
 GSM/EDGE, European multicarrier time-division multiplexed-access system, 8.111-112
 GTL, standards, 9.184
 Guard rings, 7.99
 Guard shield, in PCB, 7.100
 Guarding:
 basic principles, 9.54
 inverting mode, diagram, 9.53, 9.56
 MINIDIP layout, 9.55-56
 non-inverting mode, diagram, 9.54, 9.56
 PCB, 9.53
 Gustavsson, M., 8.157
 Gustavsson, Mikael, 2.117, 3.140, 5.91
- ## H
- Hageman, Steve, 9.91
 Hamming, window function, 5.57-58
 Hanning, window function, 5.57, 5.63-64
 Hardware:
 design,
 cable driving, 9.1
 overvoltage protection, 9.1
 passive components, 9.1-24
 receiving, 9.1
 shielding, 9.1
 Hardware design, 1-213
 Harmonic distortion, 2.46-48, 5.17
 2nd, 2.106
 3rd, 2.106
 data converter, 6.3
 total, 2.106
 plus noise, 2.106
 Harmonic sampling, 2.31-32
 Harmonic telegraph, 1.3
 Harmonics, 2.48
 Harris, Fredrick J., 5.89
 Harrison, R.M., 3.106
 Hartley, R.V.L., 1.17, 2.27, 2.35

■ ANALOG-DIGITAL CONVERSION

- Harvey, Barry, 5.25
HAS-1201, 12-bit 1-MSPS sampling ADC, 1.53
HAS-1202, 12-bit 2.2- μ s SAR ADC, 1.43
HAS-1409, 14-bit 1.25-MSPS sampling ADC, 1.53
Hauser, Max, 3.109
Hauser, Max W., 3.136
HDG-series, 4-, 6-, 8-bit 5-ns video ECL DACs, 1.53
HDS-1240E, 12-bit 40-ns ECL DAC, 1.53
HDS-1250, 12-bit 35-ns DAC, 1.43
Heat sinking, 9.128, 9.129
Heinzer, Walt, 8.49, 8.58
Heise, B., 3.137
Hendrickson, Gary, 9.179
Hendriks, Paul, 3.138
Henning, H.H., 1.18, 1.31, 2.22, 3.84, 3.104, 3.106
Henning, H.O., 7.111
Henry, J.L., 3.137
Hensley, Mike, 3.107, 7.111
Herring, G.J., 1.31
Higgins, Richard J., 5.89
High K capacitor, 9.8
High megohm resistor, 9.16
High performance hybrid and modular DACs and ADCs, 1980s, list, 1.53
High-performance mixed-signal circuit, specialized processes, 4.27
High resolution measurement sigma-delta ADC, 3.127-131
High-speed ADC:
 architecture, 3.46
 FIFO Evaluation Kit, 5.60-61
High-speed logic, 9.169-177
 EMI/RFI, 9.169-177
High-speed thermometer DAC, current outputs, 3.8
Higher order loop, 3.123
 sigma-delta converter, 3.123
Histogram, grounded-input, 2.44
Histogram test:
 ADC, 5.38-44
 buffer memory constraints, 5.41
 data display, 5.39-40
 sampling protocols, 5.41
 setup, 5.39
 sinewave, 5.42
A History of Engineering and Science in the Bell System, 1.3
Hnatek, Eugene R., 2.116, 3.36, 3.139, 5.90
Hodges, D.A., 8.157
Hodges, David A., 5.88
Hoerni, Jean, 1.15, 1.19, 4.3-4, 4.9
Hoerni, Jean A., 1.19, 4.9
Hoeschele, David F., Jr., 2.116, 3.139, 5.90
Hold mode, 2.100
Hold mode distortion, 7.101
 measurement, 7.102
Hold mode droop, 7.99
Hold mode noise, 7.102
Hold mode settling time, SHA, 7.95
Hold-to-track transition, specifications, 7.102
Holloway, Peter, 1.35, 1.47
Homodyne, 8.108
Horizontal sync, 8.76
Horna, O.A., 3.106, 7.111
Horvath, Johannes, 9.181
HS-810:
 8-bit 10-MSPS ADC, 4.4-5
 Computer Labs, Inc., 1.24
 using Gray code, 3.84
 HTC-0300, 300-ns SHA, 1.43-44
 HTS-0025, 25-ns SHA, 1.43-44
Human Body Model, ESD model, 9.121, 9.123
Hybrid clock generator, 6.94-95
Hybrid data converter, 4.6
Hybrid ground, cable shielding, 9.153
Hybrid regulation, 9.77
Hybrid SHA, 7.92
Hybrid Systems, 1.33
Hygroscopicity, PCB, 9.25
Hysteresis, 2.104, 3.43-44

I

- IC, 4.4
 ESD-sensitive, workstation environment, 9.119
 invention, 1.14
Ichiki, H., 3.104
iCoupler technology, 9.112
Idle tone:
 in sigma-delta ADC, 3.121-123
 sigma-delta converter, 3.121-123
IEC-1000-4, ESD standard, 9.122
IEC-1000-4-1, ESD standard, 9.122
IEC-1000-4-2:
 compliance testing methods, 9.121
 ESD standard, 9.122-123
IEC-1000-4-3, ESD standard, 9.122
IEC-1000-4-4, ESD standard, 9.122
IEC-1000-4-5, ESD standard, 9.122
IEC-1000-4-6, ESD standard, 9.122
IEC-1000-4-x, 9.121
IEEE-488 bus, 5.27
IEEE Standard 746-1984, 5.81, 5.88, 8.104
IEEE Standard 1057-1994 (R2001), 5.88
IEEE Standard 1241-2000, 5.21, 5.25, 5.81, 5.88
IEEE Standard 1596.3-1996, 9.179
IF sampling, 146-155, 2.31-32, 8.107
 software radio receiver and transmitter, diagram, 8.107
 time-interleaved, 8.146-155
IF sampling receiver, 1.55
IF-to-digital conversion, direct, 2.31-32
Ikeda, K., 3.104
ILC/Data Device Corporation, 1.33
Image spurs, 8.147, 8.150, 8.153
Images, aliases, 2.28
Imaging system, diagram, 8.94
IMD:

- intermodulation distortion, 2.53, 2.106, 2.108
- third-order products, 2.54-56
 - slope, 2.54
- Impedance:**
 - in grounding system, 9.29
 - input, 2.106
- Impedance mismatch, 9.149
- Impulse, 2.105
- In-amp:
 - input, 9.160-162
 - rectification, 9.160-162
 - overvoltage protection, 9.105-109
 - RFI rectification sensitivity, tests, 9.155-157
 - single supply, protection, circuit, 9.108
- In-circuit overvoltage:
 - general input common-mode, 9.93-95
 - protection, 9.93-116
 - summary, 9.116
- In-circuit voltage protection, 9.93-116
 - general input common-mode limitations, 9.93-95
- In-phase signal processing, 8.38
- Incremental optical encoder, 3.98
- Inductance, 4.15, 9.17-21
 - mutual, 9.17-20, 9.17-21
 - ringing, 9.17-20
 - stray, 9.17
 - wire and strip, calculations, 9.17
- Induction, skin effects, 9.46-48
- Inductive coupling:
 - basic principles, 9.18
 - EMI path, 9.142
- Inductor:
 - parasitic effects, 9.21
 - Q (quality factor), 9.21-22
 - quality factor, 9.21-22
 - ringing, 9.20
- Infinite ground conductivity, 9.29
- Infinite SHA, 8.45-47
- INL, integral nonlinearity, 5.2
- Inose, H., 3.136
- Input differential protection, 9.104-105
- Input impedance, 2.106
- Input multiplexer, 1.55
- Input noise, 2.72
- Input-referred noise, 2.103, 2.106, 5.71, 5.76
 - grounded input histogram, 5.44
- Instantaneous power, 8.22
- Instantaneous real power, 8.22
- Insulation resistance, capacitor, 9.2
- Integral linearity, 2.107-108
 - error measurement, 2.15-16
- Integral nonlinearity, 2.107-108
 - DAC, 5.1, 5.5
- Integrated circuit, see IC
- Integrated circuit ground pin, 9.31
- Integrated Device Technology (IDT), Inc., 9.197
- Integrated function, 1990s, table, 1.64
- Integrated-injection logic, 1.38
- Integrated-injection-logic process, 4.12
- Integrating and counting ADC architectures, 3.87-113
- Integrating servo-loop ADC tester, diagram, 5.36
- Integration, 4.21-26
 - levels, trends, 4.26
- Intel, 4.26
- Intentionally nonlinear DAC, 3.25-26
- Intercept points, amplifier, definition, 2.54-55
- Interconnection stability, resistor, 9.11
- Interface bandwidth, 4.22
- Interfacing:
 - 2.5V/1.8V, 9.190-193
 - 3.3V/1.8V, 9.190-193
 - 3.3V/2.5V, 9.188-190, 9.190-193
 - analysis, 9.190
 - 5V systems to 3.3V systems, using NMOS FET bus switches, 9.186-190
 - bidirectional, NMOS FET, 9.186
- Interference, associated impedance, 9.148
- Interlacing, television, 8.75
- Intermodulation distortion, 2.106, 2.108
 - data converter, 6.3
- Internal compliance and tolerance, CMOS IC, diagram, 9.195
- Internal high voltage generation, 9.196
- International Telephone and Telegraph Corporation, 1.8, 1.10, 8.59
- Interpolation, 3.51
- Interpolation filter, on DAC, 4.22
- Intersil, 1.33
- Intersymbol interference, 3.8
- Inverse Fourier transform, 5.51
- Inverting-mode op amp protection, 9.100-101
- Irons, Fred H., 2.91
- IS-136, US multicarrier time-division multiplexed-access system, 8.112
- ISI, intersymbol interference, 3.8
- ITT Laboratories, 3.109
- ITU-Recommendation BT.601, 8.104
- ITU-Recommendation BT.656-4, 8.104
- ITU-Recommendation BT.709-5, 8.104
- ITU Recommendation ITU-R BT.1204, 5.89

J

- Jager, F. de, 3.136
- Jantzi, S.A., 3.138
- Jayant, Nuggehally S., 2.116, 3.139, 5.90
- J.B. Rea, 1.21
- JEDEC, 9.197
- JEDEC standards, 9.184-185
- JFET RFI rectification, sensitivity, 9.159
- Jitter:**
 - aperture, 9.39
 - calculation, from phase noise, 6.88
 - oscillator, 6.86-94
- Johns, David A., 2.116, 3.139, 5.90
- Johnson noise, 9.14-15, 9.100
- Johnson, H., 9.197

■ ANALOG-DIGITAL CONVERSION

- Johnson, Howard W., 9.63
Joint Electron Device Engineering Council (JEDEC), 9.197
Jump size, 8.163
Junction field effect transistor, extra implantation, 7.11-14
Junction-to-ambient, thermal resistance, 9.127
Jung, Walt, 1.1, 3.108, 4.2, 4.19, 6.79, 7.1, 7.26-27, 8.157, 9.1, 9.25, 9.65, 9.91, 9.93, 9.127, 9.139, 9.141, 9.178, 9.199
Jung, Walter G., 1.17, 2.90, 2.117, 3.140, 4.9, 4.19, 5.91, 6.77, 8.26, 9.23
- K**
K2-W op amp, 4.2
K2-W Operational Amplifier, data sheet, 4.9
Kaiser, Harold R., 3.105
Kaiser, H.R., 3.59
Kaneko, H., 3.37
Kearney, Paul, 8.105
Kelvin divider, 3.8
 DAC, 3.4, 3.4-6
 DNL, 5.10
 no superposition, 5.10
Kelvin feedback:
 in PCB, 9.27-28
 signal leads, 9.27-28
Kelvin sensing, 7.8, 7.17, 7.20, 7.58, 8.5, 8.9
Kelvin-Varley divider, 3.18
Kelvin, Lord, 3.4
Kemet Electronics, 9.91
Kemet T491C-series, tantalum capacitor, 7.48
Kerr, Richard J., 8.175
Kessler, Martin, 4.21
Kester, W.A., 5.88, 8.104
Kester, Walt, 1.1, 1.49, 2.1, 2.23, 2.37, 2.90, 2.97, 2.117, 3.1, 3.39, 3.109, 3.140, 5.1, 5.88, 5.89, 5.91, 6.1, 6.45, 6.47, 6.67, 6.69, 6.77, 6.83, 7.1, 7.61, 7.91, 8.26, 8.27, 8.49, 8.59, 8.75, 8.107, 8.157, 8.159, 9.1, 9.25, 9.30, 9.63, 9.65, 9.91, 9.93, 9.125, 9.139, 9.141, 9.178, 9.181, 1.55, 1.65, 4.1, 4.11, 9.199
Kester, Walter, 5.88
Kester, Walter A., 5.87, 8.104
Khairoloomour, Peter, 8.58
Kilby, Jack, 1.15, 4.3-4
Kilby, J.S., 1.19, 4.9
Kimmel, William, 9.178
King, Grayson, 8.177
Kinniment, D.J., 3.106, 7.111
Kirchoff's law, 9.17, 9.28
Kitchen, Charles, 9.125, 9.178
Kitchen, Chuck, 9.178
Kitsopoulos, S.C., 3.106, 7.111
Kiyomo, T., 3.104
Klonowski, Paul, 3.108
Koch, R., 3.137
Kovacs, Gregory T.A., 7.60
Kovar lid, 9.60
- Krabbe, Hank, 4.13
kT/C noise, 2.43, 2.109
 CCD, 8.97
Kurosawa, N., 8.157
Kurth, C.F., 2.116, 3.139, 5.90
Kurz, Dov, 9.125
Kwan, Tom W., 3.36, 3.137
- L**
LabVIEW, 5.89
Lackey, 8.156
Lane, Chuck, 3.105
Lapham, Jerome F., 4.19
Laser wafer trimming, 4.12
Latch:
 in double-buffered DAC, 3.33
 output, 3.70
Latched comparator, 2.76, 3.43
Latchup, 9.35
Latency, 2.106
Lateral PNP, 4.11
LCCMOS, 1.49, 4.13
LDO, 7.27
 adjustable voltage, 9.72-74
 advantages, 9.66
 architectures, 7.35-39, 9.70-74
 DC and AC design issues, 7.38
 zoned load capacitor, effects, 7.39
device selection, voltages, table, 9.72
fixed-voltage, 9.71-72
grounding, 9.78-79
 signal routing, diagram, 9.78-79
regulator controller, 9.73
LDO regulator:
 board layout guidelines, 7.47
 thermal considerations, 7.46-51
LDO regulator controller, 7.51-59, 7.51-60
 2.8-V/8-A, 7.59
 diagram, 7.59
 basic, 7.53-54
 copper resistance design, table, 7.58
 pass device, 7.54-55
 PCB layout issues, 7.58
 PMOS FET pass device, 7.51
 sensing resistor, 7.57-58
 sensing resistors, 7.57-58
 thermal design, 7.55-57
LE1182-series elliptic filter, TTE Inc., 2.31
Leaded ferrite bead, 9.86
Leakage current, output, 2.106
Leakage resistance, static effect, 9.52
Least-significant bit, see LSB
Lee, Hae-Seung, 5.88
Lee, Seri, 9.139
Lee, Wai Laing, 3.137
Lee, W.L., 3.137
Left-justified data, 2.107
Lewis, Stephen H., 3.106
Li, Alan, 7.60, 8.58

- Li, Harry W., 5.89
 Linde Smith, John L., 3.108
 Line sensitivity, 7.17-18
 Linear compatible CMOS, 4.13
 Linear IC regulation, 9.66
 Linear mode regulation, 9.65
 Linear post regulator:
 low noise, 9.78
 switching supplies, 9.77-78
 Linear predictive coding, 8.137
 Linear ramp input, 3.79
 limitations, 5.41
 Linear regulator:
 low dropout, 7.27-60
 architectures, 7.35-39
 Linear resistance, calculation, 9.26
 Linear settling time, DAC, 2.81
 Linear voltage regulator:
 basics, 7.27-31, 9.66-68
 block diagram, 9.68
 negative leg series, 9.66
 pass device, 9.68
 positive leg series, 9.66
 three-terminal circuit, 9.67
 Linearity, 2.107
 differential, 2.107-108
 error, 2.15, 2.97
 integral, 2.107
 Linearity tempco, 2.114
 LM309, fixed-voltage regulator, 9.68
 LM317, adjustable-voltage regulator, 9.69
 LM109, basic bandgap reference, 7.4
 LM109/309, bandgap voltage reference, 7.33
 LM309:
 voltage regulator, 7.33-35, 7.37
 schematic diagram, 7.34
 LM311:
 comparator, 1.38
 IC comparator, 1.41
 LM317:
 adjustable voltage regulator,
 schematic diagram, 7.34
 topology, 7.35
 LM361, IC comparator, 1.41
 LO-PADS, 9.202
 Load sensitivity, 7.17-18
 Local high frequency bypass/decoupling, 9.89-90
 layouts, 9.89
 Locked-histogram test, 5.70-72
 ADC aperture jitter, test setup, 5.71
 Logarithmic transfer function, 3.26
 LOGDAC, functions, 3.27-28
 Logic:
 interface, 2.94-95
 standards, summary, 9.184
 types, 2.2
 Logic circuit, low voltage, interfacing, 2.95
 Logic device:
 choice and noise problems, 9.164
 EMI/RFI protection, 9.164
 Logic gate, 6.85
 RMS jitter, 6.86
 Logic IC, characteristics, 9.183
 Logic interfacing, low voltage, 9.181-197
 Logic noise:
 ADC buffering, 9.60-62
 buffering ADC, 9.60-62
 CMOS latched buffer, 9.61
 Lohman, R.D., 3.104
 Lohman, Robert D., 3.48
 Long term prediction, 8.138
 Looney, Mark, 8.146, 8.157
 Lorber, Matt, 4.11
 Low byte, 2.100
 Low-distortion DAC, 3.31-33
 Low-distortion sinewave, generation, test setups, 5.66-67
 Low dropout linear regulator, 7.27-60
 Low dropout regulator:
 architectures, 7.35-39
 definition, 7.27
 see also LDO
 Low-glitch architecture, DAC, 3.5
 Low-glitch segmented DAC, 3.31-32
 Low noise, 7.24-25
 Low power mode, 6.48
 Low-voltage-differential-signaling, see LVDS
 Low-voltage logic, interfaces, 9.181-197
 Lowpass filter, audio DAC, 6.75-76
 LPKF Laser & Electronics, 9.213
 LSB, 2.13, 2.100, 2.107
 peak-to-peak, 2.109
 rms, 2.109
 Luma signal, 8.79, 8.82
 Luminance, 5.78, 8.79
 LVDS, 3.76, 6.52, 6.54
 for high speed interfaces, 4.22
 logic, 2.2
 output driver, 6.54
 standards, 9.184
 LVDS logic, 9.175-176
 LVTTL, standards, 9.184
 Lyne, Niall, 9.125
- M**
- Machine Model, ESD model, 9.121
 MacKenzie, I. Scott, 8.191
 Maddox, C.L., 3.37
 MagAMP, 3.81
 3-bit, folding ADC, 3.81-82
 architecture, advantages, -86
 current-steering, differential gain-of-two, diagram, 3.85
 Gray code, 3.86
 Magnetic field, reflection loss, 9.149
 Magnetically-coupled noise, reduction, 9.145-146
 Magnetically coupled noise, reduction, 9.145-146
 Mahoney, Matthew, 2.116, 3.139, 5.88, 5.90

■ ANALOG-DIGITAL CONVERSION

- Malaeb, Mark, 8.58, 8.191
Mangelsdorf, Christopher W., 2.90, 3.104
Mannion, Patrick, 8.156
Manolakis, Dimitris G., 5.89
Mark/Space ratio, ADC, 3.91
Markow, John, 8.26
Mark, W., 9.23
Mark, W, 9.63
Martin, Ken, 2.116, 3.139, 5.90
Martin, Steve, 3.108
MAS-1202, 12-bit 2- μ s SAR ADC, 1.44, 1.46
MASH:
 multistage noise shaping, 3.126
 sigma-delta ADC, block diagram, 3.127
Mathcad, 5.89
MATLAB, 5.89
Matsuya, Y., 3.137
Matsuzawa, A., 2.90, 3.105
Matsuzoe, Nobuhiro, 8.191
Maximum conversion rate, 2.108
Maxwell, Darragh, 8.191
MC1650, IC comparator, 1.41
McCarthy, Mary, 8.58
McClaning, Kevin, 2.90
McDaniel, L.D., 3.37
McDaniel, Wharton, 7.60
MCM, 4.7
MDAC, 3.2
 current-mode R-2R ladder network, 3.25
 diagram, 3.25
 external voltage reference, 3.24
MDS-1250, 12-bit 50-ns DAC, 1.46
Meacham, L.A., 1.18, 3.37, 3.105, 7.111, 8.59, 8.74
Melliar-Smith, C. Mark, 1.18, 4.9
Memory, non-volatile, 4.14
Mendelsohn, Alex, 8.191
Mercer, Doug, 4.19, 8.157
MESC series RFI suppression chokes, 9.91
Metal film resistor, 9.16
Metal foil resistor, 9.16
Metal migration, 9.94
Metal-on-silicon device, 4.13
Metastability, 2.76, 3.44-45
Metastable comparator output, errors, 2.77
Metastable state, 2.76-80
 ADC, 2.76-80
Meyer, F.C., 5.87
MF Electronics, 9.39
Miao, Kai, 8.191
Mica capacitor, 9.8
Micro Power, 1.52
Micro Power Systems, 1.33
Microcontroller, 8.16
 precision analog, 8.177-191
MicroConverter:
 applications, 8.184-186
 based on ARM7 processor core, 8.187-190
 characteristics, 8.178-183
definition, 8.177
development tools, chart, 8.186
family, characteristics, 8.178-183
RTD interfacing, 8.185
sigma-delta ADC architecture, 8.182
 summary, 8.183
MicroConverter 12-bit SAR-based, summary, 8.180
MicroConverter SAR ADC performance, 8.179
MicroConverter sigma-delta ADC architecture, 8.180-182
Micronetworks, 1.33
Microprocessor supervisory products, 8.19
Microstrip:
 delay constant, 9.167
 guidelines, 9.167
Microstrip PCB layout, two pairs of LVDS signals, 9.177
Microstrip transmission line:
 characteristic impedance, 9.166
 controlled impedance, termination techniques, 9.173
 general parameters, 9.48
 on PCB, 9.166-167
MICROWIRE, serial interface, 6.51
Mid-scale settling time, 5.14
Mierlo, S. Van, 3.109, 3.136
MIL-883B, 4.6
MIL-M-38510, standard for 12-bit DAC, 1.35
MIL-STD-883 Method 3015, 9.121, 9.125
MIL-STD-883B, 1.42
MIL-STD-883B Method 3015.7, ESD test method, 9.122-123
Milled PCB prototyping, 9.203-205
 board, 9.204-205
Millman, S., 1.17
Miner, Willard M., 1.4, 1.17
Mini-Circuits, 6.45
Mini-Circuits RF transformer, 6.24-27
Mini-Mount, breadboarding system, 9.202
Minidac, 1.24-25
 12-bit, with op amp, quad switches, thin film
 resistor network, diagram, 1.26
MINIDIP guard layout, 9.55-56
Minimum 4-term Blackman-Harris, window function, 5.57, 5.63-64
Minimum conversion rate, sampling, 2.108
Minimum sampling frequency, 6.49-50
Missing code, 2.107, 2.108
 errors, 2.20-21
MIT Lincoln Labs, 1.23
Mitola, Jim, 8.156
Mixed-signal front ends, 1.55
Mixed-signal grounding, problems, 9.40-41
Mixed-signal IC:
 grounding, 9.30
 internal digital currents, diagram, 9.36
 low internal digital currents, diagram, 9.41

- grounding and decoupling, 9.35-36
- low voltage, summary, 9.182
- Mixed-signal system:
 - grounding, 9.45
 - multicard, 9.33-34
 - partitioning analog and digital circuits, 9.46
 - PCB layout guidelines, 9.45-46
- MOD-815:
 - 8-bit 15-MSPS ADC, 1.44-45
 - 8-bit 15-MSPS subranging ADC, Computer Labs Inc., 3.64
 - 8-bit 15-MSPS video sampling ADC, 1.46
- MOD-1020, 10-bit 20-MSPS sampling ADC, photograph, 1.45-46
- MOD-1205, 12-bit 5-MSPS sampling ADC, 1.45-46
- MOD-4100, 4-bit 100-MSPS flash ADC, using AM685
 - comparator, 3.49-50
- Modern data converter processes, 4.11-19
- Modular data converter, 4.6
- Modulation, 8.137
- Moghimi, Reza, 3.104, 8.58
- Monochrome, television, 8.76
- Monolithic ceramic capacitor, 9.8
- Monolithic dual FET, matched, 1.41
- Monolithic transistor array, 1.41
- Monotonic, DAC, 3.5, 5.1
- Monotonicity, 2.107, 2.108, 3.89
- Montrose, Mark, 9.64, 9.178
- Moore, Gordon, 4.26
- Moore's Law, 4.26, 4.30
- Moreland, Carl, 3.85, 3.107, 7.111
- Moreland, Carl W., 3.107
- Morrison, Ralph, 9.63, 9.178
- MOS, 4.13
- MOSFET, switch, on-resistance versus signal voltage, 7.63
- Moss, Brian, 8.191
- Most significant bit, see MSB
- Motchenbacher, C.D., 9.63, 9.125
- Motherboard, PCB, in mixed-signal system, 9.33-34
- Motorola, 1.33
- Motorola MC1650, 3.49
- Motorola MC1650 dual ECL comparators, 3.65
- MP7684, 8-bit 20-MSPS flash ADC, 1.52
- MSB, 2.2, 2.108
 - error, electron beam coder, 1.12
- μ -law, 3.26
- Mu-metal:
 - shielding, 9.20
 - shields, 9.146
- μ A702, monolithic op amp, 4.11
- μ A709:
 - IC op amp, Fairchild, 3.49
 - op amp, Fairchild, 1.24
- μ A710, IC comparator, 1.41
- μ A710/711:
 - Fairchild, 1.24
 - comparators, Fairchild, 1.23
 - μ A710 comparator, 1.25
 - μ A710/ μ A711, comparator, 4.11
 - μ A711, IC comparator, 1.41
 - μ A711/712, comparator, Fairchild, 3.49
 - μ A741, op amp, 4.11
 - Multi-bit sigma-delta ADC, 3.123-125
 - block diagram, 3.123
 - Multi-tone intermodulation distortion, 2.46
 - Multi-tone SFDR, 2.56-57
 - Multibit sigma-delta converter, 3.123-125
 - Multicard, mixed-signal systems, 9.33-34
 - Multicard system:
 - grounding, high digital currents, diagram, 9.43
 - grounding mixed-signal devices, 9.41-42
 - Multicarrier CDMA2000 receiver, RF spectrum, 8.117
 - Multicarrier receiver, chart, 8.131
 - Multicarrier transceiver, summary, 8.136
 - Multicarrier transmitter, chart, 8.135
 - Multichannel audio codecs and DACs, chart, 8.70
 - Multichannel data acquisition system, 8.27-48
 - Multichannel data distribution, 8.42
 - Multichannel system, two-tone intermodulation distortion, 8.122
 - Multipchip module, 4.7, 4.17
 - Multimode cellular chipset, 1, 4.22
 - Multiplexed Front End, 1.66
 - Multiplexer, 7.80-82, 8.37
 - analog, diagram, 8.28
 - from Analog Devices, 7.84-85
 - dual source RGB, using AD8183/AD8185/AD8186/AD8187, 7.81
 - using three AD8170, 7.81
 - fault-protected, 9.99
 - for dual-supply in-amp, circuit, 9.107
 - key specifications, 8.28
 - MOSES-8 MOSFET Multiplexer, 7.61
 - output, 2.73, 3.125
 - settling time, 2.74, 7.73
 - SHA, dynamic signal input processing, 8.30
 - triple dual input, 7.82
 - Multiplexers and analog switches, 7.61-89
 - Multiplexing, 1.4, 8.28-31
 - inputs to sigma-delta ADC, 8.36-38
 - Multiplying DAC, 2.108, 3.24-25
 - current-mode R-2R ladder network, 3.25
 - diagram, 3.25
 - external voltage reference, 3.24
 - feedthrough, 2.103
 - Multipoint ground, diagram, 9.34
 - Multistage noise shaping:
 - sigma-delta ADC, 3.126-127
 - sigma-delta converter, 3.126-127
 - Multisync, 8.86
 - Multitone spurious free dynamic range, 2.108
 - Murakami, J., 3.136

■ ANALOG-DIGITAL CONVERSION

- Murden, Frank, 3.85, 3.106, 3.107, 4.12, 7.111
Murphy, Eva, 9.181, 9.197
Musmann, H.G., 3.37
Muto, Art, 5.88
Muto, Arthur S., 5.88
Mutual inductance, 9.17-20, 9.17-21, 9.143
 within signal cabling, 9.19
MxFE, 1.66, 4.25
- N**
- N1 SADC gain error, 3.67
N1 SADC linearity error, 3.67
N1 SADC offset error, 3.67
N1 SDAC offset error, 3.67
Nahman, Norris S., 5.25
Narrowband, definition, 8.114
Narrowband digital receiver, 8.110-114
Narrowband GSM receiver bandpass sampling, diagram, 8.112
National LM361, 3.49
National Semiconductor, 1.25, 1.28, 1.33
Naylor, Jim R., 5.25, 5.87
NDB6020P, 7.53, 7.56, 7.59
NDP6020P, 7.53-56, 7.59
NDP6020P/NDB6020P, data sheet, 7.60
NE521, IC comparator, 1.41
Near-field interference, EMI path, 9.142
Neary, Eamon, 8.191
Neelands, Lewis J., 3.108
Negative full-scale, 2.104
Neil, Martin, 5.88
Net glitch area, 5.15
New TxDAC Generation, 8.157
NF, noise figure, 2.61
Nguyen, Khiem, 3.36, 3.137
Nicholas, Henry T., III, 8.175-176
Ninke, W.H., 3.37
NMR, 2.110
No missing codes resolution, 2.109, 2.112
Noise, 2.97
 capacitance-coupled, reduction, 9.144-145
 common-impedance, reduction, 9.143-144
 conducted type, 9.82
 equivalent input referred, 2.43-44
 excess, 9.14-15
 Gaussian, 2.109
 input-referred, 2.44
 input referred, grounded input histogram, 5.44
Johnson, 9.14-15
KT/C, 2.109
magnetically-coupled, reduction, 9.145-146
magnetically coupled, reduction, 9.145-146
from near-field interference, 9.144
peak, 2.109
random, 2.109
RMS, 2.109
signal-to-quantization ratio, 2.39
thermal, 9.14-15
voltage reference, 7.18-20
- Noise bandwidth, definition, 2.62
Noise coupling, mechanisms, 9.143
Noise factor, 2.61-68
Noise figure, 2.46, 2.61-68
 cascaded, using Friis equation, 2.67
Noise-free code resolution, 2.45, 2.103, 2.106, 2.109, 8.8, 8.11
Noise immunity, 3.103
Noise power ratio testing, 5.69-70
Noise reduction, power supply, 9.81-90
Noise reduction pin, 7.19
Noise Shaped Video techniques, 8.83
Noise shaping, 3.111, 3.112, 3.116
Non-coherent sampling:
 FFT output signal and harmonic leakage, 5.64
 leakage, 5.63
Non-Linear Systems, Inc., 1.21
Non-monotonic ADC, errors, 2.20
Non-monotonicity, 3.19
Nonlinear DAC, 3.25-26
Nonlinearity, 2.107, 2.110
 offset, 2.111
Nonlinearity error, resistor, 9.10
Nordenberg, H., 9.63
Normal mode, 2.110
Normal mode rejection, see NMR
Normalization, 2.2
Norton, Mark, 1.47
Notch filter, 2.59, 2.109
 minimizing analyzer overdrive, 5.68
Nova Devices, 4.11
Noyce, Robert N., 1.15, 1.19, 4.3-4, 4.9
NP0 ceramic capacitor, 9.8
NPR, 1.49, 2.58-60
 ADC testing, 5.69-70
 measurements, 2.58
 noise power ratio, 2.46, 2.109, 5.69-70
 test setup, 5.69
NTSC, 5.78-79, 5.81
 composite color video line, 8.76-77
 signal characteristics, 8.77
 videotape recorders, 8.62
Numerically controlled oscillator, 8.115, 8.160-161
Nyquist ADC, 3.111
 high resolution, 3.112
Nyquist band, 3.116
 sigma-delta ADC, 3.115
Nyquist bandwidth, 1.61, 1.64, 2.28-29, 2.38-39, 2.41, 2.63, 2.86-87, 2.98, 3.76, 5.19, 8.32, 8.113, 8.120, 8.122, 8.133, 8.160, 8.165
Nyquist conditions, 2.64
Nyquist criteria, 2.27, 2.27-29, 8.163
Nyquist frequency, 2.30, 2.49, 5.48, 6.37, 8.148-149, 8.164
Nyquist operation, 3.133
Nyquist range, 3.23
Nyquist rate, 3.110
Nyquist sigma-delta ADC, 3.112

- Nyquist theorem, PCM, 1.7
 Nyquist-type ADC, 8.1
 Nyquist zone, 2.28-29, 2.33-34, 2.58, 8.112, 8.118, 8.153
 first, 2.31-32
 frequency translation, 2.32
 undersampling, 2.31-32
 Nyquist, Harry, 1.6, 1.17, 2.27, 2.35
- O**
- OA-125, modular op amp, Computer Labs, 1.23
 O'Brien, Paul, 6.98, 8.175
 Octal DAC, 1.56
 Off-channel isolation, 8.28
 Offset, bipolar, 2.110
 Offset binary code, 2.8-9, 2.14
 bipolar 3-bit ADC, 2.9-10
 bipolar 3-bit DAC, 2.9-10
 Offset error, 2.15
 DAC, 5.1, 5.2-4
 measurement, 5.31
 Offset nonlinearity, 2.111
 Offset spurs, 8.147
 Offset step, 2.100, 2.110, 2.111
 Offset tempco, 2.115
 Ohmite Victoreen MAXI-MOX Resistors, 9.23
 Ohm's law, 9.27
 Oliver, Bernard M., 3.107
 Oliver, B.M., 1.18, 2.90
 Olshausen, Richard, 3.108
 O'Mara, Brian, 8.191
 On-Chip tools, resources, 8.189
 On-resistance, 8.28
 On-resistance modulation, 8.28
 ON Semiconductor, 6.98
 One shot, temperature sensor output mode, 8.15-16
 1-dB compression point, 2.54
 1N821-1N829 series, Zener references, 7.3
 1148, IC switcher, 9.77-78
 1408:
 8-bit bipolar process IC DAC, 1.34
 IC DAC, 1.41
 O'Neill, E.F., 1.17
 Ones complement, code, 2.11, 2.14
 Ones-density, 3.117
 Op amp:
 applied feedback, 6.9
 bipolar input, output phase-reversal, 9.103
 for buffering DAC output, 6.69
 dual,
 driver, 6.29-30
 driving, 6.29-30
 dual supply, differential DC coupled output, 6.72-73
 evaluation board,
 1990s, 9.207
 dedicated, 9.207-209
 FET, output phase-reversal, 9.103
 gain and level-shifting circuits, 6.10-13
 diagram, 6.11
 gain-of-two, 3.84
 input, 9.159-160
 rectification, 9.159-160
 input bias current, 6.7
 input common-mode voltage, 6.5
 input differential overvoltage protection network, 9.104
 inverting-mode protection, 9.100-101
 low bias current FET input I/V converter, block diagram, 9.100
 in low voltage rail-rail references, table, 7.21
 noise, antialiasing filter, 6.38
 noise figure, 2.61
 open-loop gain, 6.9
 output stages, diagram, 6.9
 overvoltage, CM protection circuit, 9.94
 performance factors, 6.2
 PNP, PMOS, or N-channel JFET stages, 6.5-6
 push-pull output, 6.8
 rail-rail input, 6.5-8
 diagram, 6.6
 rail-to-rail,
 "almost" output, 6.10
 for single-ended level shifter with gain, 6.13
 and regenerative repeaters, 1.13-16
 RFI rectification sensitivity, tests, 9.155-157
 single-supply, grounding, 9.56
 slew rates, 6.8
 specifications, key specifications, 6.4
 specifications and requirements, 6.13-15
 thermal resistance considerations, 9.131
 video driver, power dissipation, 9.133
 Op Amp Applications, 1.1, 4.2, 4.19
 Op Amps Combine Superb DC Precision and Fast Settling, 4.19
 OP177, low-noise buffer, 6.15-16
 OP184/284/484:
 bias input currents, 6.7
 rail-rail input stage, 6.7
 OP191/291/491, common-mode voltage, 6.7
 OP275, data sheet, 6.77
 OP1177, low-noise buffer, 6.15
 Open-loop SHA, 7.102-104
 circuit, 7.103
 using diode bridge switch, 7.103
 Oppenheim, V., 5.89
 Optical converter, 3.98-99
 ADC, 3.98-99
 Optical encoder:
 incremental, 3.98
 incremental and absolute, illustration, 3.99
 Opto-isolator, 8.14
 Optocoupler, 9.112
 architecture, 9.112-113
 Optoisolator, 9.112

■ ANALOG-DIGITAL CONVERSION

- OS-CON, organic semiconductor capacitor, 9.83
OS-CON Aluminum Electrolytic Capacitor Technical Book, Sanyo, 9.91
Oscillation, 3.43
Oscillator, 3.89
 broadband phase noise comparison, 6.90
 phase noise and jitter, 6.86-94
 phase noise versus frequency, 6.88
 power spectrum, phase noise, 6.86
 quartz crystal, 2.71
 resolution and input frequency, 6.94
Wenzel, 6.90-91
 jitter calculations, 6.91
Oscilloscope, sensitivity, 5.16
Oscilloscope measurement, settling time and glitch impulse area, 5.15-17
Othello direct conversion radio, 4.22
Othello radio, dual band GSM architecture, 8.144
Othello radio chipset, 8.140-145
 Virtual-IF transmitter, 8.142
Othello radio chipsets, 8.140-145
Ott, Henry, 9.178
Ott, Henry W., 9.24, 9.63, 9.91
Out-of-circuit overvoltage, protection, 9.116-124
Out-of-circuit voltage protection, 9.116-124
Output, digital, signal quantization, 2.12
Output amplifier, 1.35
Output glitch, 3.21
Output latches, flash converters, 3.70
Output leakage current, 2.106
Output phase-reversal, fixes, 9.103-104
Output phase-reversal test, 9.102-103
Output propagation delay, 2.110
Output ripple, 2.104
Output ripple voltage, voltage regulator, 9.76
Output settling time, 2.112
Output spectrum, DAC, $\sin(x)/x$ frequency rollout, 2.87
Output voltage phase-reversal, 9.101-102
 illustration, 9.102
 key points, 9.103
 prevention, 9.103-104
 testing, 9.102-103
Output voltage tolerance, 2.110
Overdrive, settling time, 5.15
Overlap bits, 3.64
Overload, 2.110
Overrange, overvoltage, 2.110
Oversampling, 2.40, 3.111, 3.112, 3.115-116, 3.116
 audio DAC, 6.75-76
 baseband antialiasing filter, 2.29
 for digital audio, 8.64
 interpolating DAC, 2.87-89, 3.23-24
 sigma-delta ADC, 3.115
 and undersampling, process gain, 2.40-41
Ovvervoltage:
 in-circuit, 9.93
 out-of-circuit, 9.93
power supply sequencing, protection, circuit, 9.111
protection, 9.93-126
 CMOS channel protectors, 9.98-99
recovery time, 2.46, 2.75, 2.110, 5.77-78
 test waveform, 5.77
Overvoltage overrange, 2.110
Overvoltage protection, 9.1, 9.93-126
 CMOS channel protector, 9.110-111
 CMOS channel protectors, 9.110-111
 digital isolators, 9.111-116
 ESD models and testing, 9.121-124
 in-amps, 9.105-109
 in-circuit, 9.93-116
 out-of-circuit, 9.116-124
Owen, Frank F.E., 2.116, 3.139, 5.90

P

- p-epi CB process, 4.12
Packaging, data converter, 4.17
PADS Software, Advanced CAM Technologies, Inc., 9.213
PAL, 5.78-79, 5.81
 signal characteristics, 8.77
 videotape recorders, 8.62
Panasonic, 9.91
Parallel ADC, 3.46-53
Parallel latch, 3.21
Parallel plate capacitor, 9.58
Parasitic capacitance, 9.11
Parasitic coupling, 9.57
Parasitic diode, 2.94
Parasitic effect, 7.37-38
 pin socket, 9.205
Parasitic inductance, 9.11
Parasitic resistance, 4.15
Parasitic thermocouple, 9.12
Parasitics, 1.56, 9.200
 capacitor, 9.2
 copper wire, 9.12
Partitioning, 4.21-30
 chip set, progress, 4.28
 developments, 4.27-30
 necessity, 4.26-27
 smart, 4.21-30
 diagram, 4.24
 purposes, 4.26-27
 versus complete integration, 4.21
Parzefall, F., 3.137
Pass device, 9.68
 associated tradeoffs, 7.31-35
 pros and cons, 7.32
 for voltage regulator, types, 7.31
Passive component, 9.1-24
 capacitor, 9.1, 9.2-8
 EMI path, 9.146-147
 error analysis, 9.22

- inductance, 9.17-21
- PCB, 9.1
- potentiometer, 9.1, 9.15
- resistor, 9.1, 9.9-16
- versus EMI/RFI, 9.146-147
- Pastoriza division of Analog Devices, 7.92
- Pastoriza Electronics, 1.23, 1.24, 1.44, 4.11
- Pastoriza, James, 1.23, 1.25
- Pastoriza, James J., 1.31, 3.16-17, 3.36
- Pattavina, Jeffrey S., 9.63
- PCB:
 - capacitive noise, 9.59-60
 - conductor resistance, 9.26-27
 - continuous ground plane, 9.50
 - design, 9.25-64, 9.163-164
 - controlled impedance traces, 9.164-166
 - EMI/RFI protection, 9.163, 9.163-164
 - double-sided,
 - from HS-81, 4.5
 - versus multilayer, 9.32-33
 - double-sided versus multilayer, 9.32-33
 - dynamic effects, 9.57-62
 - Faraday shield, 9.59-60
 - floating shield, 9.60
 - grounding, in mixed systems, 9.30-45
 - guard pattern, MINIDIP package, 9.55
 - Kelvin feedback, 9.27-28
 - layout, 7.58-59
 - mixed-signal system, 9.45-46
 - layout guidelines, for mixed-signal systems, 9.45-46
 - microstrip transmission line, as controlled impedance conductor, 9.48
 - microstrip transmission lines, 9.166-167
 - moisture sensitivity, 9.53
 - multilayer, versus double-sided, 9.32-33
 - passive component, 9.1
 - precision circuit performance, 9.25
 - signal leads, voltage drop, 9.27-28
 - signal return currents, 9.28-30
 - skin effect, 9.46-48, 9.48
 - SOIC guard layout, 9.56
 - static effects, 9.52-56
 - guard layouts, 9.55-56
 - stray capacitance, 9.58-59
 - symmetric stripline transmission lines, 9.167-168
 - trace resistance, 9.27
 - transmission lines, 9.48-49
- PCB design:
 - controlled impedance traces, 9.164-166
 - embedded traces, 9.169
 - for EMI/RFI protection, 9.163-164, 9.164
 - low impedance reference plane, 9.165
- PCM, 3.109
 - from Bell Labs, 1.11
 - and Bell System, history, 1.10-13
 - Bell System work, 1.21
 - invention, 1.5-6, 4.2
- Western Electric, 1.5
- mathematical foundations, 1.6-8
- mathematics, 1.6
 - historical summary, 1.8
- nonlinear DAC, 3.26
- Nyquist theorem, 1.7
- patent, 1.6
- patents, 1.8-10
- reinvention by Reeves, 1.8
- solid state repeater, Wrathall, 1.15
- theory, 1.5-6
 - voice channels, copper cable pairs, 1.15
- PCM DAC, architecture, 3.30
- PCM facsimile system, patent, 3.47
- Peak glitch area, DAC, 2.82
- Peak spurious component, 2.115
- Pease, Bob, 9.125
- Pease, Robert A., 9.23, 9.213
- PECL, 2.2, 6.96
 - standards, 9.184
- PECL low-jitter receiver/driver, 6.96
- Pedestal, 2.110, 2.111, 2.112
- Pedestal error, SHA, 7.95
- Pedestall, 2.100
- Peetz, Bruce E., 5.88
- Pericom Semiconductor Corporation, 9.197
- Personal digital assistants, 8.100
- Peterson, E., 1.18, 3.37, 3.105, 7.111, 8.59
- Peterson, J., 1.47, 3.105
- Phase accumulator, 8.160
- Phase-frequency detector, 8.144
- Phase jitter, in sampling clock, 9.39
- Phase-locked loop, 6.92-94, 8.145, 8.159
 - design, 6.94
- Phase noise, 2.71
 - definition, 6.86
 - jitter, calculation, 6.88, 6.90
 - oscillator, 6.86-94
 - sampling clock, sinewave, 6.87
- Phased array radar receiver, 1.23
- Phillips Laboratories, 3.109
- Pierce, J.R., 1.18, 2.90
- Pin count, 4.21
- Pin socket, 9.31, 9.205, 9.207
 - parasitic effects, 9.205
- Ping-pong high-speed DAC, 3.35
- Pipelined ADC, 2.113, 3.61-78, 3.88
- Pipelined architecture, 3.68
- Pipelining, 2.106, 2.111
- Pixel, 8.85
- Planar process, 1.14-15, 4.4
- Plassche, R.J. van de, 3.136
- Plassche, Rudy J. van de, 3.107
- Plassche, Rudy van de, 2.116-117, 3.139, 3.140, 5.90-91
- PLL, grounding DSP, 9.43-44
- PMOS:
 - pass device, 7.31-32
 - transistor current switch, 3.22-23

■ ANALOG-DIGITAL CONVERSION

- PN4117, JFET diode, 9.95
PNP/NPN, pass device, 7.31-32
Pohlmann, Ken C., 8.74
Pole-splitting, 7.42
Pole splitting, 9.71
 anyCAP topology, 7.42-43
 basic topology, 7.42
Polycarbonate capacitor, 9.8
Polyester capacitor, 9.8
Polypropylene capacitor, 9.8
Polystyrene capacitor, 9.8
Positive emitter coupled logic, see PECL
Positive full-scale, 2.104
Positive-true, 2.104-105
Potentiometer, 2.2, 9.15
 digital, 6.48, 8.49-58
 3-bit CMOS string DAC, diagram, 8.50
 passive component, 9.1
 trimming, 9.15
Poulin, Michael, 8.74, 8.104
Poulton, K., 8.157
Power Consideration Discussions, 9.139
Power conversion efficiency, 9.65
Power-down, ADC status, 3.41
Power line decoupling, resonant circuit, 9.20
Power measurement, basics, 8.22-23
Power meter, ADC application, 8.22-25
Power-on circuitry, 6.47
Power plane, 9.30-32
Power supply:
 analog, 9.65-91
 regulation priorities, 9.65
 analog ready, 9.87
 analog systems, 9.65-91
 conditioning, summary, 9.90
 filter, ferrite, 9.86-87
 linear IC regulation, 9.66
 low dropout regulator, 9.70-74
 noise, 9.65
 reduction and filtering, 9.81-90
 noise reduction and filtering, 9.81-90
 bypass/decoupling, 9.89-90
 capacitor, 9.82-85
 card entry filter, 9.87-88
 ferrite, 9.86-87
 rail bypass/distribution filter, 9.88
 pass device, 9.66-68
 regulator with adjustable voltage ICs, 9.68-69
 switching, noise, 9.81-90
 voltage regulator, 9.66-68
Power-supply rejection ratio, see PSRR
Power-up sequencing, 9.195
Poynton, Charles, 8.104
Pratt, Bill, 5.87
Preamplifier, 3.52-53
Precision analog microcontroller, 1.63, 8.177-191
Precision measurement:
 sensor conditioning, 8.1-26
 sigma-delta ADC, applications, 8.2-6
Precision Monolithics, 1.33
Precision Resistor Co., Inc., 9.23
Preston Scientific, 1.24
Principles of Pulse Code Modulation, 1.2
Printed circuit board, see PCB
Proakis, John G., 5.89
Process gain, 2.40, 8.113, 8.118
 ADC, FFT output, 5.55
 DAC, 5.20
Process support protection, 9.195
Programmable gain amplifier, 1.55
 alternate configuration, 7.78
 poor design, 7.77
Prototyping, 9.199-213
 analog, key points, 9.199
 and breadboarding, 9.199-213
 deadbug, 9.200-202
 milled PCB, 9.203-205
 PCB design, 9.206
 solder-mount, 9.202-203
 summary, 9.212
Pseudo-color, 8-bit RGB graphics system, 8.87-88
Pseudo-Gray code, 1.13, 2.7, 3.48
PSpice diode models, 9.95-96
PSRR, 2.111
PTM, constant pulse amplitude, 1.8
Pulldown resistor, 6.8
PulSAR family, SAR ADCs, 3.53
PulSAR series, 3.60
Pulse code modulation:
 digital audio, 8.63
 see also PCM
Pulse current response, 7.22-24
Pulse Engineering B4001 choke, 9.162
Pulse Engineering, Inc., 9.178
Pulse time modulation, see PTM
Pulse-width-modulated, pulse control, 3.88
Pulse width modulated, see PWM
PWM, pulse-width-modulated, 3.28-29, 3.88
PWM DAC, 3.28-29
PWM pulse, in Reeves' ADC and DAC, 1.10

Q

- QS3384 data sheet, Integrated Device Technology (IDT), Inc., 9.197
QSPI, serial interface, 6.51
Quad-slope architecture, in ADC, 3.97
Quad-slope converter, 2.111
Quad switch, 3.16-17
 DAC with thin film resistor network, diagram, 1.26
Quadrature modulation, 8.145
Quadrature signal processing, 8.38
Quality factor, inductor, 9.21-22
Quantization:
 error, 2.14, 2.38, 2.111
 root-mean-square, 2.38
 sigma-delta ADC, 3.115
 table, 2.13

- uncertainty, 2.4, 2.14, 5.28
using delta modulation, 3.110
- Quantization noise, 2.37-45, 2.59-60, 2.72, 3.119, 8.126, 8.165-166
frequency content, 2.41
function of time, 2.38
sigma-delta ADC, 3.115
- Quantizing uncertainty, 2.97, 2.111
- Quartz crystal oscillator, 2.71
- QuickStart, MicroConverter development tool, 8.186
- QXGA, electronic display standard, 8.86
- R**
- R-2R DAC, 3.12-18
3-bit binary, 3.26
resistor ladder network, diagram, 3.12
- R-2R ladder network, trimming, 3.19
- Rabbits, 3.45
ADC, 2.76
- Rabiner, L.R., 5.89
- Rack, A.J., 3.30
- Radiation, Inc., 1.23
- Radio frequency interference, see RFI
- Radix-2 algorithm, 5.54
- Rail bypass/distribution filter, 9.88
diagram, 9.88
power supply noise reduction and filtering, 9.88
- Rainey, Paul M., 1.5, 1.17, 3.9, 3.36, 3.47, 3.104
- Raltron Electronics Corporation, 6.98
- RAM-DAC, high-speed video, 1.49
- RAM-DAC family, 1.57
- Ramachandran, R., 3.106
- Ramirez, R.W., 5.89
- Ramp run-up ADC, 3.89-90
diagram, 3.90
- Ramp voltage, 3.88
- Random noise, 2.109
- Rappaport, Andy, 9.23
- Raster scan, 8.86
- Ratiometric, 2.111
- Ratiometric converter, 2.111
- Raytheon Computer, 1.23-24
- RCD Components, Inc., 9.23
- RDACs, 9.15
- RDC:
resolver-to-digital converter, 3.91, 3.99, 3.101-102
diagram, 3.102
tracking, 3.103
type-2 servo loop, 3.103
- Reay, Richard J., 7.60
- Receive signal processing, in wideband receiver, diagram, 8.115
- Receive signal processor, 8.107
- Receiver design, 8.109
digital processing at baseband, 8.109-110
- Recirculating subranging ADC, 3.74
- Recovery time, DAC, 2.81
- Rectangular, window function, 5.58
- Redcor Corporation, 1.23-24
- Redmond, Catherine, 9.181, 9.197
- Redundant bits, 3.64
- Reeves Instruments, 1.24
- Reeves, A.H., 3.28, 3.37, 7.91, 8.59
5-bit counting ADC, 3.88
- Reeves, Alec Harley, 1.8-10, 1.18, 3.105, 4.9, 7.111, 8.74
- Reeves, Alec Hartley, 4.2
- Reference noise:
bandwidth, 7.18
performance, circuit, 7.20
requirements, table, 7.19
- Reference white, 1.53
- Reflected binary code, 1.13, 3.47
- Reflection, off shielding material, 9.149
- Reflective switch, 7.79
- Regeneration time constant, 3.45
- Regular pulse excitation, 8.138
- Regulated output charge-pump voltage converter, 9.75-77
- Regulator controller, differences, 7.52-53
- Reichenbacher, P., 9.23, 9.63
- Rempfer, William C., 9.63
- Repetitive code patterns, ADC testing, 5.41
- Residue amplifier offset error, 3.67
- Residue output, 3.78
- Resistor:
aging, 9.14
comparison, chart, 9.16
comparisons, 9.16
discrete, 9.16
excess noise, 9.14-15
failure mechanisms, 9.14
mismatched, error source, 9.9
network, 9.16
parasitics, 9.11-12
passive component, 9.1
power dissipation, error source, 9.10
ratiometrical precision, 4.11
temperature-related errors, 9.11
thermoelectric effects, 9.12-14
types, 9.9
voltage sensitivity, 9.14
- Resistor noise, 2.43
- Resistor-transistor-logic, see RTL
- Resolution, 2.112
- DAC, 5.1
no missing codes, 2.109, 2.112
- Resolver, 2.2
diagram, 3.100
- Resolver-to-digital converter, 3.91, 3.99-103
ADC, 3.99-103
- Resonant circuit, power line decoupling, 9.20
- Resonator, replacing integrator, for bandpass sigma-delta ADC, 3.132

■ ANALOG-DIGITAL CONVERSION

- Retrace factor, 8.86
Reverse junction breakdown, 9.104
RF transformers, noise figure improvement, 2.66
RFI, rectification, sensitivity, 9.155
RFI rectification, 9.155
device susceptibility, 9.156
op amp and in-amp,
 sensitivity, summary, 9.157
 sensitivity testing, 9.155-157
proportional to interfering signal amplitude,
 9.158
reduction, using op amp and in-amp circuits,
 9.158
- RFI Rectification Test Configuration, 9.156
- Rheostat, 8.50
- Rich, Alan, 9.63, 9.178
- Right-justified data, 2.112
- Ringing, 9.17-20, 9.20
 voltage reference, 7.23
- Risetime, DAC, 5.16
- Ritchie, G.R., 3.37
- RMS input noise, 2.45
- RMS jitter:
 calculation, 6.89
 versus analog input frequency, ENOB, 6.85
- RMS noise:
 aperture jitter, 5.72
 measurement, 5.75
- RMS quantization error, 2.38
- RMS quantization noise, 3.115
- Roberts, Neil, 6.98
- Robertson, Dave, 4.19, 4.21, 8.156
- Robin, Michael, 8.74, 8.104
- Rohde & Schwarz, Inc., 5.25
- Rohde, Ulrich L., 6.98, 8.175
- Rollenhagen, D.C., 5.87
- Root-mean-square, see RMS
- Rorabaugh, C. Britton, 5.89
- Ross, Ian M., 4.9
- Rotating transformer, 3.100
- RS-232, 9.121
- RTL, in anti-ballistic missile system
electronics, 1.23
- Ruscak, Stephen, 8.156
- Ruscak, Steve, 2.90
- Rutten, Ivo W.J.M., 3.107
- S**
- S/N+D, see SINAD
"S" series surface mount current sensing
resistors, 7.60
- SADC, subranging ADC, 3.64-65, 3.67
- Sallen, R.P., 3.78
- Sample-and-hold, see SHA
- Sample-and-hold amplifier, see SHA
- Sample rate converter, 8.70-73
 concepts, 8.71
- Sample-to-hold offset, 2.100, 2.111, 2.112
- Sample-to-sample variation, in CCD, 8.97
- Sampled-aperiodic signal, in FFT, 5.52
Sampled data system:
 block diagram, 2.23
 fundamentals, 2.1-117
- Sampled-periodic signal, in FFT, 5.52
- Sampling:
 bandpass, 2.31-32
 harmonic, 2.31-32
 IF, 2.31-32
 Nyquist criteria, 2.27-29
 SHA need, 2.24-26
 theory, 2.23-25
- Sampling ADC, 2.112
- Sampling clock, 2.112, 6.83-98
 ADC input, 3.41
 circuitry, grounding, 9.38
 differential,
 driving input, 6.995-997
 input driving, 6.95-97
 distribution, digital to analog ground planes,
 diagram, 9.40
 encode, 2.103
 generation, 6.83-98
 grounding, 9.38-40, 9.38-41
 "hybrid" generator, 6.94-95
 jitter, 2.72, 6.83
 effect on ADC SNR, 9.39
 effects, 2.70
 low jitter single-ended to differential,
 diagram, 6.96
 phase jitter, 9.39
 phase noise, sinewave, 6.87
 pulsewidth/duty cycle, 2.103
 ratio to input frequency, SFDR, 2.42
 ratio to output frequency on 12-bit DAC SFDR,
 8.166
 summary, 6.97
- Sampling frequency, 2.112
- Sampling rate, 2.108
 criteria, 1.5
- Sampling system, simultaneous, 8.38-40
- Sampling theory:
 basics, 2.23
 discrete time sampling, 2.24
 finite amplitude resolution due to
 quantization, 2.24
- Samueli, Henry, 8.175-176
- Sanyo, 9.91
- SAR, 2.114
 logic function, implementation, 3.59
- SAR ADC, 3.11, 3.53-61, 3.91, 6.50
algorithm, 3.57
algorithm analogy, 1.27
with capacitive binary-weighted DAC, 3.12
development summary, 1.28
diagram, 1.28
dynamic transient loads, 7.23-24
fundamental timing, diagram, 3.53-54
by Schelleng, 3.58

- single-supply, resolution/conversion times, table, 3.60
superposition, 5.34
switched capacitor DAC, 3.55
terminology, 3.57
timing, 3.54-55
SAR logic IC, invention, 1.25
SAR MicroConverter products, 8.178
SAR register logic IC, invention, 1.25
Sauerwald, Mark, 9.63
Sawtooth error waveform, 5.32-33
Scaled reference, 7.20-22
Schafer, R.W., 5.89
Scharf, Brad W., 4.19
Schelleng, J.C., 3.57-59
Schelleng, John, 3.9-10
Schelleng, John C., 3.36, 3.105
Schindler, H.R., 3.104
Schmid, Hermann, 2.116, 3.139, 5.90
Schmitt trigger, 8.37
Schoeff, John A., 3.37
Schoenwetter, Howard K., 5.25
Schottky diode, 1.24, 1.41, 2.94, 5.16, 5.76, 6.96-97, 7.88, 7.103, 9.34, 9.42-44, 9.94-96, 9.103, 9.108-109
Schownwetter, H.K., 5.87
Schreier, Richard, 3.138
Schultz, Thomas W., 8.191
Scott-T transformer, 3.101
SDA6020, 6-bit 50-MSPS flash ADC, 1.52
SDC, synchro-to-digital converter, 3.91
SDC1700, synchro-to-digital converter, 1.46
Sears, R.W., 1.11, 1.18, 2.22, 3.47, 3.104
SECAM, 8.77
Segmentation, 3.18-23
Segmented ADC, 8.59
Segmented current-output DAC, diagrams, 3.21
Segmented DAC, 3.18-23, 8.59
Segmented unbuffered string DAC, 3.20
Seitzer, Dieter, 3.107
Selector, 3.57, 3.59
Semiconductor, junction temperature, 9.127
Semiconductor process, range, diagram, 4.28
Sensitivity, 8.119
Sensor, conditioning, 8.9
Sequential coder, 1.25, 3.57
Serial bit-per-stage binary ADC, 3.78-87
Serial data interface, 8.81
Serial-Gray converter, 3.81
Serial output, 2.112
Servo-loop tester, 5.36
computer-based, 5.36-38
diagram, 5.37
Servo-loop transition test, ADC, 5.35-36
Settling time, 2.46, 2.115, 3.80, 5.16-17, 5.76-77
ADC, 2.112, 5.76-77
DAC, 2.81, 2.81-82, 2.112, 5.13, 5.13-14
full-scale, definitions, 5.13-14
function of time constant, 2.75
measurement, 5.76
oscilloscope, 5.15
multiplexer, 2.74
output, 2.112
overdrive, 5.15
Settling time error, SHA, 7.95
74ACTQ240, Fairchild driver, 9.172
74FCT3807/A, IDT driver, 9.172
7400-series TTL logic, 4.11
7400TTL:
transistor-transistor-logic, 1.23
RCA, 1.24
SFDR, 1.49, 1.55, 2.46, 2.51-53, 2.84, 2.113, 3.32, 5.17
12-bit DAC, sampling clock and output frequency, 5.22
ADC, 2.41
clock frequency, worst harmonic, 5.24
DAC, 2.83-86
measurement, 2.85
data converter, 6.3
measurement in DAC, 5.19
measurement with analog spectrum analyzer, 2.86-87
multi-tone, 2.56-57, 2.108
two tone, 2.115
SHA, 1.55, 2.24-26, 7.91
acquisition time, 8.33
in ADC, FFT processing gain, 2.43
amplifier, function, 2.24-26
aperture delay, 7.96
aperture delay time, 7.96
aperture jitter, 7.97
aperture uncertainty, 7.97
applications, 7.108-110
architectures, 7.102-105
open-loop, 7.102-103
basic operation, 7.93-94
circuit, 7.91-111
DAC deglitcher, 7.109
dielectric absorption, 7.100, 9.4
differential switching, 7.104
driving ADCs, 7.108
droop error, 3.67
effective aperture delay time, 7.96
error sources, 7.94
function, 2.25
hold mode, 2.25
hold mode specifications, 7.99-102
internal circuit, for IC ADCs, 7.104-108
minimizing DAC glitches, 7.108
multiple,
data distribution system, 7.110
for simultaneous sampling, 7.109
output, jitter effects, 7.98
in pipelined delay, 7.110
sample mode, 2.25
in sampling, 2.24-26

■ ANALOG-DIGITAL CONVERSION

- in SAR ADC, 3.53
- settling time error, 3.67
- specifications, 7.94
- stray capacitance, 7.101
- switched capacitor CMOS, circuit, 7.106
- synchronous sampling clock delay, 7.97
- track mode specifications, 7.94-95
 - bandwidth, 7.94
 - distortion, 7.95
 - gain, 7.94
 - noise, 7.95
 - nonlinearity, 7.94
 - offset, 7.94
 - settling time, 7.95
 - slew rate, 7.95
- track-to-hold mode specifications, 7.95-99
- versus THA, 2.25
- virtual ground design, guard shield, 7.100
- waveforms, 7.96
 - definitions, 2.69
- SHA circuit, 7.91-111, 7.93
 - applications, 7.108-111
 - architectures, 7.102-105
 - basic operation, 7.93-94
 - history, 7.91-93
 - hold mode specification, 7.99-102
 - hold-to-track transition specifications, 7.102
 - internal circuits, 7.105-108
 - internal timing, 7.96
 - track mode specifications, 7.94-95
 - track-to-hold mode specifications, 7.95-99
- Shadow mask:
 - binary-coded, 1.12-13, 2.7
 - electron beam coder, for binary and Gray code, 1.12
- Shannon decoder, 3.31
- Shannon-Rack decoder, 1.11, 3.31
- Shannon, C.E., 1.17, 1.18, 2.35, 2.90, 3.30
- Shannon, Claude, 2.27
- Shannon, Claude E., 3.107
- SHARC DSP, 9.170, 9.174-175
 - bi-directional transmission, source termination, 9.175
- Sheet resistance, calculation, 9.26
- Sheingold, Dan, 1.33-34, 1.47, 2.1, 2.22, 2.91, 2.97, 2.116, 3.108, 3.112-113, 3.139, 4.2, 5.1, 5.25, 5.87, 5.88, 5.90, 7.26
- Shielding, 9.1
 - absorption loss, 9.149
 - effectiveness, calculation, 9.150
 - magnetic field, 9.20
 - review, 9.148-151
- Shockley, W., 1.19, 4.9
- Shockley, William, 1.15, 4.3-4
- Shunt, voltage reference, 7.2
- Siemens, 1.52
- Sigma-delta ADC, 2.112
 - advantages, 3.112
 - architecture, 3.112
- benefits, 8.1
- timeline, 3.112
- architecture timeline, 1.30
- bandpass, 3.132-133
- basics, 3.114-120
- characteristics, 3.115
- on chip features, 8.2
- choice of name, 3.113-114
- CMOS process, 4.15
- decimation, 3.114
- for digital audio, 8.64
- digital filter, 2.74, 3.114, 3.125-126
- in digital temperature sensor, 8.14
- first-order,
 - diagram, 3.117
 - modulator, idling patterns, 3.122
- high-density digital VLSI, 3.114
- high resolution, 3.127-131, 8.1
 - applications, 8.3
 - driving, 6.15-16
- high speed clock, 9.30
- linear, 8.59
- modulator, 3.117
 - ENOB, 3.120
 - frequency domain linearized model, 3.119
 - quantization noise shaping, 3.120
 - repetitive bit pattern, 3.122
 - waveforms, 3.118
- modulator loop, higher order, 3.123
- multi-bit, 3.123-125
- multiplexing inputs, 8.36-38
- oversampling, 3.114
- performance,
 - chop mode disabled, 8.183
 - normal, 8.182
- precision measurement, 8.2-6
- quantization noise shaping, 3.114
- second-order,
 - modulator:
 - block diagram, 3.120
 - idling patterns, 3.122
- single and multibit, 3.111
- SNR versus oversampling, loops, 3.121
- switched capacitor input, circuit, 7.22
- synchronous voltage-to-frequency converter, 3.118
- Sigma-delta architecture, summary, 3.134-135
- Sigma-delta converter, 3.109-140
 - ADC basics, 3.114-120
 - bandpass, 3.132-133
 - DAC, 3.133-134
 - high resolution measurement ADC, 3.127-131
 - higher order loop, 3.123
 - history, 3.109-114
 - idle tone, 3.121-123
 - multibit, 3.123-125
 - multistage noise shaping, 3.126-127
- Sigma-delta DAC, 3.133-134
 - CMOS process, 4.15

- for digital audio, 8.64
- interpolation filter, 3.23
- linear, 8.59
- schematic, 3.133
- Sigma-delta MicroConverters, 16-/24-bit, 1.65-66
- SigmaDSP family, audio DACs, 8.68
- Sign-magnitude code, 2.11, 2.14
- Sign-magnitude converter, 2.14
- Signal:
 - aliasing, 2.27
 - in FFT, 5.52
 - undersampled, Nyquist zone, 2.34
- Signal return current, 9.28-30
 - in PCB, 9.28-30
- Signal-to-noise-and-distortion ratio, see SINAD
- Signal-to-noise ratio, see SNR
- Signal trace routing, 9.18
 - correct, 9.19
- Signetics, 1.33
- Signetics 521, 3.49
- Sikimoto, T., 3.37
- Silence descriptor, 8.138
- Silicon germanium, data converter role, 4.17
- Silicon transistor, 4.4
- Siliconix PAD/JPAD/SSTPAD series low leakage Pico-amp diodes, Vishay/Siliconix, 9.125
- Simpson, Chester, 7.60
- Simultaneous sampling system, 8.38-40
- SINAD, 1.49, 1.55, 2.46, 2.103, 2.113, 5.28
 - calculation from SNR and THD, for DAC, 5.21
 - data converter, 6.3
 - FFT, noise and distortion, calculation, 5.64
 - FBPW, 2.99
 - signal-to-noise-and-distortion, 2.46, 2.48-50, 2.103, 2.113
- Sinewave, probability density function, 5.42
- Sinewave converter, 8.72
- Sinewave curve fitting:
 - for ADC ENOB, 5.49-50
 - test setup, 5.50
- Sinewave generator, 5.82
- Sinewave histogram DNL and INL, for ADC, 5.43-44
- Sinewave input, low-distortion, 5.66-68
- Singer, Larry, 2.90
- Single-carrier narrowband system, 8.122
- Single-carrier receiver, chart, 8.131
- Single-ended current-to-voltage conversion, 6.73-75
- Single-ended single-supply DC-coupled level shifter, diagram, 6.12
- Single-ended to differential conversion, using RF transformer, 6.97
- Single loop upconversion, 8.170
- Single NPN, pass device, 7.31-32
- Single PNP, pass device, 7.31-32
- Single-pole switch, 3.4
- Single-shot mode, 6.49-50
- Single-slope conversion, 2.113
- Skew glitch, 3.20
- Skin effect, 9.46-48, 9.49
 - PCB, 9.46-48
- Skinny connection, 9.32
- Slattery, Colm, 8.175
- Sleep, 6.48-50
 - ADC status, 3.41
- Slew rate, 2.113
- Slewing time, DAC, 2.81
- Slope clipping, 3.110
- Small signal bandwidth, 2.50
- Smith, B., 3.37
- Smith, B.D., 1.28, 3.9-10, 3.13, 3.26, 3.36, 3.59, 3.81, 3.105, 3.106
- Smith, B.K., 3.9
- Smith, Bruce K., 3.36
- Smith, D.B., 3.78
- Smith, Steven W., 5.89
- SMPTE 125M, 8.104
- SMPTE 170M, monochrome television standard, 8.76
- SMPTE 244M, 8.104
 - standard for NTSC signals, 8.78
- SMPTE 259M, 8.104
 - standard for NTSC signals, 8.78, 8.81
- SMPTE 292M, 8.104
- Snelgrove, M., 3.138
- SNR, 1.49, 1.55, 2.72, 5.17, 5.28
 - ADC,
 - aperture and sampling clock jitter effects, 2.71
 - sampling clock jitter effect, 9.39
 - and broadband aperture jitter, 6.83
 - DAC, 2.83-86
 - spectrum analyzer, 5.20
 - data converter, 6.3
 - degradation from jitter, 9.39
 - digital audio, 8.60-61
 - FFT, values, 5.66
 - measurement with analog spectrum analyzer, 2.86-87
 - sampling clock jitter effects, 7.98
 - signal-to-noise ratio, 2.39, 2.46, 2.48-50, 5.17
 - theoretical, 2.39
 - total, equation, 2.72-73
 - without harmonics, 2.113
- Soakage, 9.3
- Socket, 9.200, 9.205-206
 - low-profile, 9.205
 - problems, 9.205-206
- Sockolov, Steve, 9.23
- Sodini, C.G., 3.137
- Softcell family, 8.134, 8.136
- SoftFone chipset, 8.140-145
- SoftFone radio chipsets, 8.140-145
- Software radio, 8.107-145
 - ADC dynamic range, dither, 8.126-131

■ ANALOG-DIGITAL CONVERSION

- evolution, 8.108
- IF sampling, 8.107-157
- receiver, digital baseband processing, 8.109-110
- SOIC guard layout, 9.56
- Solder-Mount:
 - breadboarding system, 9.202
 - prototyping, 9.202-203
 - board, 9.203
- Solid-state:
 - key developments, 1.15, 4.4
 - and op amp, history, 1.13-16
- Solomon, Jim, 7.60
- Sonet/SDH OC-48, using AD8152, 7.83-84
- SOT-223 packaging, reduction, 7.51
- Souders, T. Michael, 5.88
- Souders, Thomas, 5.87
- Southern and F-Dyne film capacitors, 9.23
- Span, 2.104
- Sparkle code, 1.52, 2.76-80, 3.45
 - ADC, 2.76-80
- SPDT switch, 3.3
- Specification MIL-PRF-123B, 9.23
- Specification MIL-PRF-19978G, 9.23
- Specifications, definitions, 2.97-117
- Spectral leakage, ADC testing, 5.55
- Spectral output, code-dependent glitches, effect, 2.84
- Spectrum:
 - in-band SFDR, 2.51
 - out-of-band SFDR, 2.51
- Spectrum analyzer:
 - DAC distortion and SNR measurement, 5.20
 - sensitivity to input overdrive, 5.68
- Speech decoder, 8.136
- Speech encoder, 8.136
- SPI, serial interface, 6.51
- Sprague, Clarence A., 3.36
- Spread-spectrum, 8.116
- Spurious free dynamic range, 2.113, 5.17
- Stability, 2.113
- Staffin, R., 3.104
- Staffin, Robert, 3.48
- Staircase, 2.113
- Staircase generator, 5.82
- Standard IPC-2141, 9.178
- Standby mode, 6.48, 6.50
 - ADC status, 3.41
- Staniforth, Alan, 9.178
- Star ground, 9.31, 9.34
- Stata, Ray, 1.24, 1.33, 1.47, 4.11
- Static error, DAC, measurement methods, 5.1
- Status, 2.101
- Stewart, James W., 8.191
- Stop, Russell, 3.107, 7.111
- Straight binary, coding scheme, 2.14
- Strain gage, 2.2
- Stray capacitance, 9.58-59
 - PCBs, 9.57-59
- SHA, 7.101
- Stray inductance, 9.17
- String DAC, 3.4, 3.18
 - architecture for digital potentiometer, 8.49
- INL, 5.11
- INL trimming, 3.6
- no superposition, 5.10
- resistors, 3.6
- unbuffered, segmented, 3.19-20
- Strip inductance, 9.17
- Stroud, Tim, 8.105
- Submicron CMOS, 4.14
- Subranging ADC, 2.113, 3.11, 3.61-78, 3.88
- Subranging converter, 2.104
- Substrate PNP, 4.11
- Successive approximation, see SAR
- Superheterodyne, 8.108, 8.142-143
- Superhomodyne, 8.142-144
- Superposition:
 - DAC,
 - bit errors, 5.5
 - DNL and INL, 5.6
 - Supply range, 7.17-18
 - Supply voltage, 4.21
 - shrinking, effects, 4.27
- Susskind, Alfred K., 2.116, 3.139, 5.90
- SVFC:
 - clock frequency, 3.94
 - nonlinearity, 3.95
 - problems, 3.94
 - quantization, 3.95
 - synchronous VFC, 3.93-94
 - temperature stability, 3.94
 - waveforms, 3.95
- SVGA, electronic display standard, 8.86
- Swanson, E.J., 3.137
- Swart, Leland K., 3.36
- Sweetland, Karl, 3.36, 3.137
- Switch:
 - from Analog Devices, 7.84-85
- CMOS,
 - 1-GHz, 7.78-79
 - application, 7.73-78
 - basics, 7.62-64
 - error sources, 7.65-73
- CMOS and DMOS, 1.41
- digital crosspoint, 7.83-84
- hold mode, 6.19-20
- track mode, 6.19-20
- video, and multiplexers, 7.80-82
 - video crosspoint, 7.82-83
- Switch capacitance, 7.70
- Switches and multiplexer, CMOS process, 7.62
- Switching regulator, 9.79-80
 - analog ready, 9.82
 - capacitor, 9.82-85
 - peak amplitudes, 9.82
 - power supply noise, reducing, 9.82
- Switching time, 2.114, 8.28

- DAC, 2.81
 Switching transients, charge-balance VFC, 3.93
 SXGA, electronic display standard, 8.86
 Symmetric stripline, 9.167
 capacitance, 9.168
 transmission line, 9.167-168
 formation, 9.168
 Sync, 1.53
 Synchro, 2.2, 3.99-103
 diagram, 3.100
 Synchro ADC, 3.99-103
 Synchro-to-digital converter, 3.91
 Synchronous sampling clock delay, SHA, 7.97
 Synchronous VFC, 3.91, 3.93
 System Management Bus, 8.21
- T**
 T-1 carrier system, Bell Labs, 1.16
 T-Carrier digital transmission system, 8.137
 T-Tech, Inc., 9.213
 Tadewald, T., 9.23, 9.63
 Talambiras, Robert P., 1.31, 3.36, 3.105, 3.107
 Tan, Nianxiong Nick, 2.117, 3.140, 5.91
 Tan, N.N., 8.157
 Tantalum and Ceramic Surface Mount Capacitor Catalog, 9.23
 Tantalum capacitor, 9.8
 Tantalum Electrolytic and Ceramic Capacitor Families, 9.91
 Tant, M.J., 2.90
 Tartaglia, mathematician, 3.56
 TDC-1007J:
 8-bit 30-MSPS video-speed flash ADC, 1.40, 1.45, 1.52
 TRW LSI Division, 3.49
 TDC-1014J:
 6-bit 30-MSPS video-speed flash ADC, 1.40, 1.45
 TRW LSI Division, 3.49
 TDC-1016J, 6-bit 30-MSPS flash ADC, 1.40, 1.52
 TDC-1048, 8-bit 30-MSPS flash ADC, 1.52
 TDM, telegraph, 1.4
 Teal, Gordon, 4.3-4
 Teflon capacitor, 9.8
 Tektronix, Inc., 5.25
 Teledyne Philbrick, 1.33
 Telegraph, electric, history, 1.3
 Telegraph multiplexing system, 1.3
 Telephone:
 cellular, handsets, 8.136-139
 most significant communication event, 1.3
 NPR, 5.69
 patent, 1.4
 Television, standard interlace format, 8.75
 Telmos, 1.52
 Temes, Gabor C., 2.116, 3.137, 3.139, 5.90
 Tempco:
 gain, 2.114
 linearity, 2.114
 offset, 2.115
 Temperature, capacitor, 9.6
 Temperature coefficient, 2.113, 2.114
 Temperature measurement, digital, direct, 8.14-19
 Temperature retrace, resistor, 9.11
 Temperature sensor, microprocessor substrate, 8.19-22
 10 percent white, 1.53
 Testability, 4.22
 Tewksbury, Stuart K., 5.87
 Texas Instruments, 1.15, 1.24, 4.3-4
 THA, 2.25
 for deglitching DAC, 3.32
 Thandi, Gurgit, 9.91
 THD, 2.46-48, 2.106, 3.32, 5.17, 5.28
 data converter, 6.3
 THD+N, 2.46-48, 2.106, 5.17
 data converter, 6.3
 digital audio, 8.60-61
 Theoretical SNR, jitter, 6.84
 Thermal basics, 9.127-128
 Thermal Coastline packaging, 7.39, 7.48-49
 Thermal EMF, 9.12
 Thermal management, 9.127-139
 basics, 9.127-128
 Thermal noise, 8.124, 9.14-15
 Thermal rating curves:
 for BATWING and PSOP3 packages, 9.131
 for standard and ADI Thermal Coastline 8-pin SOIC packages, 9.130
 Thermal relationships, table, 9.128
 Thermal resistance, 9.127
 considerations, 9.131
 junction and ambient air, 9.128
 Thermal tail, 2.115
 Thermal turbulence, 9.14
 Thermocouple, 2.2
 conditioning, 8.12-14
 effect, 9.12
 EMF, effects, diagram, 9.13
 measurement design, 8.13-14
 resistor, diagram, 9.13
 type K, conditioning, 8.12-14
 Thermoelectric effect, 9.12-14
 Thermometer DAC, 3.6-9
 3-bit, in current-output segmented DAC, 3.21
 current output, diagram, 3.7
 high speed, current outputs, 3.8
 Thevenin impedance, 9.172
 Thick film resistor, 9.16
 Thin film laser trimming, sigma-delta ADC, 3.124
 Thin-film resistor, 9.16
 in in-amp, 9.105
 process, 4.11-12
 Thin-film wafer trimmed resistor, 4.12
 Threshold, 2.104
 THS-0025, 25-ns SHA, 1.46
 THS-0300, 300-ns SHA, 1.46
 TIA/EIA-644-A Standard, 9.179

■ ANALOG-DIGITAL CONVERSION

- Time division multiplexing, see TDM
Time-interleaved ADC:
 digital post-processor, 8.146-155
 matching requirements, 8.150
Time interleaving, 8.146, 8.154
Time-skew, 2.102
Timing, data converter, 2.95-96
TLM1070, 7-bit 20-MSPS flash ADC, 1.52
TMP05/TMP06:
 data sheet, 8.26
 digital output sensor, 8.14-17
 circuit, 8.15
 output format, 8.15
TMP06, digital output sensor, interfaced to microcontroller, 8.16
Tolerance, 7.15, 7.18
 capacitor, 9.6
Total harmonic distortion, see THD
Total harmonic distortion plus noise, see THD+N
Total unadjusted error, 2.115
Touchscreen:
 construction, 8.100
 digitizer, 8.100-103
 voltages, absolute and ratiometric measurements, 8.101
Touchscreen digitizer, 8.100-103
Trace, embedding, 9.169
Track-and-hold, see THA
Track-and-hold circuit, 7.91
Track mode distortion, 7.101
Tracking ADC, 3.90-91
Transfer function:
 data converter, graphs, 2.14
 folding stage, 3.81
Transformer coupling, 6.24
Transient error, SHA, 7.95
Transient response, 2.73, 2.73-75, 2.115, 8.33
Transient voltage suppressor, 9.109, 9.124
Transistor, germanium, invention, 1.14
Transistor-transistor logic, 2.2
Transmission line, 9.48-49, 9.165
 clock distribution, 9.174
 PCB, as controlled impedance conductor, 9.48
 single, end termination, 9.175
 symmetric stripline, PCB, 9.167-168
 termination guidelines, 9.169-170
Transmission Systems for Communications, 1.17
Transmit DAC, 1.58
TransZorb, 9.124
 clamp, 9.106
 General Semiconductor, Inc., 9.126
Travis, Bill, 8.191
Trench-isolation, 9.111
 CMOS switch, 7.89
Triboelectric effect, 9.117
TrimDAC, 1.58, 9.15
Trimming, 4.8, 4.11
 ADC, 3.39
 laser wafer, 4.12
 Trimpot, 9.15
Triple-slope architecture, in ADC, 3.97
TRW LSI Division, 1.33, 1.40, 1.45, 1.52
TTE, elliptic filters, 2.30
TTE, Inc., 2.35
TTL, 1.41, 2.2
 standards, 9.184
Tukey, J.W., 5.89
Tunnel diode, 3.48
Turney, William J., 3.138
Two-converter interleaved FFT plot, 8.149
Two-converter time-interleaved 12-bit 400-MSPS ADC, 8.148
Two-tone intermodulation distortion, 2.46, 2.53
Two-tone SFDR, 2.115
2N5457, JFET diode, 9.95-96
2502:
 8-bit serial SAR IC, 1.41
 Advanced Micro Devices and National Semiconductor, 1.25
2503:
 8-bit serial expandable SAR IC, 1.41
 Advanced Micro Devices and National Semiconductor, 1.25
2504:
 12-bit serial expandable SAR IC, 1.41-42
 Advanced Micro Devices and National Semiconductor, 1.25
Twos complement code, 2.9, 2.11, 2.14
TxDAC, 1.57, 1.58, 4.25, 6.66, 6.70
 clock-rate dependent power dissipation, 9.138
CMOS process, 4.15
communications, 5.13, 5.18
current switching, 3.22
interpolating, oversampling, block diagram, 2.89
testing, 5.46
 in wideband radio, 8.132
Type 5MC Metallized Polycarbonate Capacitor, Electronic Concepts, Inc., 9.91
Type EXC L leadless ferrite bead, 9.91
Type EXCEL leaded ferrite bead, 9.91
Type HFQ Alumminium Elecrolytic Capacitor, Panasonic, 9.91
Type K thermocouple, 8.12-14

U

- U-matic, videotape recorders, 8.62
Undersampling, 2.31-32
 antialiasing filter, 2.33-34
 and oversampling, process gain, 2.40-41
Understanding Common Mode Noise, 9.178
Unipolar converter, 2.14-15
 zero TC, 2.114
UNIVAC computer, invention, 1.21
Upmall, 8.156
UXGA, electronic display standard, 8.86

V

- Vacuum tube:
 data converter, 4.1-3
 invention, 4.1
 patent, 1.13
 and op amp, history, 1.13-16
 Vacuum tube binary DAC, 3.9
 Van de Grift, Rob E.J., 3.107
 Van de Plassche, R.J., 3.136
 Van de Plassche, Rudy, 2.116-117, 3.139, 3.140, 5.90-91
 Van de Plassche, Rudy J., 3.107
 Van de Weg, H., 3.136
 Van der Veen, Martien, 3.107
 Van Doren, A., 1.31, 5.87
 Van Mierlo, S., 3.109, 3.136
 Variable frequency oscillator, see VFO
 Variable phase shifter, in locked-histogram ADC test setup, 5.71
 Vassalli, Luca, 8.191
 VCXO, voltage-controlled crystal oscillator, 6.91
 Vector Electronic Company, 9.213
 Vectorscope, 5.80
 Veen, Martien van der, 3.107
 Velazquez, S., 8.157
 Verster, T.C., 3.64, 3.106
 Vertical sync, 8.76
 VFC, 2.104, 3.91-96, 8.14
 applications, 3.96
 charge-balance, 3.91
 current-steering multivibrator, 3.91
 waveforms, 3.95
 VFO, 3.91
 VGA, electronic display standard, 8.86
 VHS-630, 6-bit 30-MSPS flash converter, Computer
 Labs Inc., 3.49
 VHS-675, 6-bit 75-MSPS flash converter, Computer
 Labs Inc., 3.49
 Video, analog and digital standards, 8.80
 Video crosspoint switch, 7.82-83
 Video DAC, properties, 8.88
 Video decoder, specifications, 8.85
 Video encoder, specifications, 8.85
 Video RAM-DAC, 8.87, 8.90-91
 Video switch, 7.80-82
 Video testing, 5.78-83
 ADC, 5.78-83
 Vishay/Dale Resistors, 9.24
 Vishay/Siliconix, 9.125
 Viswanathan, T.R., 3.106
 Viterbi coding, 8.137
 Viterbi decoding, 8.137
 Vito, Tom, 2.90
 VLSI mixed-signal CMOS processing, 8.33
 VM-700, Tektronix, 5.19
 VM-5000, Tektronix, 5.19
 Vocoder, 1.10
 Voice activity detector, 8.138
 Voiceband ADC, sigma-delta, 8.139
 Voiceband codec, 8.65, 8.139
 Voiceband digital audio, beginnings, 8.59
 Voiceband telcom digital audio:
 diagram, 8.60
 standards, 8.60
 Voldicon VF7, 8-bit 1-MSPS sampling ADC, Adage, 1.24
 Voltage-adjustable regulator, 9.68-69
 Voltage compliance, 9.185
 voltage tolerance, 9.185
 internal, 9.195-196
 Voltage-controlled crystal oscillator, 6.91
 phase noise, 6.92
 Voltage converter:
 charge-pump, 9.74-75
 regulated output, 9.75-77
 Voltage doubler, 9.74
 Voltage drop:
 analysis, 9.28
 signal leads, 9.27-28
 Voltage follower protection circuit, 9.96-98
 Voltage inverter, 9.74
 Voltage-mode binary-weighted resistor DAC, 3.10
 Voltage reference, 1.35
 architectures, characteristics, 7.14
 capacitive decoupling, 6.81
 data converter, 6.79-81, 7.1-26
 DC specifications, table, 7.18
 design specifics, 6.81
 drift, 7.16, 7.18
 large capacitive load, 7.23
 line sensitivity, 7.17-18
 load sensitivity, 7.17-18
 low noise, 7.24-25
 noise, 7.18-20
 precision, 7.1-2
 issues, 7.1-2
 pulse current response, 7.22-24
 scaled reference, 7.20-22
 shunt, 7.2
 specifications, 7.15-25
 standard hookup, diagram, 7.15
 supply range, 7.17-18
 temperature drift, accuracy, table, 7.16
 three-terminal, 7.2
 tolerance, 7.15, 7.18
 transient loads, 7.23
 trim, 7.14
 two-terminal, 7.2
 types, 7.2-4
 Voltage regulator:
 block diagram, 7.30
 current overload, 7.29
 grounding, 9.78-81
 linear,

■ ANALOG-DIGITAL CONVERSION

- basics, 7.27-31, 9.66-68
- low dropout, 7.27-60
- low dropout, 9.70-74
 - adjustable voltage, 9.72-74
 - fixed voltage, 9.71-72
- pass device, types, 7.31
- pole-splitting topology, 7.42
- positive leg series style, 7.27
- three terminal, circuit, 7.28
- Voltage sensing, feedback, 9.27-28
- Voltage sensitivity, resistor, 9.14
- Voltage-to-frequency converter, see VFC
- Voltage tolerance, 9.185
 - voltage compliance, 9.185
 - internal, 9.195-196
- W**
 - Wadell, Brian C., 9.179
 - Wainwright Instruments, 9.202
 - Wainwright Instruments GmbH, 9.213
 - Wainwright Instruments Inc., 9.213
 - Waldhauer, F.D., 3.106
 - Waldhauer, W.D., 3.84
 - Waltman, Ron, 2.90
 - Water metering system, binary weighted, 1.2
 - Waveform generator, 5.17
 - WCDMA, 2.57-58
 - Weaver, Lindsay A., 8.175
 - Weg, H. Van de, 3.136
 - Weigh scale:
 - analysis, using AD7730, 8.6-7
 - design analysis, 8.6-12
 - load cell characteristics, 8.7
 - fullscale output, 8.7
 - Welland, D.R., 3.137
 - Wenzel Associates, Inc., 6.98, 9.39
 - Wesco film capacitors, 9.23
 - Western Electric, 1.14
 - Wheable, Desmond, 3.108
 - Wide code, errors, 2.20
 - Wideband, definition, 8.114
 - Wideband DCMA, 2.57-58
 - Wideband digital receiver, 8.114-126
 - Wideband radio:
 - transmission, 8.132-136
 - transmitter, 8.132
 - architectures, 8.132
 - Widlar, Bob, 1.24, 4.11, 7.26, 7.60
 - Wikner, J. Jacob, 2.117, 3.140, 5.91
 - Wikner, J.J., 8.157
 - Wilhelm, Tim, 5.88
 - Williams, Jim, 9.213
 - Williamson, Russell, 8.191
 - Williams, Tim, 9.178
 - Window function, 5.57-58
 - characteristics, 5.58
 - comparison, 5.59
 - frequency response, 5.58
 - Windowing, to reduce spectral leakage, 5.57
 - Wire inductance, 9.17
 - Wire microstrip, 9.165
 - Wireless air interface standards, wideband ADC requirements, table, 8.126
 - Wireless communication:
 - evolution, chart, 8.116
 - standards, 8.116
 - Wirewound resistor, 9.16
 - Witte, Robert A., 2.90
 - Wold, Ivar, 1.47, 3.108
 - Wold, Peter I., 3.36
 - Wong, James, 9.23, 9.178
 - Wong, Thick C., 5.88
 - Woodward, Charles E., 2.90, 3.104
 - Wooley, B.A., 3.137
 - Wooley, Bruce, 3.137
 - Word, 2.2
 - Worst harmonic, 2.46-48
 - data converter, 6.3
 - Worst other spur, 2.115
 - Wrathall repeater, germanium transistors, 1.14-15
 - Wrathall, L.R., 1.14-15, 1.19
 - Wurcer, Scott, 9.23
- X**
 - XFCB:
 - high-speed complementary bipolar process, 1.61
 - for producing converters, 4.12
 - XFET, 6.80
 - reference, 7.11-15, 7.16
 - characteristics, 7.14
 - XGA, electronic display standard, 8.86
- Y**
 - Yasuda, Y., 3.136
 - Yester, Francis R., Jr., 3.138
 - Yield, 4.22
 - Young, F.M., 1.31
 - Young, Joe, 3.107, 7.111
- Z**
 - Zeltex, Inc., 1.24, 1.33
 - Zener diode, 1.24, 1.35, 1.39, 1.41, 1.42, 3.17, 7.3-4, 7.11, 7.19, 9.96-97, 9.106, 9.109, 9.124
 - monolithic, 7.3
 - Zeoli, G.W., 2.90
 - Zero error, 2.97
 - Zero TC, 2.114
 - Zuch, Eugene L., 2.116, 3.139, 5.87, 5.90
 - Zumbahlen, Hank, 8.58

ANALOG DEVICES' PARTS INDEX

- AD2S90, 3.103
- AD29x, 7.20
- AD38x, 7.15
- AD39x, 7.15
- AD42x, 7.20
- AD43x, 7.20
- AD52xx-series, 1.58
- AD260, 9.114
- AD261, 9.114
- AD376, 1.53
- AD386, 7.92
- AD390, 1.50
- AD431, 7.25
- AD480, 4.12
- AD510, 7.21
- AD512, 7.21
- AD550, 1.25-26, 1.38, 1.41, 3.15-17, 4.6
- AD558, 1.50
- AD561, 1.35, 1.38
- AD562, 1.35, 1.38, 1.41, 1.42, 4.8
- AD563, 1.35, 1.41
- AD565, 1.35, 1.38, 1.39-40, 1.41, 4.8
- AD565A, 1.35
- AD569, 1.50
- AD570, 1.39
- AD571, 1.38, 1.40, 4.12
- AD572, 1.42, 4.6-7
- AD574, 1.39-40, 1.51, 1.59, 2.24, 3.41, 4.12, 6.49, 7.24, 7.92, 8.29
- AD574A, 1.63
- AD580, 7.5-6
- AD582, 7.92
- AD583, 7.92
- AD584, 7.6
- AD585, 7.92
- AD586, 7.16, 7.18, 7.20
- AD587, 7.19, 7.20
- AD588, 7.15-16, 7.17-18
- AD589, 7.5, 7.6, 7.20-21
- AD592, 8.184-185
- AD620, 8.9, 9.105-107, 9.161-162
- AD621, 9.161-162
- AD622, 9.161-162
- AD623, 9.52, 9.108, 9.161
- AD627, 9.108, 9.161
- AD629, 9.51, 9.98-99
- AD670, 1.51
- AD671, 1.60
- AD673, 1.51
- AD674, 1.51
- AD680, 7.5, 7.17
- AD684, 7.91, 7.92
- AD688, 7.17
- AD768, 6.73
- AD770, 1.52
- AD780, 6.23, 7.5, 7.15, 7.17-18, 7.18, 7.24, 8.47, 8.184-185
- AD781, 7.91
- AD783, 7.91, 7.92
- AD795, 9.100-101
- AD797, 6.15, 7.20, 9.105, 9.156
- AD817, 9.133
- AD820, 8.47, 9.97
- AD820/822, 7.21
- AD827, 9.156
- AD845, 9.156
- AD850, 1.25-26, 1.41, 3.16-17
- AD872, 1.61, 1.63
- AD974, 3.60, 6.18
- AD976, 6.18
- AD977, 6.18
- AD51xx-series, 1.58
- AD76xx-series, 6.18
- AD77xx-series, 6.15-16, 7.24-25, 9.30
- AD92xx-series, 6.21, 6.29-30
- AD158x-series, 7.18
- AD185x-series, 3.133
- AD746x-series, 6.18
- AD771x-series, 1.62, 1.63
- AD789x-series, 1.62, 6.18, 6.19
- AD813x-series, 6.31, 6.33-34, 6.75
- AD922x-series, 6.22
- AD974x, 8.136
- AD976x, 1.57
- AD976x-series, 6.70
- AD977x, 1.57
- AD977x-series, 3.22, 6.70
- AD978x, 8.136
- AD978x-series, 8.135
- AD985x, 8.171
- AD985x-series, 3.22, 9.138
- AD987x, 1.57
- AD1170, 3.96
- AD1175, 1.53, 1.54
- AD1332, 1.53
- AD1377, 1.53, 1.54
- AD1382, 1.64
- AD1385, 1.64
- AD1580, 7.5, 7.6-7, 7.20-21
- AD1582, 7.7
- AD1582-1585 series, 7.5, 7.7, 7.15, 7.17, 7.23
- AD1671, 1.60, 1.63
- AD1674, 1.59, 1.63
- AD1833, 8.70
- AD1833C, 8.70
- AD1834, 8.70
- AD1835A, 8.70
- AD1836A, 8.70
- AD1836AC, 8.70
- AD1837A, 8.70

■ ANALOG-DIGITAL CONVERSION

AD1838A, 8.70
AD1839A, 8.69-70, 8.70
AD1852, 8.67
AD1853, 3.134, 6.75-76, 8.67
AD1854J, 8.67
AD1854K, 8.67
AD1855, 8.67
AD1856, 1.50
AD1857, 1.57, 1.58
AD1858, 1.57, 1.58
AD1859, 1.57, 1.58
AD1860, 1.50
AD1862, 3.32-33
AD1865, 1.56
AD1871, 3.124, 8.66
AD1879, 3.123
AD1890, 8.72
AD1896, 8.72
AD1938, 8.70
AD1953, 8.68
AD1955, 3.134, 8.66, 8.67
AD5170, 8.54
AD5172, 8.53-54
AD5173, 8.53-54, 8.56
AD5227, 8.56
AD5231, 5.11
AD5235, 5.11, 8.52-53
AD5245, 8.50-51, 8.55
AD5246, 8.50-51
AD5247, 8.50-51
AD5251, 8.52
AD5252, 8.52
AD5253, 8.52
AD5254, 8.52
AD5300, 8.42
AD5310, 8.42
AD5320, 8.42-43
AD5322, 6.62-64
AD5340, 6.64-65
AD5379, 8.44-45
AD5380, 1.65-66
AD5381, 1.65-66
AD5382, 1.65-66
AD5383, 1.65-66
AD5390, 1.65
AD5391, 1.65
AD5516, 8.44
AD5533B, 8.45-46
AD5535, 9.210, 9.211
AD5541, 8.47
AD5545/AD5555, 6.74
AD5570, 8.43
AD5660, 8.43
AD6521, 8.141
AD6522, 8.141
AD6600, 8.111, 8.131
AD6620, 8.111, 8.131, 8.136
AD6622, 8.135, 8.136
AD6623, 8.135, 8.136
AD6624, 8.111, 8.131
AD6630, 8.131
AD6633, 8.135, 8.136
AD6634, 8.111, 8.131, 8.136
AD6635, 8.131, 8.136
AD6636, 8.131, 8.136
AD6640, 8.131
AD6640/44/45, 8.136
AD6644, 3.85, 8.131
AD6645, 1.65-66, 2.51-53, 2.56-57, 2.58,
2.64-66, 2.73, 3.77-78, 3.85, 4.12, 6.27-28,
6.38-40, 6.83, 6.97, 7.107, 8.117-120,
8.122-125, 8.128-129, 8.131, 8.146, 9.137-138
AD6650, 8.111, 8.131
AD6652, 8.111, 8.131
AD6654, 8.131
AD7001, 1.62, 1.63
AD7008, 1.57-58
AD7111, 2.112, 3.27-28
AD7226, 1.50
AD7240, 1.50
AD7245, 1.50
AD7311, 8.84
AD7450, 9.210
AD7450A, 6.35
AD7466, 6.17, 6.51-52
AD7467, 6.17, 6.51
AD7468, 6.17, 6.51
AD7482, 3.60
AD7484, 3.60
AD7490, 3.60
AD7500-series, 7.62
AD7520, 1.36, 1.38, 4.13
AD7524, 1.37-38, 1.38
AD7528, 1.50
AD7535, 1.50
AD7541, 1.36, 1.38
AD7545, 1.50
AD7546, 1.50
AD7550, 1.38, 1.40
AD7568, 1.56-57, 1.58
AD7570, 1.38, 1.40
AD7572, 1.51
AD7575, 1.51
AD7579, 1.51
AD7582, 1.51
AD7621, 1.65-66, 3.60, 3.61
AD7664, 1.65
AD7674, 1.65-66, 3.60-61, 6.42-43
AD7675, 3.61
AD7676, 3.61
AD7677, 3.60, 6.41-42
AD7678, 3.61
AD7679, 3.61
AD7710, 7.24-25
AD7730, 1.62, 1.63, 3.127-130, 6.15, 6.79,
8.2-6, 8.6-12, 8.9, 9.210
AD7732, 8.37
AD7734, 8.37

AD7738, 8.37
 AD7739, 8.36-38
 AD7793, 8.12-14
 AD7820, 1.51
 AD7821, 1.51
 AD7840, 1.50
 AD7846, 1.50
 AD7853/AD7853L, 6.55
 AD7853L, 6.55-56
 AD7854/AD7854L, 6.59-61
 AD7865, 8.39-40
 AD7870, 1.51
 AD7871, 1.51
 AD7873, 8.102
 AD7880, 1.59, 1.63
 AD7890-10, 6.18-19, 9.109
 AD7908/AD7918/AD7928, 8.34-35
 AD7928, 3.60
 AD7938/AD7939, 8.35-36
 AD7943, 3.2
 AD8001, 9.207-209
 AD8016, 9.130-133
 AD8017, 9.133
 AD8017AR, 9.127-130
 AD8018, 7.82
 AD8021, 6.41-43
 AD8027, 6.8, 6.23
 AD8028, 6.8, 6.30
 AD8031, 6.23, 6.43
 AD8032, 6.30
 AD8038, 6.37
 AD8055, 6.72, 6.74
 AD8057, 6.12, 6.13-15, 6.23, 9.133
 AD8058, 6.13-15, 6.29-30, 9.133
 AD8061, 6.23, 6.72-73
 AD8062, 6.30
 AD8074, 7.85
 AD8075, 7.85
 AD8091, 6.23
 AD8092, 6.30
 AD8108, 7.85
 AD8109, 7.85
 AD8110, 7.82, 7.85
 AD8111, 7.82, 7.85
 AD8113, 7.82, 7.85
 AD8114, 7.82, 7.85
 AD8115, 7.82, 7.85
 AD8116, 7.82-83, 7.85
 AD8130, 6.34
 AD8131, 6.35
 AD8132, 6.34, 6.35
 AD8137, 6.35-36
 AD8138, 6.35-37
 AD8139, 6.35, 6.38, 6.38-39, 6.42-44
 AD8150, 7.85
 AD8151, 7.85
 AD8152, 7.83-84, 7.85
 AD8170, 7.80, 7.85
 AD8174, 7.80, 7.82, 7.85
 AD8180, 7.80, 7.85
 AD8182, 7.80, 7.85
 AD8183, 7.80-81, 7.82
 AD8184, 7.82, 7.85
 AD8185, 7.80-81, 7.82, 7.85
 AD8186, 7.80-81, 7.82, 7.85
 AD8187, 7.80-81, 7.82, 7.85
 AD8346, 4.25-26
 AD8349, 8.134-135, 8.136
 AD8350, 8.131
 AD8351, 6.38-40
 AD8370, 6.41
 AD8402, 1.58
 AD8403, 1.58
 AD8515, 6.18
 AD8517, 6.18
 AD8531, 6.7
 AD8531/32/34, 7.21
 AD8532, 6.7
 AD8534, 6.7
 AD8541/42/44, 7.21
 AD8551, 9.50, 9.56
 AD8610, 9.103
 AD8628, 6.74
 AD8631, 6.18
 AD8800, 1.58
 AD9000, 1.52
 AD9002, 1.52
 AD9003, 1.53
 AD9005, 1.53, 1.54
 AD9006/AD9016, 1.52
 AD9008, 1.58
 AD9012, 1.52
 AD9014, 1.64
 AD9020, 1.52
 AD9028/AD9038, 1.52
 AD9032, 1.65-66
 AD9042, 1.61, 1.63, 1.64, 3.75-76, 3.85, 4.12, 7.106-107
 AD9048, 1.52
 AD9054, 1.62
 AD9054A, 3.86
 AD9058, 1.52
 AD9060, 1.52
 AD9100, 7.92
 AD9101, 7.92
 AD9109, 7.82
 AD9220, 1.61, 1.63
 AD9221, 1.61, 1.63
 AD9223, 1.61, 1.63
 AD9225, 3.76, 6.20-21, 6.24
 AD9226, 2.49, 8.131, 8.136
 AD9229, 6.52-54
 AD9235, 3.69, 3.76-77, 6.36-37
 AD9235/38, 8.131
 AD9236, 5.43-44
 AD9244, 8.136
 AD9245, 9.134-135
 AD9245/AD9444, 8.131

■ ANALOG-DIGITAL CONVERSION

- AD9289, 6.52-54
AD9410, 3.51-53
AD9430, 2.60, 3.69, 3.76-77, 5.61-62, 5.70,
6.26-27, 6.57-59, 8.146, 9.136-137, 9.176, 9.211
AD9432, 8.131
AD9432/33, 8.136
AD9433, 6.41
AD9444, 8.136
AD9444/45, 8.131
AD9480, 3.49
AD9700, 1.50
AD9712, 1.57
AD9720, 1.57
AD9726, 6.66
AD9744, 5.22-23, 8.135
AD9754, 8.136
AD9772, 8.135
AD9772A, 8.135, 8.136
AD9773, 2.89
AD9775, 2.89, 3.22
AD9777, 2.84-86, 2.89, 4.25-26, 8.135, 9.138
AD9784/86, 8.135
AD9786, 8.133-134
AD9814, 8.99
AD9816, 8.99
AD9822, 8.99
AD9826, 8.99
AD9830, 8.168
AD9831, 8.168
AD9832, 8.168
AD9833, 8.167, 8.168
AD9834, 8.166-168, 8.168
AD9835, 8.168
AD9850, 1.57, 8.171
AD9851, 5.22, 8.171
AD9852, 8.171
AD9853, 8.174
AD9854, 8.171
AD9856, 8.174
AD9857, 8.171, 8.173, 8.174
AD9858, 1.65-66, 8.168-171, 8.171
AD9859, 8.173
AD9860/AD9862, 4.29
AD9877, 4.23, 4.25
AD9879, 4.23, 4.25
AD9887A, 8.93-94
AD9888, 8.91-92
AD9898, 8.99
AD9951, 8.173
AD9952, 8.173
AD9953, 8.173
AD9954, 8.171-172, 8.173
AD10242, 1.64
AD10678, 1.65-66
AD12400, 1.65-66, 8.152-154, 8.152-155
AD74122, 8.65
AD20msp430, 8.140-141
ADC-12QZ, 1.44, 1.46, 4.6
ADC-12U, 1.24, 1.25
ADC80, 1.43
ADC1130, 1.46
ADC1140, 1.53
ADE775x-series, 1.63, 8.22
ADE7755, 8.23-25
ADF41xx-series, 6.92
ADF4001, 6.92
ADF4360, 6.93
ADG2xx-series, 7.85
ADG4xx-series, 7.85
ADG5xx-series, 7.85
ADG6xx-series, 7.85
ADG7xx-series, 7.85
ADG8xx-series, 7.85
ADG9xx-series, 7.85
ADG200-series, 7.62
ADG201-series, 7.62
ADG412, 7.71
ADG438F, 7.85, 9.99
ADG439F, 7.85, 7.89, 9.99
ADG465, 9.98, 9.107, 9.110
ADG466, 9.98, 9.110-111
ADG467, 9.98, 9.110
ADG508F, 7.85, 7.89, 9.99
ADG509F, 7.85, 7.89, 9.99
ADG528F, 7.85, 7.89
ADG708, 7.68, 7.72
ADG725, 7.61
ADG726, 7.61
ADG731, 7.61
ADG732, 7.61
ADG801/ADG802, 7.64
ADG918, 7.78-79
ADG919, 7.78-79
ADG3xxx-series, 7.85
ADG12xx-series, 7.85
ADG14xx-series, 7.85
ADG32xx-series, 7.84
ADG314x-series, 9.189
ADG324x-series, 9.191
ADG3231, 9.188-189, 9.191
ADG3233, 9.191
ADG3241, 9.190
ADG3242, 9.190
ADG3243, 9.190
ADG3245, 9.190
ADG3246, 9.190, 9.194
ADG3247, 9.190
ADG3248, 9.190
ADG3249, 9.190
ADG3257, 9.186-189
ADMxxx-E series, 9.124
ADM1023, 8.19-22
ADM8830, 9.75
ADM8839, 9.75
ADM8840, 9.75
ADP33xx-series, 9.70-71
ADP330x-series, 7.39-40
ADP333x-series, 7.39-40

ADP3300, 7.43-46, 7.48, 9.71-72
 ADP3300-5, 7.46
 ADP3301, 7.43-44, 9.71-72
 ADP3302, 7.43-44
 ADP3303, 7.43-44, 9.72
 ADP3303A, 9.72
 ADP3307, 7.43-44, 9.72
 ADP3308, 7.44, 9.72
 ADP3309, 7.44, 9.72
 ADP3310, 7.51-52, 7.54, 7.57, 7.58-59, 9.78-80
 ADP3310-3.3, 9.77-78
 ADP3310-5, 7.53
 ADP3330, 7.44, 7.49, 9.72
 ADP3331, 7.44, 7.49, 9.72-73
 ADP3333, 7.44, 7.50, 9.72
 ADP3334, 7.44, 9.72
 ADP3335, 7.44, 7.50, 9.72
 ADP3336, 7.44, 7.50, 8.56, 9.72
 ADP3338, 7.44, 7.50-51, 9.72
 ADP3339, 7.44, 7.50, 9.72
 ADP3605, 9.76
 ADP3607, 9.76
 ADP3607-5, 9.77
 ADR01, 7.5, 7.15, 7.18, 7.20
 ADR02, 7.5, 7.15, 7.18, 7.20
 ADR03, 6.74, 7.5, 7.15, 7.18, 7.20
 ADR29x, 7.15, 7.17-18
 ADR29x-series, 7.23
 ADR38x, 7.17-18
 ADR38x-series, 7.5, 7.8
 ADR39x, 7.17-18
 ADR39x-series, 7.5, 7.8
 ADR42x, 7.18
 ADR43x, 7.15, 7.17-18
 ADR43x-series, 7.23
 ADR290, 7.12
 ADR290-ADR293 series, 7.12
 ADR291, 7.12
 ADR292, 7.12
 ADR292E, 7.20
 ADR293, 7.12
 ADR380, 7.9
 ADR381, 7.9
 ADR390, 6.35, 7.10
 ADR391, 7.10
 ADR392, 7.10
 ADR395, 7.10
 ADR430-ADR439 series, 7.13
 ADR431, 6.23, 6.42, 7.24-25
 ADR433, 7.24
 ADR510, 7.5, 7.7, 7.21
 ADR512, 7.5, 7.7, 7.20-21
 ADR520, 7.7
 ADR525, 7.7
 ADR530, 7.7
 ADR540, 7.7
 ADR545, 7.7
 ADR550, 7.7
 ADSP-21xx-series, 6.62
 ADSP-218x, 8.141
 ADSP-2106L, 9.170
 ADSP-2189, 6.60-61
 ADSP-2189M, 6.55-56, 6.63-65
 ADSP-21160, 9.43-44
 ADSX34, 7.85
 ADT7301, 8.17-19
 ADu7xxx-series, 8.187-190
 ADuC7xxx-series, 8.187-190
 ADuC8xxx-series, 8.187-190
 ADuC70xx-series, 8.189
 ADuC702x-series, 8.188
 ADuC812, 8.178, 8.180, 8.186
 ADuC812 MicroConverter, 1.63
 ADuC814, 8.179-180, 8.186
 ADuC816, 8.183, 8.186
 ADuC824, 8.183, 8.186
 ADuC831, 8.178, 8.180, 8.186
 ADuC832, 8.178, 8.180, 8.186
 ADuC834, 8.180-182, 8.183, 8.186
 ADuC836, 8.183, 8.186
 ADuC841, 8.178, 8.180, 8.186
 ADuC842, 8.178, 8.180, 8.186
 ADuC843, 8.178, 8.180, 8.186
 ADuC845, 8.180-182, 8.183, 8.186
 ADuC847, 8.181, 8.183, 8.186
 ADuC848, 8.181, 8.183, 8.186
 ADuC7020, 8.188
 ADuC7021, 8.188
 ADuC7022, 8.188
 ADuC7024, 8.188
 ADuC7026, 8.188
 ADuM1100A, 9.112-114
 ADuM1100B, 9.112-114
 ADuM1300, 9.113
 ADuM1301, 9.114
 ADuM1400, 9.113
 ADuM1401, 9.114
 ADV453, 1.50
 ADV471, 1.50
 ADV476, 1.50
 ADV478, 1.50
 ADV7125, 8.88-89
 ADV7160/ADV7162, 8.90
 ADV7183A, 8.82-83
 ADV7310, 8.83-84
 AMP03, 9.51, 9.100
 CAV-1040, 1.53, 1.54
 CAV-1220, 1.53, 1.54
 DAC-12QZ, 1.46, 4.8
 DAC08, 1.38, 1.41
 DAC80, 1.41-43
 DAC1138, 1.46
 HAS-1201, 1.53
 HAS-1202, 1.43
 HAS-1409, 1.53
 HDG-series, 1.53
 HDS-1240E, 1.53
 HDS-1250, 1.43

■ ANALOG-DIGITAL CONVERSION

HTC-0300, 1.43, 7.92	OP275, 6.76
HTS-0025, 1.43, 7.92	OP279, 6.7, 7.21, 7.22
LOGDAC, 2.112	OP281/481, 7.21
MAS-1202, 1.44	OP284, 6.7, 7.21
MOD-815, 1.44, 1.45, 3.63, 3.64	OP291, 6.7
MOD-1020, 1.45	OP297, 9.156
MOD-1205, 1.45	OP484, 6.7
MOD-4100, 3.50	OP491, 6.7
MOSES-8, 7.61	OP777, 7.21, 9.98
OP27, 7.20, 9.104	OP1177, 6.15-16
OP42, 9.156	REF01, 7.5
OP80, 9.156	REF02, 7.5
OP113, 7.20	REF03, 7.5
OP113EP, 7.20	REF43, 7.15, 7.17
OP177, 6.15, 9.13	REF19x, 7.15, 7.17, 7.18, 7.23
OP181/281/481, 7.22	REF19x-series, 7.5
OP184, 6.7, 7.20	REF195, 7.15, 7.17, 7.18
OP184/284/484, 7.21	SHA1, 7.92
OP191, 6.7	SHA2, 7.92
OP193/293, 7.21	TMP05/TMP06, 8.14-17
OP193/293/493, 7.22	TMP06, 8.16
OP196/296/496, 7.21	Transmit TxDAC family, 2.85
OP200, 9.156	TxDAC family, 1.55
OP213, 7.71	VHS-630, 3.49
OP249, 9.156	VHS-675, 3.49